Form 3160-5 (August 1999)

1. Type of Well

Oil Well Gas Well Other

## **UNITED STATES** DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPLICATE - Other instructions on reverse side.

SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to re-enter an abandoned well. Use form 3160-3 (APD) for such proposals.

FORM APPROVED
OMB NO. 1004-0135
Expires: November 30, 2000

15. Lease Serial No. NMSF077952

8. Well Name and No. J C GORDON D 3E

6.	If Indian, Allottee or Tribe Name	

7. If Unit or CA/Agreement, Name and/or No.

2. Name of Operator XTO ENERGY INC		OLLY PERKINS -Mail: Regulatory@xtoe	9. API Well No. 30-045-24726-00-S1					
3a. Address 2700 FARMINGTON AVE., BI FARMINGTON, NM 87401	3b. Phone No. (include area code) Ph: 505.324.1090 Ext: 4020 Fx: 505.564.6700		10. Field and Pool, or Exploratory BASIN DAKOTA					
4. Location of Well (Footage, Sec., 7	., R., M., or Survey Description)			11. County or Parish, and	State			
Sec 23 T27N R10W NENW 0 36.56662 N Lat, 107.86795 W				SAN JUAN COUN	ITY, NM			
12. CHECK APPI	ROPRIATE BOX(ES) TO	INDICATE NATUR	E OF NOTICE, R	EPORT, OR OTHER	DATA			
TYPE OF SUBMISSION	TYPE OF ACTION							
Notice of Intent	□ Acidize	□ Deepen	□ Produc		☐ Water Shut-Off			
_	Alter Casing	☐ Fracture Treat	☐ Reclar	nation	☐ Well Integrity			
☐ Subsequent Report	🛮 Casing Repair	☐ New Construce	ion 🔲 Recom	plete	Other			
☐ Final Abandonment Notice	Change Plans	Plug and Abar	don 🔲 Tempo	orarily Abandon				
	Convert to Injection	□ Plug Back	Water	Disposal				
Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the site is ready for final inspection.)  XTO Energy Inc. proposes to do a casing repair in the following manner:  1. MIRU PU. 2. TOH with 2-3/8" tubing. 3. TIH with Baker 2-7/8" float shoe with wiper plug in place, 4 jts 2-7/8" tubing (Baker Locked), Baker Model D liner hanger, 2-7/8" x 1' perf sub, Baker 2-7/8" float collar and 206 jts 2-7/8" tubing. Set liner hanger at 6,600' with EOT at 6,728'.  4. MIRU BJ cement trucks. Circulate bottoms up ( 91 bbls, 2% KCl water). Pump 20 sx Premiun Lite high strength cement with 3#/sx CSE, 0.2% CD-32, 0.7% FL-52, 5% A-10 & 4#/sx LCM-1 (10.5#/gals, 4.06 cuft/sx). Tail in with 175 sx Premium Lite high strength cement with 3#/sx CSE, 0.2% CD-32, 0.7% FL-52, 5% A-10 & 4#/sx LCM-1 (12.5#/gals, 2.11 cuft/sx). Wash up lines. Drop 2-7/8" wiper plug and displace cement to float collar with 38.2 bbls fresh water. RDMO BJ cement truck. RDMO								
Electronic Submission #30277 verified by the BLM Well Information System For XTO ENERGY INC, sent to the Farmington Committed to AFMSS for processing by JM LOVATO on 05/07/2004 (04JXL0236SE)								
Name (Printed/Typed) HOLLY P	ERKINS	Title	REGULATORY CO	OMPLIANCE TECH				
Signature (Electronic	Submission)	Date (	5/04/2004					
	THIS SPACE FO	R FEDERAL OR S	TATE OFFICE U	JSE				
Approved By JIM LOVATO  Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease			FROLEUM ENGIN	NEER	Date 05/07/2004			
which would entitle the applicant to cond Title 18 U.S.C. Section 1001 and Title 43	<del> </del>		armington	moles to any demonstrate	gangy of the Maited			
States any false, fictitious or fraudulent	statements or representations as	to any matter within its jur	isdiction.	make to any department or a	gency of the United			
** BLM REVISED ** BLM REVISED ** BLM REVISED **								

## Additional data for EC transaction #30277 that would not fit on the form

## 32. Additional remarks, continued

PU.
5. WOC 48 hours.
6. MIRU CT UT. RIH with 2-1/4" mill, 1.69" NAVI-Drill mud motor and 1-1/4" CT. Tag TOC and drill out wiper plug, cement and wiper plug with float shoe. RIH to PBTD. Circ well. POH with mud motor. RDMO CT UT.