Form 3160-5 (September 2001)

UNITED STATES DEPARTMENT OF THE INTERIOR

FORM APPROVED

1/	OMB NO. 1004-0135
/	Expires January 31, 2004

SUNDRY NOTICES	AND MANAGEMENT AND REPORTS ON WELLS proposals to drill or to re-enter an m 3160-3 (APD) for such proposals	5. Lease Serial No. MMNM 28277 6. If Indian, Allottee or Tribe Name AY AM 0
1. Type of Well	Other Instructions on reverse side	7. If Unit or CA/Agreement, Name and/or No.
	3b. Phone No. (include of 505-325-6800	Arboles 20A 1Y 9. API Well No. 30-039-23562
12. CHECK APPROPRIATE	BOX(ES) TO INDICATE NATURE OF	
TYPE OF SUBMISSION	יו	PE OF ACTION
Notice of Intent X Subsequent Report Final Abandonment Notice	Acidize Deepen Alter Casing Fracture Treat Casing Repair New Construction Change Plans X Plug and Abandon Convert to Injection Plug Back	Production (Start/Resume) Reclamation Well Integrity Recomplete Temporarily Abandon Water Disposal

Describe Proposed or Completed Operation (clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recomplete horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the final site is ready for final inspection.)

This well was plugged and abandoned on 9/27/03.

9/26/03: MIRU. ND wellhead, NU BOP. TOH with 2 3/8" tbg. RIH with bit and casing scraper 3700'. RIH and set 7" cement retainer at 3550'. Test tbg to 1000 psi and circulate hole. Test casing to 500 psi OK. Sting into retainer.

9/27/03: RU BJ. Plug #1, mix and pump 153 sks 15.6# cement below retainer, sting out and pump 48 sks on top of cement retainer at 3550'. TOH to 2400'. Plug #2, mix and pump 28 sks cement a balanced plug from 2300' to 2400'. TOH and lay down tbg to 252'. Plug #3, mix and pump 48 sks cement from 252' to surface, circulate good cement to surface. TOH laying down tbg. RD BJ. ND BOP, cut off wellhead. RDMO.

14. I hereby certify that the foregoing is true and correct Name (Printed/Typed)	itle		
Don Graham	Production_Superintendent		
In Aran	Pate 5/7/04		
THIS SPACE FOR FEDERAL	OR STATE OFFICE USE	ACCEPTED FOR PECCAS	
Approved by	Title	MAY Pag 2004	
Conditions of approval, if any, are attached. Approval of this notice does not warrant of certify that the applicant holds legal or equitable title to those rights in the subject leas which would entitle the applicant to conduct operations thereon.	r Office	FARMINGTON FIELD UTFICE	

Title 18 U.S.C. Section 1001, and Title 43 U.S.C. Section 1212, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.