UNITED STATES

FORM APPROVED

	UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT					FORM APPROVED MB No. 1004-0135 ires November 30, 2000	
1	SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals (APD) for such						
	31/RMIT IN TRIPLICATE - Other Instructions on reverse side						
	Control Well Cons Well Cother WIW					8. Well Name and No. Navajo TI "F" #101	
) 	Address		3b. Phone No. (in	3b. Phone No. (include area code)		9. API Well No. 300451111600S1	
		nington, N. M. 87499	(505) 326-1	(505) 326-1163		10. Field and Pool, or Exploratory Area Horseshoe Gallup	
	SAN 17W	Sec., T., R., M., or Survey Descrip SEC QTR NWNW	nton)		11. County or		
	12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA						
	TYPE OF SUBMISSION			TYPE OF ACTION	TYPE OF ACTION		
>	Subsequent Report	Acidize Atter Casing Casing Repair Change Plans Convert to Injection	Deépen Fracture Treat New Constructi Plug and Aband Plug Back		C Abandon	Water Shut-Off Well Integrity Other	
because of the subsequent recomplete horizontally, give subsurface locations and measured and true vertical depths of all pertinent may be allocated the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports shall be filed to be a multiple completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 shall be filed only after all requirements, including reclamation, have been completed, and that the site is ready for final inspection.) See Coll & Gas, Inc. plugged and abandoned this well on February 17, 2004. Coll & Gas, Inc. plugged and abandoned this well on February 17, 2004. Coll & Establish circulation with 18 bbls water, circulate well clean. Plug #1 with 51 sxs cement w/2% CaC12 from 163' to the Gallup perforations. TOH and LD tubing. Shut in well and WOC. Pressure test casing to 500#, hels OK RIJ						eports shall be filed within 30 days, a Form 3160.4 shall be filed once en completed, and the operator has	
	The fill the Gallup perforations. TOH and LD tubing. Shut in well and WOC. Pressure test casing to 500#, hels OK RU The fill and tag cment at 690'. Perforate 2 holes at 90'. Establish circulation out bradenhead with total 13 bbls of water The fill with 41 sxs cement pumped down the 4-1/2" casing from 90' to surface, circulate good cement out bradenhead. The fill with 41 sxs cement pumped down the 4-1/2" casing from 90' to surface, circulate good cement out bradenhead. The fill with 41 sxs cement pumped down the 4-1/2" casing at surface in annulus. Mix 33 sxs cement to The fill with 41 sxs cement out bradenhead. The fill with 41 sxs cemen						
	Servey certify that the fore Name (Printed/Typed) Gina M.		~ Tiu	e VI	CE-PRESIDEI	NT	
	Ain		E FOR FEDERAL O	e IRISTATE OFFICE U)5/24/04 SE		
			all and the second seco	Title	Dat	ė	
	the applicant holds	are attached. Approval of this r legal or equitable title to those to conduct operations thereon.	notice does not warrant or rights in the subject leas	r	ACCEPI	TED FOR RECORD	

13. U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United theory may false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction. JUN 0 1 2004