This form is <u>not</u> to be used for reporting packer leakage tests in Southeast New Mexico

NEW MEXICO OIL CONSERVATION DIVISION

Operator Williams Exploration and Production Lease Name Rosa UNIT

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST Well No. 31 B

Location Of V	Well: Unit Letter	Sec	<u>/ク</u> Twp	_3,	<u>/a/</u> Rge	5 h	∠_ API # 30-0 <u>-3</u> ∠	0392657900
	Name of Re	-	Type of Prod.		_	Method of Prod.	Prod. Medium	
ļ	 		(Oi	(Oil or Gas)		<u> (</u>	Flow or Art. Lift)	(Tbg. 0r Csg.)
Upper Completion	Me.Ca	CA	CAS			Flow	Tha	
Lower		F (1 6 -						
Completion	Me.(A DAho)	TD	GA	GAC			Flow	Tha
				/			<u> </u>	
•		P :	re-Flow Shut-	-In P	ressure Dat	а		
Upper	Hour, Date, Shut			Length of Time Shut-In			Press. Psig	Stabilized? (Yes or No)
Completion	10:30 40		, –	n2 hes		1	165 4	Ves
Lower	Hour, Date, Shut			of Time Shut-In			Press. Psig	Stabilized? (Yes or No)
Completion	10:30 4.		, -	hR			570 A	405
		V.:						
			Flow T	est N	o. 1			
Commenced a		0:30 4-26-0		Zon			per or Lower):	wek
Time			essure	Prod. Zo			Remarks	
(Hour, Date)	Since*	Upper Compl.	Lower Comp	<u>əl.</u>	Temp.		<u> </u>	
10:30 4-27-4	24100	167#	118#		700			
10:304.2804		176#	1124		680	680		11 1/20
0304-29		170#	120 ×			A A		
							12 ox 63	2004
							Carrie	्र १५ 😁

roduction rate during test

)il: _		BOPD based on	Bbls. In		Hrs	Grav	•	GOR	
<u> </u>	150	MCEPD	. Test thru (Orifice or M	ator). ~	C'E'AD				

Mid-Test Shut-In Pressure Data

Upper	Hour, Date, Shut-In	Length of Time Shut-In	SI Press. Psig	Stabilized? (Yes or No)
Completion		·	· .	
Lower	Hour, Date, Shut-In	Length of Time Shut-In	SI Press. Psig	Stabilized? (Yes or No)
Completion		·		

(Continue on reverse side)

Flow Test No. 2

			TIOW 16					
Commenced a	at (hour, date)**			Zone producing (U	Ipper or Lower):			
Time Lapsed Time		<u>Pressure</u>		Prod. Zone	Remarks			
(Hour, Date)	Since**	Upper Compl.	Lower Compl	. Temp.				
_								
					·			
Production rate					-	205		
						GOR		
Remarks:	MICFFI); Test thru (Offi	ice of Meter):					
•				implete to the best o	_			
Approved MAY 1 2 2004 20				Operator Williams freduction By Jeff Gorn, Title Tech III				
New Mexico Oil	Conservation Di	vision		D				
	////			Бу <u>Је</u>	+ 60000y			
By Cha	h'/			Title Tech	4 171			
TitleOEPUTY OIL & GAS INSPECTOR, DIST.				E-mail Address				
				Date A.	29-01			

Northwest New Mexico Packer Leakage Test Instructions

- 1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- 2. At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in case of a gas well and 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.
- 5. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.

- 6. Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hour tests: immediately prior to the beginning of each flow-period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.

24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.

8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 11-16-98, with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).