

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

RECEIVED

Sundry Notices and Reports on Wells

2004 APR 30 PM 5:51

1. Type of Well
GAS

070 FARMINGTON, NM

Lease Number
NMSF-077652

If Indian, All. or
Tribe Name

2. Name of Operator
BURLINGTON
RESOURCES OIL & GAS COMPANY

7. Unit Agreement Name

3. Address & Phone No. of Operator
PO Box 4289, Farmington, NM 87499 (505) 326-9700

8. Well Name & Number
East #12

4. Location of Well, Footage, Sec., T, R, M
1650' FSL, 990' FEL, Sec. 4, T-31-N, R-12-W, NMPM

9. API Well No.
30-045-20486

10. Field and Pool
Aztec Pictured Cliffs

11. County and State
San Juan Co, NM

25

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission

Type of Action

<input checked="" type="checkbox"/> Notice of Intent	<input type="checkbox"/> Abandonment	<input type="checkbox"/> Change of Plans
<input type="checkbox"/> Subsequent Report	<input type="checkbox"/> Recompletion	<input type="checkbox"/> New Construction
<input type="checkbox"/> Final Abandonment	<input checked="" type="checkbox"/> Plugging Back	<input type="checkbox"/> Non-Routine Fracturing
	<input type="checkbox"/> Casing Repair	<input type="checkbox"/> Water Shut off
	<input type="checkbox"/> Altering Casing	<input type="checkbox"/> Conversion to Injection
	<input type="checkbox"/> Other -	

13. Describe Proposed or Completed Operations

It is intended to squeeze the subject well according to the attached procedure.

Verbal approval received from Steve Mason, BLM, on 3/1/04 to squeeze the csg.

CONDITIONS OF APPROVAL
Adhere to previously issued stipulations.

14. I hereby certify that the foregoing is true and correct.

Signed Tammy Wimsatt Title Regulatory Specialist Date 4/29/04

(This space for Federal or State Office use)
APPROVED BY Jim Lovato Title Petr. Eng. Date 6/1/04
CONDITION OF APPROVAL, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

NMACD

OPERATOR

BURLINGTON

RESOURCES

IMPLEMENTATION TEAM

SUNDRY SQUEEZE PROCEDURE

EAST #12

1650' S, 990' E
Unit I, Section 25, T31N, R12W
San Juan County, NM
LAT: 36 DEG 52.08'
LONG: 108 DEG 2.64'

Isolated holes between 1260' – 1292'. Injected at 1.5 bpm with 1500 psi.

1. TIH with packer and set at +/- 1230'.
2. Squeeze off holes with 150 sxs Type III cement with 2% CaCl₂.
3. WOC overnight.
4. Drill out cement. Test squeeze to 500 psi for 15 minutes.
5. Resqueeze as required.
6. Perform Pictured Cliffs restimulation.