

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
OMB NO. 1004-0135
Expires: November 30, 2000

SUNDRY NOTICES AND REPORTS ON WELLS
Do not use this form for proposals to drill or to re-enter an abandoned well. Use form 3160-3 (APD) for such proposals.

SUBMIT IN TRIPLICATE - Other instructions on reverse side.

1. Type of Well <input type="checkbox"/> Oil Well <input checked="" type="checkbox"/> Gas Well <input type="checkbox"/> Other		7. If Unit or CA/Agreement, Name and/or No.
2. Name of Operator BP AMERICA PRODUCTION CO		8. Well Name and No. WARREN LS 12S
3a. Address P. O. BOX 3092 HOUSTON, TX 77253		9. API Well No. 30-045-32283-00-X1
3b. Phone No. (include area code) Ph: 281.366.4081 Fx: 281.366.0700		10. Field and Pool, or Exploratory BASIN FRUITLAND COAL
4. Location of Well (Footage, Sec., T., R., M., or Survey Description) Sec 24 T28N R9W NWSE 1750FSL 1945FEL 36.38700 N Lat, 107.44300 W Lon		11. County or Parish, and State SAN JUAN COUNTY, NM

12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION	TYPE OF ACTION
<input checked="" type="checkbox"/> Notice of Intent	<input type="checkbox"/> Acidize
<input type="checkbox"/> Subsequent Report	<input type="checkbox"/> Deepen
<input type="checkbox"/> Final Abandonment Notice	<input type="checkbox"/> Fracture Treat
	<input type="checkbox"/> New Construction
	<input type="checkbox"/> Plug and Abandon
	<input type="checkbox"/> Plug Back
	<input type="checkbox"/> Production (Start/Resume)
	<input type="checkbox"/> Reclamation
	<input type="checkbox"/> Recomplete
	<input type="checkbox"/> Temporarily Abandon
	<input type="checkbox"/> Water Disposal
	<input type="checkbox"/> Water Shut-Off
	<input type="checkbox"/> Well Integrity
	<input checked="" type="checkbox"/> Other Change to Original APD

13. Describe Proposed or Completed Operation (clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recompleat horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompleat in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the site is ready for final inspection.)

Original APD was submitted on 4/6/04 and approved 5/20/04.

The original surface casing was permitted for 8 5/8" 32.3# with hole size 12.5. The production casing was permitted for 7" 20.0# with hole size of 8.75.


BP America requests change to size and weight of casing. We respectfully request to run surface casing of 8 5/8" 20# x42 STC in a 12 1/4" hole and the production casing changed to 5 1/2" 15.5# J-55 STC in a 7 7/8" hole.

Please see attached amended cement report.

Verbal approval given by Adrienne Garcia to Harald Jordan on 5/25/04.

14. I hereby certify that the foregoing is true and correct. Electronic Submission #31142 verified by the BLM Well Information System For BP AMERICA PRODUCTION CO, sent to the Farmington Committed to AFMSS for processing by ADRIENNE GARCIA on 06/14/2004 (04AXG2627SE)	
Name (Printed/Typed) CHERRY HLAVA	Title AUTHORIZED REPRESENTATIVE
Signature (Electronic Submission)	Date 05/26/2004

THIS SPACE FOR FEDERAL OR STATE OFFICE USE

Approved By 	Title Petr. Eng	Date 6/14/04
Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.		
Office		

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

Cementing Program

Well Name: **Warren LS 12S**
 Location: **Sec 24 - 28N - 09W, 1750' FSL, 1945' FEL**
 County: **San Juan**
 State: **New Mexico**

Field: **Basin Fruitland Coal**
 API No.
 Well Flac
 Formation: **Fruitland Coal**
 KB Elev (est) **5867**
 GL Elev. (est) **5854**

Casing Program:

Casing String	Est. Depth (ft.)	Hole Size (in.)	Casing Size (in.)	Thread	TOC (ft.)	Stage Tool Or TOL (ft.)	Cmt Cir. Out (bbl.)
Surface	120	12 1/4	8 5/8	ST&C	Surface	NA	
Production -	2300	7 7/8	5 1/2	LT&C	Surface	NA	

Casing Properties:

Casing String	Size (in.)	Weight (lb/ft)	Grade
Surface	8 5/8	20	H-40 K-55
Production -	5 1/2	15.5	K-55 J-55

Mud Program

Apx. Interval (ft.)	Mud Type	Mud Weight	Recommended Mud Properties Prio Cementing:
0 - SCP	Water/Spud	8.6-9.2	PV <20 YP <10 Fluid Loss <6
SCP - TD	Water/LSND	8.6-9.2	
SCP - TD	Gas/Air/N2/Mist	NA	

Cementing Program:

	Surface	Production
Excess %, Lead	100	40
Excess %, Tail	NA	40
BHST (est deg. F)	75	120
Special Instructions	1,6,7	2,4,6

1. Do not wash pumps and lines.
2. Wash pumps and lines.
3. Reverse out
4. Run Blend Test on Cement
5. Record Rate, Pressure, and Density on 3.5" disk
6. Confirm densitometer with pressurized mud scales
7. 1" cement to surface if cement is not circulated.
8. If cement is not circulated to surface, run temp. survey 10-12 hr. after landing plug.

Notes:

*Do not wash up on top of plug. Wash lines before displacing production cement job to minimize drillout.

Surface:

Preflush	20 bbl.	FreshWater	
Slurry 1	80 sx Class C Cement		99 cuft
TOC@Surface	+ 2% CaCl2 (accelerator)		
			0.4127 cuft/ft OH

Slurry Properties:	Density (lb/gal)	Yield (ft3/sk)	Water (gal/sk)
Slurry 1	15.2	1.27	5.8

Casing Equipment: 8-5/8", 8R, ST&C
 1 Guide Shoe

Cementing Program

1 Top Wooden Plug
 1 Autofill insert float valve
 Centralizers, 1 per joint except top joint
 1 Stop Ring
 1 Thread Lock Compound

Production:

Fresh Water 10 bbl CW100

Lead	170 sx Class "G" Cement	432 cuft
Slurry 1	+ 3% D79 extender	
TOC@Surface	+ 2% S1 Calcium Chloride	
	+1/4 #/sk. Cellophane Flake	
	+ 0.1% D46 antifoam	
Tail	100 sx 50/50 Class "G"/Poz	121 cuft
Slurry 2	+ 2% gel (extender)	
500 ft fill	0.1% D46 antifoam	0.1733 cuft/ft OH
	+1/4 #/sk. Cellophane Flake	0.2009 cuft/ft csg ann
	+ 2% CaCl2 (accelerator)	

Slurry Properties:	Density (lb/gal)	Yield (ft3/sk)	Water (gal/sk)
Slurry 1	11.4	2.61	17.77
Slurry 2	13.5	1.27	5.72

Casing Equipment: 5 1/2", 8R, ST&C

1 Float Shoe (autofill with minimal LCM in mud)
 1 Float Collar (autofill with minimal LCM in mud)
 1 Top Rubber Plug
 1 Thread Lock Compound