

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
OMB No. 1004-0136
Expires November 30, 2000

APPLICATION FOR PERMIT TO DRILL OR REENTER

1a. Type of Work: <input checked="" type="checkbox"/> DRILL <input type="checkbox"/> REENTER		5. Lease Serial No. NMSF - 079511-A
1b. Type of Well: <input type="checkbox"/> Oil Well <input checked="" type="checkbox"/> Gas Well <input type="checkbox"/> Other <input checked="" type="checkbox"/> Single Zone <input type="checkbox"/> Multiple Zone		6. If Indian, Allottee or Tribe Name
2. Name of Operator BP AMERICA PRODUCTION COMPANY		7. If Unit or CA Agreement, Name and No.
Contact: MARY CORLEY E-Mail: corleyml@bp.com		8. Lease Name and Well No. ARCHULETA 1C
3a. Address P.O. BOX 3092 HOUSTON, TX 77253	3b. Phone No. (include area code) Ph: 281.366.4491 Fx: 281.366.0700	9. API Well No. 30045 32317
4. Location of Well (Report location clearly and in accordance with any State requirements. *) At surface NENW Lot C 355FNL 960FWL 36.48200 N Lat, 107.43200 W Lon At proposed prod. zone		10. Field and Pool, or Exploratory BLANCO MESAVERDE
14. Distance in miles and direction from nearest town or post office* 12 MILES FROM AZTEC, NEW MEXICO		11. Sec., T., R., M., or Blk. and Survey or Area C Sec 19 T30N R8W Mer NMP SME: BLM
15. Distance from proposed location to nearest property or lease line, ft. (Also to nearest drig. unit line, if any) 355	16. No. of Acres in Lease 342.54	12. County or Parish SAN JUAN
17. Spacing Unit dedicated to this well 342.54 R-120 unit #3	18. Distance from proposed location to nearest well, drilling, completed, applied for, on this lease, ft. 1904	13. State NM
19. Proposed Depth 5623 MD	20. BLM/BIA Bond No. on file WY2924	
21. Elevations (Show whether DF, KB, RT, GL, etc.) 6272 GL	22. Approximate date work will start 06/01/2004	23. Estimated duration 5 DAYS

24. Attachments

The following, completed in accordance with the requirements of Onshore Oil and Gas Order No. 1, shall be attached to this form:

- | | |
|---|--|
| 1. Well plat certified by a registered surveyor. | 4. Bond to cover the operations unless covered by an existing bond on file (see Item 20 above). |
| 2. A Drilling Plan. | 5. Operator certification |
| 3. A Surface Use Plan (if the location is on National Forest System Lands, the SUPO shall be filed with the appropriate Forest Service Office). | 6. Such other site specific information and/or plans as may be required by the authorized officer. |

25. Signature (Electronic Submission)	Name (Printed/Typed) MARY CORLEY	Date 04/22/2004
Title AUTHORIZED REPRESENTATIVE		
Approved by (Signature) <i>[Signature]</i>	Name (Printed/Typed)	Date 6/21/04
Title Acting Field Manager - Minerals		

Application approval does not warrant or certify the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Conditions of approval, if any, are attached. *Non standard location, will be required.*

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

Additional Operator Remarks (see next page)

Electronic Submission #29879 verified by the BLM Well Information System
For BP AMERICA PRODUCTION COMPANY, sent to the Farmington

DRILLING OPERATIONS AUTHORIZED ARE
SUBJECT TO COMPLIANCE WITH ATTACHED
"GENERAL REQUIREMENTS".

This action is subject to technical and
procedural review pursuant to 43 CFR 3165.3
and appeal pursuant to 43 CFR 3165.4

HOLD C104 FOR *NSL*

** OPERATOR-SUBMITTED ** OPERATOR-SUBMITTED ** OPERATOR-SUBMITTED **

NMOCD

District I
PO Box 1980, Hobbs NM 88241-1980
District II
PO Drawer KK, Artesia, NM 87211-0719
District III
1000 Rio Brazos Rd., Artesia, NM 87410
District IV
PO Box 2088, Santa Fe, NM 87504-2088

State of New Mexico
Energy, Minerals & Natural Resources Department

OIL CONSERVATION DIVISION
PO Box 2088
Santa Fe, NM 87504-2088

Form C-1022
Revised February 21, 1994
Instructions on back
Submit to Appropriate District Office
State Lease - 4 Copies
Fee Lease - 3 Copies

☐ AMENDED REPORT

WELL LOCATION AND ACREAGE DEDICATION PLAT

1 API Number 30-045-32317		2 Pool Code 72319		3 Pool Name BLANCO MESAVERDE	
4 Property Code 000268		5 Property Name Archuleta			6 Well Number # 1C
7 OGRID No. 000770		8 Operator Name BP AMERICA PRODUCTION COMPANY			9 Elevation 6272

10 Surface Location

UL or Lot No. C	Section 19	Township 30 N	Range 8 W	Lot Ids	Feet from the 355	North/South line NORTH	Feet from the 960	East/West line WEST	County SAN JUAN
---------------------------	----------------------	-------------------------	---------------------	---------	-----------------------------	----------------------------------	-----------------------------	-------------------------------	---------------------------

11 Bottom Hole Location If Different From Surface

12 UL or lot no.	Section	Township	Range	Lot Ids	Feet from the	North/South line	Feet from the	East/West line	County
13 Dedicated Acre 342.54 14 Joint or Infill 15 Consolidation Code 16 Order No. R-120 unit #3									

NO ALLOWABLE WILL BE ASSIGNED TO THIS COMPLETION UNTIL ALL INTERESTS HAVE BEEN CONSOLIDATED
OR A NON-STANDARD UNIT HAS BEEN APPROVED BY THE DIVISION

16 		17 OPERATOR CERTIFICATION I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief. Signature: <i>Mary Corley</i> Printed Name: Mary Corley Title: Regulatory Analyst Date: 04.22.2004
18 SURVEYOR CERTIFICATION I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my belief. Date of Survey: October 15, 2003 Signature: <i>GARY D. VAN...</i> Title: REGISTERED PROFESSIONAL LAND SURVEYOR 		7016 Certificate Number

(R) - BLM Record

Additional Operator Remarks:

1C

Notice of Staking was submitted on 11/24/2003.

BP America Production Company respectfully request permission to drill the subject well to a total depth of approximately 5623' and complete in the Blanco Mesaverde Pool.

As an alternate to the drilling of the surface hole with drilling mud as stated on the attached Form 46, BP request permission to either drill with drilling mud or with air/air mist. Additionally, BP request as a possible alternate to the cementing of the surface casing to be either the cementing program stated on the cementing report or with approximately 94 CU/FT TYPE I-II, 20% FLYASH, 14.5 PPG, 7.41 GAL/SK, 1.61 CF/SK YIELD, 80 DEG BHST READY MIX CMT.

SUPPLEMENTAL TO SURFACE USE PLAN

New facilities:

A 4 1/2" diameter buried steel pipeline that is + or 150 feet in length will be constructed. The pipe wall thickness is .156 and the pipe wall strength is 42,000. It will be adjacent to the access road and tie the well into an Archuleta #2 well meter operated by BP America Production Company. The pipeline will not be used to transport gas to drill the well. After the well is spud the pipeline will be authorized by a right-of-way issued to El Paso Field Services, refer to the attached survey plat.

**BP AMERICA PRODUCTION COMPANY
DRILLING AND COMPLETION PROGRAM**

Prospect Name: Archuleta
Lease: Archuleta
County: San Juan
State: New Mexico
Date: April 20, 2004

Well No: 1 C
Surface Location: 19-30N-8W, 355 FNL, 960 FWL
Field: Blanco Mesaverde

OBJECTIVE: Drill 400' below the top of the Point Lookout Sandstone, set 2 7/8" production long string, Stimulate CH, MF and PL intervals

METHOD OF DRILLING		APPROXIMATE DEPTHS OF GEOLOGICAL MARKER			
TYPE OF TOOLS	DEPTH OF DRILLING	Estimated GL: 6278'		Estimated KB: 6289'	
Rotary	0 - TD				
LOG PROGRAM		MARKER		SUBSEA	TVD
TYPE	DEPTH INVERAL	Ojo Alamo		4375	1917
<u>OPEN HOLE</u>		Kirtland		4296	1996
None		Fruitland		3744	2548
		Fruitland Coal	*	3581	2711
		Pictured Cliffs	*	3279	3013
		Lewis	*	3006	3286
<u>CASED HOLE</u>		Cliff House	#	1748	4544
GR-CCL-CBL	TD to 5 1/2" shoe	Menefee	#	1417	4875
		Point Lookout	#	1069	5223
		Mancos		681	5611
REMARKS:		TOTAL DEPTH			
- Please report any flares (magnitude & duration).		669			
		5623			
		# Probable completion interval		* Possible Pay	
SPECIAL TESTS		DRILL CUTTING SAMPLES		DRILLING TIME	
TYPE		FREQUENCY	DEPTH	FREQUENCY	DEPTH
None		None	Production hole	Geograph	0-TD
REMARKS:					

MUD PROGRAM:					
Approx. Interval	Type Mud	Weight, #/gal	Vis, sec/qt	W/L cc's/30 min	Other Specification
0 - 120	Spud	8.6-9.2			
120 - 2661 (1)	Water/LSND	8.6-9.2		<6	
2661 - 5623	Gas/Air/N2/Mist	Volume sufficient to maintain a stable and clean wellbore			

REMARKS:
(1) The hole will require sweeps to keep unloaded while fresh water drilling. Let hole conditions dictate frequency.

CASING PROGRAM: (Normally, tubular goods allocation letter specifies casing sizes to be used. Hole sizes will be governed by Contract)						
Casing String	Estimated Depth	Casing Size	Grade	Weight	Hole Size	Landing Pt, Cmt, Etc.
Surface/Conductor	120	8 5/8"	X-42 ST&C	20#	12.25"	1
Intermediate 1	2661	5 1/2"	J-55 ST&C	15.5#	7.875"	1,2
Production	5623	2 7/8"	J-55	6.5#	4.75"	3,4

REMARKS:
(1) Circulate Cement to Surface
(2) Set casing 50' above Fruitland Coal
(3) Bring cement 100' above 5 1/2" shoe
(4) 100' Overlap

CORING PROGRAM:
None

COMPLETION PROGRAM:
Rigless, 2-3 Stage Limited Entry Hydraulic Frac

GENERAL REMARKS:
Notify BLM/NMOCD 24 hours prior to Spud, BOP testing, and Casing and Cementing.

Form 46 Reviewed by: _____ Logging program reviewed by: N/A

PREPARED BY:	APPROVED:	DATE:
HGJ/MNP/JMP		April 20, 2004
Form 46 12-00 MNP		Version 2.0

BP America Production Company

BOP Pressure Testing Requirements

Well Name: Archuleta
County: San Juan

1 C
State: New Mexico

Formation	Estimated TVD/MD	Anticipated Bottom Hole Pressure	Maximum Anticipated Surface Pressure **
Ojo Alamo	1917		
Fruitland Coal	2711		
PC	3013		
Lewis Shale	3286		
Cliff House	4544	500	0
Menefee Shale	4876		
Point Lookout	5223	600	0
Mancos	5611		
Dakota	-	2600	1374

** Note: Determined using the following formula: $ABHP - (.22 \times TVD) = ASP$

Requested BOP Pressure Test Exception: 750 psi

SAN JUAN BASIN
Mesaverde Formation
Pressure Control Equipment

Background

The objective Mesaverde formation maximum surface pressure is anticipated to be less than 1000 psi, based on shut-in surface pressures from adjacent wells. Pressure control equipment working pressure minimum requirements are therefore 2000 psi. Equipment to be used will conform to API RP-53 (Figure 2.C.2) for a 2000 psi system per Federal Onshore Order No. 2. Due to available conventional equipment within the area, 3000 psi rated pressure control equipment will typically be utilized in a double ram type arrangement. Regional drilling rigs to be utilized have substructure height limitations which exclude the use of annular preventers; therefore a rotating head will be installed above these rams. This pressure control equipment will be utilized for conventional drilling below conductor to total depth in the Mesaverde. No abnormal temperature, pressure, or H2S anticipated.

Equipment Specification

Interval

BOP Equipment

Below conductor casing to total depth 9", 11" nominal or 7 1/16", 3000 psi
double ram preventer with rotating
head.

All ram type preventers and related control equipment will be hydraulically tested to 250 psi (low pressure) and 750 psi (high pressure), upon installation, following any repairs or equipment replacements, or at 30 day intervals. Accessories to BOP equipment will include kelly cock with a handle available, floor safety valves and choke manifold which will also be tested to equivalent pressure.

Cementing Program

Well Name: Archuleta 1C
Location: 19-30N-08W, 355 FNL, 960 FWL
County: San Juan
State: New Mexico

Field: Blanco Mesaverde
API No.
Well Flac
Formation: MesaVerde
KB Elev (est) 6289
GL Elev. (est) 6278

Casing Program:

Casing String	Est. Depth (ft.)	Hole Size (in.)	Casing Size (in.)	Thread	TOC (ft.)	Stage Tool Or TOL (ft.)
Surface	120	12 1/4	8 5/8	ST&C	Surface	NA
Intermediate	2661	7 7/8	5 1/2	ST&C	Surface	NA
Production -	5623	4 3/4	2 7/8		2561	NA

Casing Properties:

(No Safety Factor Included)								
Casing String	Size (in.)	Weight (lb/ft)	Grade	Burst (psi.)	Collapse (psi.)	Joint St. (1000 lbs.)	Capacity (bbl/ft.)	Drift (in.)
Surface	8 5/8	24	X42	2950	1370	244	0.06368	7.972
Intermediate	5 1/2	15.5	J55	4810	4040	202	0.0238	5.067
Production -	2 7/8	6.5	J-55	7264	7676	72	0.00579	2.375

Mud Program

Apx. Interval (ft.)	Mud Type	Mud Weight	Recommended Mud Properties Prio Cementing:
0 - SCP	Water/Spud	8.6-9.2	Fluid Loss <6
SCP - ICP	Water/LSND	8.6-9.2	
ICP - TD	Gas/Air Mist	NA	

Cementing Program:

	Surface	Intermediate	Production
Excess %, Lead	100	100	40
Excess %, Tail	NA	0	40
BHST (est deg. F)	72	110	159
Time Between Stages, (hr)	NA	NA	NA
Special Instructions	1,6	1,6	2,6

1. Do not wash pumps and lines.
2. Wash pumps and lines.
3. Reverse out
4. Run Blend Test on Cement
5. Record Rate, Pressure, and Density on 3.5" disk
6. Confirm densitometer with pressurized mud scales
7. 1" cement to surface if cement is not circulated.
8. If cement is not circulated to surface, run temp. survey 10-12 hr. after landing plug.

Surface:

Preflush	20 bbl.	FreshWater	
Slurry 1	80 sx Class C Cement		
TOC@Surface	+ 2% CaCl2 (accelerator)		
			102 99 cuft
			0.413 cuft/ft OH
			100 % excess
Slurry Properties:	Density (lb/gal)	Yield (ft3/sk)	Water (gal/sk)
Slurry 1	15.2	1.27	5.8

Intermediate:

Fresh Water	20 bbl	fresh water
-------------	--------	-------------

Cementing Program

Lead
Slurry 1
TOC@Surface

290 sx Class "G" Cement
+ 3% D79 extender
+ 1/4 #/sk. Cellophane Flake
+ 0.1% D46 antifoam
70 sx 50/50 Class "G"/Poz
+ 2% gel (extender)
0.1% D46 antifoam
+ 1/4 #/sk. Cellophane Flake
+ 2% S1 Calcium Chloride

757
732 cuft

Tail
Slurry 2

500 ft fill

89
87 cuft

0.1733 cuft/ft OH
0.2009 cuft/ft csg ann
80 % excess

Slurry Properties:	Density (lb/gal)	Yield (ft ³ /sk)	Water (gal/sk)
Slurry 1	11.7	2.61	17.77
Slurry 2	13.5	1.27	5.72

Production:

Fresh Water 10 bbl CW100

Slurry

140 LiteCrete D961 / D124 / D154
+ 0.03 gps D47 antifoam
+ 0.5% D112 fluid loss
+ 0.11% D65 TIC

353
336 cuft

TOC@Liner Top


Slurry Properties:	Density (lb/gal)	Yield (ft ³ /sk)	Water (gal/sk)
Slurry	9.5	2.52	6.38

0.078 cuft/ft OH
40 % excess
0.0886 cuft/ft csg ann

PAD LAYOUT PLAN & PROFILE
BP AMERICA PRODUCTION COMPANY


Archuleta #1C
 450' 355' F/NL 960' F/WL 850'
 SEC. 19, T30N, R8W, N.M.P.M.
 SAN JUAN COUNTY, NEW MEXICO

Lat: 36°48'10"
 Long: 107°43'09"



Area of Construction Zone - 330'x400' or 3.03 acres, more or less.

SCALE: 1"=60'-HORIZ.
 1"=40'-VERT.



NOTE: Contractor should call One-Call for location of any marked or unmarked buried pipelines or cables on well pad and/or access road at least two (2) working days prior to construction.


Cuts and fills shown are approximate - final finished elevation is to be adjusted so earthwork will balance. Corner stakes are approximate and do not include additional areas needed for sideslopes and drainages. Final Pad Dimensions are to be verified by Contractor.

VANN SURVEYS
 P. O. Box 1306
 Farmington, NM

BP American Production Company
Well Control Equipment Schematic



BOP Stack



Choke & Kill Manifold

