UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to re-enter an abandoned well. Use form 3160-3 (APD) for such proposals.

FORM APPROVED OMB NO. 1004-0135 Expires: November 30, 2000

Expires: November 30, 2000 ase Serial No.

5.	Lease Serial No. NMSF081155	
6.	If Indian, Allottee or Tribe Name	

				L.					
SUBMIT IN TRI	erse side.		7. If Unit or CA/Agreen	nent, Name and/or No.					
1. Type of Well ☐ Oil Well ☑ Gas Well ☐ Oth			8. Well Name and No. ALLISON UNIT 53C						
Name of Operator BURLINGTON RESOURCES	ES t@br-inc.com		9. API Well No. 30-045-30368-00-X1						
PO BOX 4289			(include area co 9.4068 .4062	de)	10. Field and Pool, or Exploratory MESAVERDE POINT LOOKOUT				
4. Location of Well (Footage, Sec., T	., R., M., or Survey Description	n)			11. County or Parish, as	nd State			
Sec 29 T32N R6W SENE 152			SAN JUAN COUNTY, NM						
12. CHECK APPI	ROPRIATE BOX(ES) TO	O INDICATE	NATURE OF	F NOTICE, R	EPORT, OR OTHER	DATA			
TYPE OF SUBMISSION	OF SUBMISSION TYPE OF ACTION								
Ninting of Intent	☐ Acidize	☐ Deep	en	☐ Produc	tion (Start/Resume)	☐ Water Shut-Off			
□ Notice of Intent	Alter Casing	☐ Frac	ture Treat	☐ Reclam	ation	☐ Well Integrity			
Subsequent Report	Casing Repair	☐ New	Construction	☐ Recom	_				
Final Abandonment Notice	Change Plans	Plug	and Abandon	Tempo	rarily Abandon	Other Drilling Operations			
_	Convert to Injection	Plug	Back	□ Water	Disposal				
Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the site is ready for final inspection.) 7" & 4-1/2" CASING REPORTS 4/29/04 RIH w/8-3/4" bit & tagged cement @ 197'. Drilled cement & then formationt o 3978'. Circ. hole. 5/4/04 RIH w/7", 20#, J-55 ST&C casing and set @ 3973'. RU BJ to cement. Pumped a preflush of 20 bbls water ahead of 1st stage Lead - 133 (283 cf - 50.4 bbl slurry)sx Premium Lite w/3% CaCl2, .5#/sx Cello-flake, .40% LCM-1, .40% FL-52. Tailed w/90 sx (124 cf - 22 bbl slurry)Type III w/1% CaCl2, .25#/sx Flocele, .20% FL-52. Dropped plug and displaced wiwater to stage tool @ 2768. Bumped plug w/1000 psi. Opened stage tool w/2200 psi. Circ 20 bbls to surface. 2nd stage - preflush w/20 bbls water & 10 bbls SAPP. Pumped Lead - 381 sx (811.5 cf - 144.5 bbls slurry) Premium Lite w/3% CaCl2, .50#/sx Celloflake, .40% LCM-1, & .40% FL-52. Dropped plug and displaced w/water. Bumped plug to 2000 psi to close stage tool. Circ. 42 bbls cement to surface. Plug down @ 1630 hrs 5/4/04. PT blind rams, manifold and casing to 1500 psi for 30 minutes. Good test.									
	Electronic Submission a For BURLINGTON RI mitted to AFMSS for proce	ESOURCES O	G CO LP, ser	it to the Farmi	ngton				
Name (Printed/Typed) PATSY C	LUGSTON	Title SR. F	REGULATOR	Y SPECIALIST					
Signature (Electronic S	Submission)		Date 06/10	/2004					
	THIS SPACE FO	OR FEDERA	L OR STAT	E OFFICE U	SE				
Approved By ACCEPT	ED			INE GARCIA LEUM ENGIN	EER	Date 06/14/2004			
Conditions of approval, if any, are attache certify that the applicant holds legal or equivalent would entitle the applicant to conditions.	Office Farmi								
Title 18 U.S.C. Section 1001 and Title 43 States any false, fictitious or fraudulent	U.S.C. Section 1212, make it statements or representations a	a crime for any posts to any matter w	erson knowingly thin its jurisdicti	and willfully to r	nake to any department or	agency of the United			

Additional data for EC transaction #31783 that would not fit on the form

32. Additional remarks, continued

5/5/04 RIH w/6-1/4" bit & D/O cement shoe & then formation to 6344' (TD). TD reached 5/7/04. RU to run liner. RIH w/4-1/2" 10.5#, J-55 ST&C casing and set @ 6343' w/ TOL @ 3867.5' RU BJ to cement liner. Pumped 178 sx (352 cf - 62.68 bbl slurry) Premium Lite w/additives. Displaced w/FW & sugar in 1st 10 bbls. Bumped plug to 2000 psi. Packed off liner top & released running tool. Load hole & reversed out excess cement from liner top. Reversed out 15 bbls cement. TOOH. ND BOP & RD rotary tool. RD & released rig @ 0000 hrs 5/7/04 Completion will conduted the casing PT before completion begins.