Form 3160-5 (September 2001)

UNITED STATES DEPARTMENT OF THE INTERIOR **BUREAU OF LAND MANAGEMENT**

		•		/	
			*	. /	
	UNITED STATES DEPARTMENT OF THE BUREAU OF LAND MAN	INTERIOR	RECE!	V	FORM APPROVED OM B No. 1004-0135 Expires: January 31, 2004
CHMDDV	NOTICES AND REP	ODTE ON WEL	10	NMSF - (
not use th	notices and her his form for proposals to ell. Use Form 3160-3 (A	o drill or to re-en	teran []	6 If Indian	Allottee or Tribe Name
MIT IN TRI	IPLICATE- Other instr	uctions on revers	e side.	7. If Unit or (31057	CA/Agreement, Name and/or No.
Well	Gas Well Other		8. Well Nam		
Richardson C	Operating Company			9. API Well	
3b. Phone No. (include area code)				30-045-3	
	vay, Farmington, NM 87401 T., R., M., or Survey Description)		10. Field and Pool, or Exploratory Area W Kutz PC & Basin Frt Coal		
	ion 29 T29N-R13W				r Parish, State
on LMT Secti	100 27 127N-R13W			San Juai	n County, NM
CHECK AI	PPROPRIATE BOX(ES) TO	INDICATE NATURE	OF NOTICE, R	EPORT, OR	OTHER DATA
MISSION		TYPI	E OF ACTION		
nt port rment Notice	Acidize Alter Casing Casing Repair Change Plans Convert to Injection	Deepen Fracture Treat New Construction Plug and Abandon Plug Back	Production (Statement of Statement of Statem	´· [Water Shut-Off Well Integrity Other Spud and TD
is to deepen dire d under which the pletion of the inv a completed. Fin		y, give subsurface locations de the Bond No. on file wi results in a multiple comple	s and measured and tru th BLM/BIA. Require tion or recompletion i	ne vertical depths ed subsequent re in a new interval,	, a Form 3160-4 shall be filed once
semt w/ 2% C surface. Shu BOP. Drill 6 ill 6 1/4" hole in 45jts 4 1/2" im metasilicati	SC12, 1/4#persk celloflake. Ce	ement yeild 1.18cuft/sk, a 4 1/2" csg. , GL. Cement as follow ilsonite, 12.5ppg, 2.06cc	59cuft, 15.6ppg, 10 s: pmp 20bbls wat	er preflush. L	ead in with 190sx Class B ss. B w/ 1/4#persk celloflake,
				JUN, 201	04

SUBMIT IN TR	IPLICATE-	Other inst	tructions on reve	erse side.		CA/Agree	ement, Name and/or No.
. Type of Well Oil Well	✓ Gas Well	Other	····	· · · · · · · · · · · · · · · · · · ·	31057		
					8. Well Nam		ι
. Name of Operator Richardson	Operating Con	pany			9. API We		
Address	way Farmingto	- NM 97401	3b. Phone No. (inch. 505-564-3100	ide area code)	30-045-		
3100 La Plata High Location of Well (Footage, Sec.							Exploratory Area asin Frt Coal
2210' FSL & 1530' FWL Sec		11		11. County or Parish, State San Juan County, NM			
12. CHECK A	PPROPRIATE	BOX(ES) TO	O INDICATE NATU	JRE OF NOTICE, R	EPORT, OR	OTHER	R DATA
TYPE OF SUBMISSION			Т	YPE OF ACTION			
Notice of Intent Subsequent Report	Acidize Alter Ca	Repair	Deepen Fracture Treat New Construction	,	,	Well	er Shut-Off I Integrity Ex Spud and TD
Final Abandonment Notice	Change	Plans to Injection	Plug and Abandor Plug Back	Temporarily A Water Disposal			
If the proposal is to deepen din Attach the Bond under which following completion of the in testing has been completed. F determined that the site is read 05/05/04 Spud well at 2: 50sx Class B cmt w/ 2%	rectionally or reco the work will be p anyolved operations inal Abandomner by for final inspect 100pm. Drill 8 3. CsC12, 1/4#pers	mplete horizonta verformed or pro- s. If the operation at Notices shall be ion.) 4" hole to 128	ally, give subsurface loca vide the Bond No. on fil in results in a multiple con e filed only after all require. '. Run 124' of 7" 20#	tions and measured and tre with BLM/BIA. Requirempletion or recompletion irements, including reclarions ST&C csg. Cement a	red subsequent re in a new interva nation, have been as follows: pm	ports shal l, a Form 3 n complete p Sbbis p	Il be filed within 30 days 3160-4 shall be filed once ed, and the operator has preflush. Mix and pmp
If the proposal is to deepen din Attach the Bond under which following completion of the in testing has been completed. F determined that the site is read 05/05/04 Spud well at 2:	rectionally or reco the work will be provided operations inal Abandonmer by for final inspect popm. Drill 8 3. CsC12, 1/4#pers at-in, WOC. 6 1/4" hole to 8 e to 1348', TD v " 10.5# J-55 csg te, 1/4#persk ce	replete horizontal serformed or provision. If the operation t Notices shall be tion.) 4" hole to 128 k celloflake. Company of the vell. Prep to rus. Land at 1334 dioflake, 3#/sk	ally, give subsurface local vide the Bond No. on fill in results in a multiple con- e filed only after all requi- t. Run 124' of 7" 20# Cement yelld 1.18cufts an 4 1/2" csg. 8', GL. Cement as fol- gilsonite, 12.5ppg, 2.4	tions and measured and tre with BLM/BIA. Requirempletion or recompletion irements, including reclared ST&C csg. Cement a sk, 59cuft, 15.6ppg, 10 llows: pmp 20bbls wa	red subsequent r in a new interva nation, have been as follows: pm Obbls slurry. I	ports shall, a Form 3 n complete p Sbbis p Tush with	Il be filed within 30 days 3160-4 shall be filed once ed, and the operator has preflush. Mix and pmph 4bbls water. Circ
If the proposal is to deepen din Attach the Bond under which following completion of the it testing has been completed. F determined that the site is read 05/05/04 Spud well at 2:: 50sx Class B cmt w/ 2% 4bbls cmt to surface. Sh: 05/06/04 NU BOP. Drill 05/07/04 Drill 6 1/4" hol 05/08/04 Run 45/ts 4 1/2 w/ 2% sodium metasilica 3#/sk gilsonite; 15.6ppg, WOC.	rectionally or reco the work will be produced operations inal Abandonmer by for final inspect 100pm. Drill 8 3. CsCl2, 1/4#pers at-in, WOC. 6 1/4" hole to 8 e to 1348', TD vg 110.5# J-55 cs te, 1/4#persk ce 1.18 cuft/sk yiel	mplete horizonta erformed or prova- i. If the operation it Notices shall be ion.) 4" hole to 128 k celloflake. Company of the rell. Prep to ru- lloflake, 3#/sk d. Circ 12bbls	ally, give subsurface local vide the Bond No. on fill in results in a multiple con- e filed only after all requi- t. Run 124' of 7" 20# Cement yelld 1.18cufts an 4 1/2" csg. 8', GL. Cement as fol- gilsonite, 12.5ppg, 2.4	tions and measured and tre with BLM/BIA. Requirempletion or recompletion irements, including reclared ST&C csg. Cement a sk, 59cuft, 15.6ppg, 10 llows: pmp 20bbls wa	red subsequent r in a new interva nation, have been is follows: pm Obbls slurry. I ter preflush. I	ports shall, a Form 3 n complete p Sbbis p Tush with	Il be filed within 30 days 3160-4 shall be filed once ed, and the operator has preflush. Mix and pmph 4bbls water. Circ
If the proposal is to deepen din Attach the Bond under which following completion of the it testing has been completed. F determined that the site is read 05/05/04 Spud well at 2:: 50sx Class B cmt w/ 2% 4bbls cmt to surface. Sh: 05/06/04 NU BOP. Drill 05/07/04 Drill 6 1/4" hol 05/08/04 Run 45/ts 4 1/2 w/ 2% sodium metasilica 3#/sk gilsonite; 15.6ppg, WOC.	rectionally or reco the work will be provided operations inal Abandonmer by for final inspect DOpm. Drill 8 3. CsCl2, 1/4#pers at-in, WOC. 6 1/4" hole to 8 e to 1348', TD v " 10.5# J-55 csg te, 1/4#persk ce 1.18 cuft/sk yiel	mplete horizonta erformed or prova- i. If the operation it Notices shall be ion.) 4" hole to 128 k celloflake. Company of the rell. Prep to ru- lloflake, 3#/sk d. Circ 12bbls	ally, give subsurface local vide the Bond No. on fill in results in a multiple con- e filed only after all requi- t. Run 124' of 7" 20# Cement yelld 1.18cufts an 4 1/2" csg. 8', GL. Cement as fol- gilsonite, 12.5ppg, 2.4	tions and measured and tre with BLM/BIA. Requirempletion or recompletion irements, including reclared ST&C csg. Cement a sk, 59cuft, 15.6ppg, 10 llows: pmp 20bbls wa	red subsequent r in a new interva nation, have been is follows: pm Obbls slurry. I ter preflush. I	ports shall, a Form 3 n complete p Sbbis p Tush with	Il be filed within 30 days 3160-4 shall be filed once ed, and the operator has preflush. Mix and pmph 4bbls water. Circ
If the proposal is to deepen din Attach the Bond under which following completion of the it testing has been completed. F determined that the site is read 05/05/04 Spud well at 2:: 50sx Class B cmt w/ 2% 4bbls cmt to surface. Sh: 05/06/04 NU BOP. Drill 05/07/04 Drill 6 1/4" hol 05/08/04 Run 45/15 4 1/2 w/ 2% sodium metasifica 3#/sk gilsonite; 15.6ppg, WOC.	rectionally or reco the work will be provided operations inal Abandonmer by for final inspect DOpm. Drill 8 3. CsCl2, 1/4#pers at-in, WOC. 6 1/4" hole to 8 e to 1348', TD v " 10.5# J-55 csg te, 1/4#persk ce 1.18 cuft/sk yiel	mplete horizonta erformed or prova- i. If the operation it Notices shall be ion.) 4" hole to 128 k celloflake. Company of the rell. Prep to ru- lloflake, 3#/sk d. Circ 12bbls	ally, give subsurface local vide the Bond No. on fill in results in a multiple content of the filed only after all requirement with 1.18 cuft. The subsurface is a multiple content with 1.18 cuft. The subsurface is a subsurface is a subsurface is a subsurface.	tions and measured and tre with BLM/BIA. Requirements, including reclaration or recompletion irements, including reclarations,	red subsequent r in a new interva nation, have been is follows: pm Obbls slurry. I ter preflush. I	ports shall, a Form 3 a complete p Sbbis p Flush with with sa. B w/ 1	il be filed within 30 days 3160-4 shall be filed once ed, and the operator has preflush. Mix and pm h 4bbls water. Circ with 100sx Class B 1/4#persk celloflake,
If the proposal is to deepen din Attach the Bond under which following completion of the it testing has been completed. F determined that the site is read 05/05/04 Spud well at 2: 50sx Class B cmt w/ 2% 4bbls cmt to surface. She 05/06/04 NU BOP. Drill 05/07/04 Drill 61/4" hol 05/08/04 Run 45/st 41/2 w/ 2% sodium metasifica 3#/sk gilsonite; 15.6ppg, WOC.	rectionally or reco the work will be produced operations in Abandonmer by for final inspect Dopm. Drill 8 3. CsC12, 1/4#pers at-in, WOC. 6 1/4" hole to 8 e to 1348; TD v " 10.5# J-55 csg te, 1/4#persk et 1.18 cuft/sk yiel	mplete horizonta erformed or provation for the operation t Notices shall be tion.) '4" hole to 128 k celloflake. Company of the celloflake. Company of the celloflake, 3#/sk d. Circ 12bbls	ally, give subsurface local vide the Bond No. on fill in results in a multiple content of the filed only after all requirements. Run 124' of 7" 20#Cement yelld 1.18cuft. In 4 1/2" csg. 8', GL. Cement as for gilsonite, 12.5ppg, 2.0 cmt to surface. Title	tions and measured and tre with BLM/BIA. Requirements, including reclaration or recompletion irements, including reclarations,	red subsequent r in a new intervanation, have been as follows: pm bbls slurry. I ter preflush. In with \$05x Ch	ports shall, a Form 3 a complete p Sbbis p Flush with with sa. B w/ 1	Il be filed within 30 days 3160-4 shall be filed once ed, and the operator has preflush. Mix and pmph 4bbls water. Circ
Attach the Bond under which following completion of the in testing has been completed. Federmined that the site is read 05/05/04 Spud well at 2: 50sx Class B cmt w/ 2% 4bbls cmt to surface. Shr 05/06/04 NU BOP. Drill 05/07/04 Brill 6 1/4" hol 05/08/04 Run 45/ts 4 1/2 w/ 2% sodium metasilica 3#/sk gilsonite; 15.6ppg, WOC.	rectionally or reco the work will be produced operations inal Abandonmer by for final inspect to the produced operations of the produced operations of the produced operations of the produced operations to the produced operations of the p	mplete horizontal cerformed or provision. If the operation of Notices shall be ion.) 4" hole to 128 k celloflake. Comment of the celloflake. Comment of the celloflake. Comment of the celloflake, 3#sk d. Circ 12bbls. Circ 12bbls. Circ 12bbls.	ally, give subsurface local vide the Bond No. on fill in results in a multiple content of the filed only after all requirements. Run 124' of 7" 20# Cement yelld 1.18cufts and 4 1/2" csg. B', GL. Cement as folgitsonite, 12.5ppg, 2.6 cent to surface. Title Date	tions and measured and tre with BLM/BIA. Requimpletion or recompletion irements, including reclar ST&C csg. Cement a sk, 59cuft, 15.6ppg, 10 llows: pmp 20bbls wa b6cuft/sk yield. Tail ir	red subsequent re in a new intervanation, have been as follows: pm bbbls slurry. It ter preflush. It with \$08x Cb	ports shall, a Form 3 a complete p Sbbis p Flush with with sa. B w/ 1	il be filed within 30 days 3160-4 shall be filed once ed, and the operator has preflush. Mix and pm h 4bbls water. Circ with 100sx Class B 1/4#persk celloflake,

(Instructions on page 2)