Forn 3160.5 (August 1999)

UNITED STATES DEPARTMENT OF THE INTERIOR

BUREAU OF LAND MANAGEMENT

FORM APPROVED OMB NO. 1004-0135 Expires: November 30, 2000

5. Lease Serial No.

	NMSF079050C
6.	If Indian, Allottee or Tribe Name

SUNDRY NOTICES AND REPORTS ON WELLS
Do not use this form for proposals to drill or to re-enter an
shandoned well. Use form 3160-3 (APD) for such proposals

abandoned wei	i. Use form 3160-3 (AP	D) for such pi	oposais.		, · · · · · · · · · · · ·		
SUBMIT IN TRIF		7. If Unit or CA/Agreement, Name and/or No. NMNM78412C					
1. Type of Well ☐ Oil Well ☐ Gas Well ☐ Oth		8. Well Name and No. SAN JUAN 28-6 UNIT 155N					
2. Name of Operator BURLINGTON RESOURCES	Contact:	TAMMY JONE E-Mail: twimsat			9. API Well No. 30-039-27601-00-X1		
3a. Address PO BOX 4289 FARMINGTON, NM 87499		3b. Phone No. Ph: 505.599 Fx: 505.599		e)	10. Field and Pool, or Exploratory BASIN DAKOTA BLANCO MESAVERDE		
4. Location of Well (Footage, Sec., T.	. R., M., or Survey Description	1			11. County or Parish, and State		
Sec 28 T28N R6W SWNW 24	•			RIO ARRIBA COUNTY, NM			
12. CHECK APPR	OPRIATE BOX(ES) TO	O INDICATE	NATURE OF 1	NOTICE, RE	PORT, OR OTHER	DATA	
TYPE OF SUBMISSION	TYPE OF SUBMISSION TYPE OF ACTION						
Notice of Intent	☐ Acidize	□ Deep	en	□ Production	on (Start/Resume)	□ Water Shut-Off	
_	Alter Casing Fractu		ure Treat	Reclamation		■ Well Integrity	
Subsequent Report Subsequent Re	Casing Repair	□ New	Construction	☐ Recomple	ete	Other Drilling Operations	
Final Abandonment Notice	Change Plans	□ Plug	and Abandon	Temporar	rily Abandon		
_	Convert to Injection	□ Plug	Back	□ Water Di	sposal		
7"& 4-1/2" CASING REPORT 5/21/04 MIRU Bearcat #3. NU RIH w/8-3/4" bit & tagged cem 5/25/04 RIH w/ 7" 20#, J-55 S gel water, 2 bbls water ahead Tailed w/90 sx Type III (113 cf preflush of 10 bbls water, 10 b bbl slurry) Displaced w/109 bb section, NU BOPE. WOC. P	tent @ 101'. Drilled cem T&C casing & set @ 349 of 1st Stage Lead - 55 s - 22 bbl slurry). Opened bbl muldclean II, 10 bbls bls water. Circ. 25 bbls ce	ent and then foot. RU to cem x Premium Lite d stage tool & water, ahead cement to surface	ormation to 349 ent. Pumped a e - (108 cf - 21 l circ. Pumped 2 of 304 sx (Prem ce. WOC. ND	91'. Circ. hole preflush of 10 bbl slurry); nd stage nium Lite (115 BOP, Installe	bbls JU	2004 2004 2004	
	Electronic Submission For BURLINGTON RI nitted to AFMSS for proce	ESOURCES OB	GCO LP, sent ENNE GARCIA o	to the Farming on 06/14/2004 (0	iton 94AXG2597SE)		
Name (Printed/Typed) PATSY CL	LUGSTON		Title SR. REGULATORY SPECIALIST				
Signature (Electronic S	Submission)		Date 06/07/2	2004			
,	THIS SPACE FO	OR FEDERA	L OR STATE	OFFICE US	E		
Approved By ACCEPT	ED			IE GARCIA EUM ENGINE	ER	Date 06/14/2004	
Conditions of approval, if any, are attache ertify that the applicant holds legal or equivalent would entitle the applicant to conductive the	Office Farmington						
itle 18 U.S.C. Section 1001 and Title 43 States any false, fictitious or fraudulent	U.S.C. Section 1212, make it statements or representations a	a crime for any pe s to any matter wi	rson knowingly an thin its jurisdiction	nd willfully to ma n.	ke to any department or	agency of the United	

Additional data for EC transaction #31586 that would not fit on the form

32. Additional remarks, continued

5/26/04 RIH w/6-1/4" bit & D/O stage tool & load hole. PT casing & rams to 1500# - 30 minutes. Good test. D/O cement & then formation to 7716' TD. TD reached 5/29/04. Circ. hole. RIH w/4-1/2" 10.5# J-55 ST&C casing and set @ 7716'. RU to cement. Pumped a preflush of 10 bbls chemical wash, 2 bbls FW. Pumped Lead - 9 sx (26 cf - 5 bbl slurry) Premium Lite HS cement w/.25#/sx cello-flake, .3% CD-32, 6.25#/sx LCM-1, 1% FL-52. Tail - 277 sx (504 cf - 97.6 bbl slurry) Premium Lite HS FM Cement w/.25#/sx cello-flake, .3% CD-32, 6.25#/sx LCM-1, 1% FL-52. Dropped plug and displaced w/122.6 bbls FW w/25#sugar in 1st 10 bls. Bumped plug w/950 psi @ 2325 hrs 5/31/04. ND BOP. RD & released rig @ 0600 hrs 6/1/04. Will show TOC & casing PT on next report.