Form 3160-5 (April 2004)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM	APPRO	VED
OMB	No. 1004	-0137
 Expires:	March	31, 200

5. Lease Serial No.	
CEO/CECS	

SUNDRY NOTICES AND REPORTS ON WELLS			SF046563				
Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160 - 3 (APD) for such proposals 100 22				6. If Indian, Allottee or Tribe Name			
				6 11 15			
SUBMIT IN TRI	PLICATE- Other instr	ructions on reve	erse side.		CA/Agreement, Name and/or No.		
1. Type of Well Oil Well	Gas Well Other			IVENDA.	811457		
			Snick Com 32 2A				
2. Name of Operator Koch Exploration Company, LLC			9. API Well No.				
3a Address PO Box 489, Aztec, NM		3b. Phone No. (inclu 505-334-9111	ide area code)	30-045-31449 10. Field and Pool, or Exploratory Area			
4. Location of Well (Footage, Sec., T., R., M., or Survey Description)			Basin Fruitiand Coal				
S32, T28N, R10W (J)				11. County or Parish, State			
1375' FSL & 1840' FEL				San Juan, NM			
12. CHECK AF	PROPRIATE BOX(ES) TO	INDICATE NATU	TRE OF NOTICE, RI	EPORT, OR	OTHER DATA		
TYPE OF SUBMISSION		Т	YPE OF ACTION				
	Acidize	Deepen	Production (Star	t/Resume)	Water Shut-Off		
Notice of Intent	Alter Casing	Fracture Treat	Reclamation		Well Integrity		
Subsequent Report	Casing Repair Change Plans	New Construction Plug and Abandon		andon	Other Set Surface Production Casing		
Final Abandonment Notice	Convert to Injection	Plug Back	Water Disposal	anon	110024001 000118		
testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the site is ready for final inspection.) Drilled 6 3/4" hole to 2050', and ran 4 1/2", 10.5#, J-55, ST&C Casing, landed @ 2076' KB (KB=5'0"). Cemented on 6/14/04. Lead cement pumped 207 sks 12.5# Class B Cement w/ 2% Sodium Metasillicate, plus 3#/sk Gilsonite, plus 2#/sk PHENOSEAL, plus .25#/sk Celloflake, yield 2.09, volume 433 cu. ft. Tail with 57 sks 14.5# Class B Cement, plus 1% gel, plus2% CALC, plus 3#/sk Gilsonite, plus .25#/sk Celloflake, yield 1.4, volume 80 cu ft We used centralizers on the bottom 2 joints, and every +/- 400' thereafter. Used 2 turbolators, 1 at the base of the Ojo, and the other in the Ojo. Circulated 6 bbls of good cement to surface. Wait on cement +/- 60 hours.							
6/17/04, move rig off locati	on. 			A CONTRACTOR OF THE PARTY OF TH	JUL 2004		
14. I hereby certify that the oreginame (Printed Typed John Clark	soing is true and correct	Title	District Superintenden	t	30000 July 1990		
Signature Signature	' VWO	Date	06	/18/2004			
	THIS SPACE FOR F	EDERAL OR	STATE OFFICE	USE AC	EPTED FOR RECORL		
Approved by			Title		ate 0 7 2004		
Conditions of approval, if any, are a certify that the applicant holds legal which would entitle the applicant to	or equitable title to those rights in		Office	F	ARMINGTON FIELD OFFICE		
Title 18 U.S.C. Section 1001 and Title States any false, fictitious or fraudule	43 U.S.C. Section 1212, make it a ent statements or representations a	crime for any person is to any matter within	knowingly and willfully to its jurisdiction.	make to any	department or agency of the United		