Form 3160-5 (April 2004)

## UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM_APPROVED
0147674 1004 0100
UM#B No. 1004-0137
OM B No. 1004-0137 Expires: March 31, 2007
parpires, ivinien 31, 2007

FARMINGTON FIELD OFFICE

ם	SUREAU OF LAND MAI	VAGEMENT			papires: March 31, 2007	
SUNDRY NOTICES AND REPORTS ON WELLS					5. Lease Scial No. NNISF-078390	
SUNDRY Do not use th	NOTICES AND RE is form for proposals	PORIS ON W	entzony IIIN 2	J. /	Allottee of Tribe Name	
abandoned we	ell. Use Form 3160 - 3	(APD) for such p	roposals.	NA		
SUBMIT IN TRI	PLICATE- Other ins	tructions on rev	n c	MINGTO	CA/Agreement, Name and/or No.	
1. Type of Well Oil Well	Gas Well Other			8. Well Nan		
2. Name of Operator Richardson C	Operating Company	,	X50105)	Federal 9. API We	<b>42-10 #3</b> Il No.	
3a Address 3100 La Piata Highway, Farmi	ngton, NM, 87401	3b. Phone No. (inch 505-564-3100	ude area code)	30-045-	31942 Pool, or Exploratory Area	
4. Location of Well (Footage, Sec., )	T., R., M., or Survey Description)	lan.			ruitiand Coal	
1185 FSL, 1810 FEL, Sec. 10,	1'28N, R8W			ं गु	or Parish, State  on County, New Mexico	
12. CHECK AF	PROPRIATE BOX(ES) TO	O INDICATE NAT	IRE OF NOTICE, R	EPORT, OR	OTHER DATA	
TYPE OF SUBMISSION		T	YPE OF ACTION			
Notice of Intent	Acidize Alter Casing	Deepen Fracture Treat	Production (St	art/Resume)	Water Shut-Off Well Integrity	
Subsequent Report	Casing Repair	New Construction	L		Other Production csg	
	Change Plans	Plug and Abandon		oandon	& cement	
Final Abandonment Notice	Convert to Injection	to Injection Plug Back Water Dispo				
318'. Secure rig, SDFN. 5/11/04 Drill 541' of 6 1/4' 5/12/04 Drill 34' of 6 1/4" h 5/13/04 Drill 384' of 6 1/4" 5/14/04 Drill 500' of 6 1/4' 5/15/04 Drill 452' of 6 1/4' Secure rig, SDFN. 5/16/04 TH with 60 joint MIRU Key cementer. Cer 11.50ppg, 2.83 yield, as lea cement to surface. Bump l	OP and surface casing to 600" hole to 859". Whre line suriole to 862". Trip and change "hole to 1560". Secure rig, S"hole to 2060". Secure rig, S"hole to 2512". TD well. Cits 4 1/2" J-55 11.6# productionent production casing with d. Tail in with 100 sx Class Plug with 1000 psi, shut well	vey at 694' = 3/4 degrebit. Drill 314' of 6 1/DFN. DFN. rculate well clean. Wencasing, shoe joint 4 225 sx Class B cement	ce. Secure rig, SDFN. 4" hole to 1176'. Secu- ire line survey at 2512' 2', insert float at 2453', t with 3% Sodium Me ilsonite, 1/4/sk celloflat WOC.	re rig, SDFN.  = 1/2 degree.  , PBTD. Land tasilicate, 3#/s ke, 15.60ppg, 1	TOH with DP/DC and bit.  casing at 2495.11' +1 GL.  k gilsonite, 1/4#/sk celloflake,  l.18 yield. Circulate 28 BBL	
Name (Printed/Typed)	eksted	Title	Complia	nce H	dministrator	
Signature 150	cksted	Date		06/28/2004		
V	THIS SPACE FOR	FEDERAL OR	STATE OFFICE	USE	ACCEPTED FOR RECO	
Approved by			Title	E	ae	
Conditions of approval, if any, are					JUL n 7 2064	
certify that the applicant holds legal	or equitable title to those rights	in the subject lease	Office		EADMINISTEN SIELD AFEIR	

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department of the United States any false, fictitious or fraudulent statements or representations as to anymatter within its jurisdiction.

(Instructions on page 2)

which would entitle the applicant to conduct operations thereon.