Form 3160-5 (April 2004)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

CHIMPPY	MATICES	AND	DEDADTO	ON WELLS

FORM APPROVED OMB No. 1004-0137 Expires: March 31, 2007

ease Serial No.

1011020 7412 112	PORTS ON WE	LLO			
form for proposals	to drill or to re-e	nter an		Allottee or Tribe Name	
		· · · · · · · · · · · · · · · · · · ·		32	
PLICATE- Other ins	tructions on rever	se side.RECEI	7. If Unit or	CA/Agreement, Name and/or No.	
Gas Well Other		070 FARMIN	8. Well Nan	ne and No.	
2. Name of Operator Richardson Operating Company				Federal 32-13 #3 API Well No.	
3a Address		3b. Phone No. (include area code)		30-045-31955	
3100 La Plata Highway, Farmington, NM, 87401 4. Location of Well (Footage, Sec., T., R., M., or Survey Description)		505-564-3100		10. Field and Pool, or Exploratory Area Basin Fruitland Coal	
4. Location of Well (Poolage, Sec., 1., R., M., or Survey Description) 1020 FNL, 1910 FWL, Sec. 13, T28N, R8W			11. County or Parish, State		
128N, K8W		hand the same of the	1 3	n County, New Mexico	
PROPRIATE BOX(ES) T	O INDICATE NATUR	E OF NOTICE, R	EPORT, OR	OTHER DATA	
	TYI	PE OF ACTION			
Acidize	Deepen	Production (Sta	urt/Resume)	Water Shut-Off	
_ `		LJ		Well Integrity	
			randon	Other Spud through Production Casing	
_		_ ` `	ABIA COLL		
				P/DC and bit. Run 301' 7" 20# celloflake, 15.60 ppg, 1.18 yield.	
,-1' GL. Cement surface ca Secure rig, SDFN. WOC. and surface casing to 600 p 428'. Secure rig, SDFN. hole to 1996'. Secure rig, S b. Drill 544' of 6 1/4" hole to hole to 3025'. TD well. TO	asing with 120 sx Class E psi, held OK. Drill 937' SDFN. to 2540'. Secure rig, SDI DH with DP/DC and bit. ing with 177 sx Class B o back. Bump plug with 1	s cement with 3% Canew 6 1/4" hole to 1: FN. Run 2999' of 4 1/2" Rement with 2% Sodi	aCl2, 1/4#/sk (249'. Wire Li 10.50# J-55 c ium Metasilic	celloflake, 15.60 ppg, 1.18 yield. ne survey @ 1212' = 1/2 degree. asing. Land casing at 2999', ate, 3#/sk celloflake, and 1/4#/sk	
,-1' GL. Cement surface ca Secure rig, SDFN. WOC. and surface casing to 600 p 428'. Secure rig, SDFN. hole to 1996'. Secure rig, S a. Drill 544' of 6 1/4" hole thole to 3025'. TD well. TO b'. Cement production casift yield. Did not circulate	asing with 120 sx Class E psi, held OK. Drill 937' SDFN. to 2540'. Secure rig, SDI DH with DP/DC and bit. ing with 177 sx Class B o back. Bump plug with 1	s cement with 3% Canew 6 1/4" hole to 1: FN. Run 2999' of 4 1/2" Rement with 2% Sodi	CI2, 1/4#/sk o 249'. Wire Li 10.50# J-55 c um Metasilic Secure rig, S	celloflake, 15.60 ppg, 1.18 yield. ne survey @ 1212' = 1/2 degree. asing. Land casing at 2999', ate, 3#/sk celloflake, and 1/4#/sk	
,-1' GL. Cement surface ca Secure rig, SDFN. WOC. and surface casing to 600 p 428'. Secure rig, SDFN. hole to 1996'. Secure rig, S b. Drill 544' of 6 1/4" hole to 3025'. TD well. TO bl'. Cement production casift yield. Did not circulate the procedure to bring ceme	psi, held OK. Drill 937' SDFN. to 2540'. Secure rig, SDI H with DP/DC and bit. ing with 177 sx Class B c back. Bump plug with 1	s cement with 3% Canew 6 1/4" hole to 1.2 FN. Run 2999' of 4 1/2" tement with 2% Sodi. 000 psi, shut in well	CI2, 1/4#/sk o 249'. Wire Li 10.50# J-55 c um Metasilic Secure rig, S	celloflake, 15.60 ppg, 1.18 yield. ne survey @ 1212' = 1/2 degree. asing. Land casing at 2999', ate, 3#/sk celloflake, and 1/4#/sk SDFN. WOC.	
,-1' GL. Cement surface ca Secure rig, SDFN. WOC. and surface casing to 600 p 428'. Secure rig, SDFN. hole to 1996'. Secure rig, S b. Drill 544' of 6 1/4" hole to 3025'. TD well. TO bl'. Cement production casift yield. Did not circulate the procedure to bring ceme	psi, held OK. Drill 937' SDFN. to 2540'. Secure rig, SDI H with DP/DC and bit. ing with 177 sx Class B of back. Bump plug with 1 ent to surface. Title Date	s cement with 3% Canew 6 1/4" hole to 1: FN. Run 2999' of 4 1/2" ement with 2% Sodi 000 psi, shut in well	10.50# J-55 c: um Metasilic: . Secure rig, S	celloflake, 15.60 ppg, 1.18 yield. ne survey @ 1212' = 1/2 degree. asing. Land casing at 2999', ate, 3#/sk celloflake, and 1/4#/sk	
,-1' GL. Cement surface ca Secure rig, SDFN. WOC. and surface casing to 600 p 428'. Secure rig, SDFN. hole to 1996'. Secure rig, S h. Drill 544' of 6 1/4" hole to hole to 3025'. TD well. TO b'. Cement production casi ft yield. Did not circulate is ut procedure to bring ceme	psi, held OK. Drill 937' SDFN. to 2540'. Secure rig, SDI H with DP/DC and bit. ing with 177 sx Class B c back. Bump plug with 1 ent to surface. Title Date	Rement with 3% Canew 6 1/4" hole to 1: FN. Run 2999' of 4 1/2" tement with 2% Sodi 000 psi, shut in well LANO.	10.50# J-55 c: um Metasilic: Secure rig, S	asing. Land casing at 2999', ate, 3#/sk celloflake, and 1/4#/sk SDFN. WOC.	
1' GL. Cement surface ca Secure rig, SDFN. WOC. and surface casing to 600 p 428'. Secure rig, SDFN. hole to 1996'. Secure rig, S a. Drill 544' of 6 1/4" hole: hole to 3025'. TD well. TO by Cement production casift yield. Did not circulate but procedure to bring cements or the procedure to bring cements of the procedure to bring cements.	psi, held OK. Drill 937' SDFN. to 2540'. Secure rig, SDI DH with DP/DC and bit. ing with 177 sx Class B c back. Bump plug with 1 ent to surface. Title Date	s cement with 3% Canew 6 1/4" hole to 1: FN. Run 2999' of 4 1/2" ement with 2% Sodi 000 psi, shut in well	10.50# J-55 c: um Metasilic: Secure rig, S	asing. Land casing at 2999', atc., 3#/sk celloflake, and 1/4#/sk SDFN. WOC. ACCEPTED FOR RECO	
,-1' GL. Cement surface ca Secure rig, SDFN. WOC. and surface casing to 600 p 428'. Secure rig, SDFN. hole to 1996'. Secure rig, S h. Drill 544' of 6 1/4" hole to hole to 3025'. TD well. TO b'. Cement production casi ft yield. Did not circulate is ut procedure to bring ceme	psi, held OK. Drill 937' SDFN. to 2540'. Secure rig, SDI DH with DP/DC and bit. ing with 177 sx Class B c back. Bump plug with 1 ent to surface. Title Date R FEDERAL OR S	Rement with 3% Canew 6 1/4" hole to 1: FN. Run 2999' of 4 1/2" tement with 2% Sodi 000 psi, shut in well LANO.	10.50# J-55 c: um Metasilic: Secure rig, S	asing. Land casing at 2999', ate, 3#/sk celloflake, and 1/4#/sk SDFN. WOC.	
	Gas Well Other ins Gas Well Other erating Company gton, NM, 87401 R, M, or Survey Description 28N, R8W ROPRIATE BOX(ES) T Acidize Alter Casing Casing Repair Change Plans Convert to Injection Operation (clearly state all peronally or recomplete horizont work will be performed or preved operations. If the operation of the control of the operation of the operations. If the operation of the opera	Gas Well Other Gas Well Other	erating Company Ston, NM, 87401 3b. Phone No. (include area code)	Use Form 3160 - 3 (APD) for such properties 30 70 70 70 70 70 70 70	

(Instructions on page 2)