

Submit 3 Copies To Appropriate District  
Office  
District I  
1625 N. French Dr., Hobbs, NM 88240  
District II  
1301 W. Grand Ave., Artesia, NM 88210  
District III  
1000 Rio Brazos Rd., Aztec, NM 87410  
District IV  
1220 S. St. Francis Dr., Santa Fe, NM  
87505

State of New Mexico  
Energy, Minerals and Natural Resources

Form C-103  
Revised March 25, 1999

OIL CONSERVATION DIVISION  
1220 South St. Francis Dr.  
Santa Fe, NM 87505

WELL API NO.	30-031-21007
5. Indicate Type of Lease	STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No.	VA-1683
7. Lease Name or Unit Agreement Name:	BOIS D' ARC WASH 36 # 1
8. Well No.	1
8. Pool name or Wildcat	WC 20N5W36J Mesaverde (Gas)

SUNDRY NOTICES AND REPORTS ON WELLS APR 2004  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:  
Oil Well ☐ Gas Well ☒ Other

2. Name of Operator  
SYNERGY OPERATING, LLC

3. Address of Operator  
PO BOX 5513 FARMINGTON, NM 87499 (505) 325-5449

4. Well Location

Unit Letter J, 1960' feet from the SOUTH line and 1485' feet from the EAST line

Section 36 Township 20 N Range 5 W NMPM MCKINLEY County

10. Elevation (Show whether DR, RKB, RT, GR, etc.)  
6620' GL

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐ CHANGE PLANS ☐

PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☒

CASING TEST AND CEMENT JOB ☐

OTHER: ☐

12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation.

Synergy Operating, LLC plugged and abandoned the subject well on 01-21-2002 in the following manner.

01-21-2002

MIRU BJ Services. ND WH. Unscrew 8-5/8" casing sub and wellhead. Install return lines. MU and run 1" PVC tubing inside of 8-5/8" Surface casing. Run to PBTD of 164'. Cut off PVC. Install Threaded coupling. Hang PVC and seal wellhead to allow circulation. BJ Services. Test lines. Establish rate with 4 bbls of water. Returns are clear water. Mix and place 12.3 bbls ( 69.50 ft3, 50 sxs) of Cement inside casing. Circulate good cement to surface. SD. Wash up Remove WH and 5' casing sub. Install Dryhole marker plate on top of hole. RD release cementers. Well has been plugged and abandoned. The cellar will be filled in with dirt available on location, to facilitate drilling of the replacement well.

A new well, the Wash 36 # 1-R will be drilled 20'+/- to the north of this well. A new APD will be submitted for this well.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Thomas E. Mullins TITLE Engineering Manager DATE 01-24-2002  
Type or print name Telephone No. (505) 566-3725

(This space for State use)

APPROVED BY H. Villanueva TITLE DEPUTY OIL & GAS INSPECTOR, DIST. 03 DATE AUG 24 2004  
Conditions of approval, if any:

8-24-04