This form is <u>not</u> to be used for reporting packer leakage tests in Southeast New Mexico

Completion Lower

Completion

Hour, Date, Shut-In

NEW MEXICO OIL CONSERVATION DIVISION

Page 1 Revised 11/16/98

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST in Southeast New Mexico Well CONOCOPHILLIPS COMPANY 217817 Lease Name SAN JUAN 32-8 UNIT No. 49 Operator Location Of Well: Unit Letter A Sec 15 Twp 32N Rge 8W API# 30-045-25394 Name of Reservoir or Pool Type of Prod. Method of Prod. Prod. Medium (Oil or Gas) (Flow or Art. Lift) (Tbg. Or Csg.) Upper PICTURED CLIFFS GAS **FLOWING** TUBING Completion Lower Completion **MESAVERDE** GAS FLOWING TUBING **Pre-Flow Shut-In Pressure Data** Upper Hour, Date, Shut-In Length of Time Shut-In SI Press. Psig Stabilized? (Yes or No) Completion 8/16/04 1500 hrs 72 hrs 280 Yes Length of Time Shut-In Hour, Date, Shut-In SI Press. Psig Stabilized? (Yes or No) Lower 8/16/04 1500 hrs Completion 72 hrs 320 Yes Flow Test No. 1 Commenced at (hour, date)*8/19/04 1520 hrs Zone producing (Upper or Lower): Lower Lapsed Time Prod. Zone Pressure Remarks Time (Hour, Date) Since* Upper Compl. Lower Compl. Temp. 8/19/04 0 hrs 280320 T/I Lower Zone; Upper Zone S/I 8/20/04 24 hrs 295 105 Flowing Lower Zone; Upper Zone S/I 8/21/04 48 hrs 300 110 Flowing Lower Zone; Upper Zone S/I 8/22/04 72 hrs 310 100 Flowing Lower Zone; T/I Upper Zone Production rate during test Oil: BOPD based on Bbls. In Grav. GOR Gas: MCFPD; Test thru (Orifice or Meter): Mid-Test Shut-In Pressure Data Upper Hour, Date, Shut-In Length of Time Shut-In SI Press. Psig Stabilized? (Yes or No)

(Continue on reverse side)

Length of Time Shut-In

SI Press. Psig

Stabilized? (Yes or No)

Flow Test No. 2

Commenced at (hour, date)**					Zone producing (Upper or Lower):			
Time	Lapsed Time	Pressure			Prod. Zone	Remarks		
(Hour, Date)	Since**	Upper Compl.	per Compl. Lower Comp		Temp.			
11					1			
1				·				
Production rate	during test							
Oil:	BOPD based on Bbls. In MCFPD; Test thru (Orifice or Meter):				Hrs	Grav	GOR	
	MCFP	D; Test thru (Ori	fice or Meter):					
Remarks:								
I hanabri aantifi	that the informat	ian harain aantai	and in two and	0000	nlata ta tha haat	of my Imavilada	^	
	that the informat				piete to the best	of my knowledg	c.	
Approved	AUG 24 2	`n n ./	20		Operator	CONOCOPH	ILLIPS COMPANY	
Approved AUG 2 4 2004 20 20 New Mexico Oil Conservation Division								
1 1 ()					By Daniel Deliver Dan Debrick			
By Cha	iliu K				Title		MSO	
					_	Q 23-ALL		
Title SERVIT OIL & CAS INSTITUTE, DIST. 40					Date	0-63-07		

Northwest New Mexico Packer Leakage Test Instructions

- 1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- 2. At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in case of a gas well and 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.
- 5. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.

- 6. Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hour tests: immediately prior to the beginning of each flow-period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.

24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.

8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 11-16-98, with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).