

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**
Sundry Notices and Reports on Wells

2004 AUG 27 AM 5:11

1. **Type of Well**
Other

2. **Name of Operator**

Central Resources, Inc. c/o NMOCD Aztec District Office

3. **Address & Phone No. of Operator**

1000 Rio Brazos Road, Aztec, NM 87410 505-334-6178

4. **Location of Well, Footage, Sec., T, R, M**

330' FSL and 1900' FEL, Section 14, T-31-N, R-17-W,

Case Number
BIA #14-20-603-2022

If Indian, All. or

Tribe Name

Navajo

7. **Unit Agreement Name**

Horseshoe Gallup Unit

Well Name & Number

HSGU #79

API Well No.

30-045-10703

10. **Field and Pool**

Horseshoe Gallup Unit

11. **County & State**

San Juan County, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission

☐ Notice of Intent

☒ Subsequent Report

☐ Final Abandonment

Type of Action

☒ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☐ Other -

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut off

☐ Conversion to Injection

13. Describe Proposed or Completed Operations

A-Plus Well Service Plugged and Abandoned the above well NMSA 1978, Section 13-1-127, Purchase Agreement: 04-521-0700028; Purchase Document: 04-199-000549.

7/16/04 MOL. RU rig. Change out wellhead. TOH and LD 45 joints 2-3/8" tubing and 4-1/2" packer. Shut in well.

7/19/04 Open well. PU 49 joints A+ workstring and round-trip 4-1/2" casing scraper to 1547'. TIH with tubing and set 4-1/2" DHS cement retainer at 1547'. Sting out of retainer. Load casing with 25 bbls of water. Pressure test casing to 500#, held OK. Sting into retainer and pump waste fluid, displace with water. Plug #1 with CR at 1547', spot 28 sxs Type III cement (37 cf) inside casing above CR up to 1142' to isolate the Gallup interval. Shut in well.

7/20/04 Open well, no pressure. TIH and tag cement at 873'. TOH and LD tubing. Perforate squeeze holes at 204'. Establish circulation out bradenhead with 21 bbls of water. Circulate BH annulus clean with an additional 9 bbls water. Plug #2 with 57 sxs Type III cement (75cf), pump down the 4-1/2" casing from 204' to surface, circulate good cement out bradenhead. WOC. Open well. ND BOP. Dig out and cut off wellhead. Found cement down 5' in the casing and at the surface in the annulus. Mix 10 sxs cement to fill casing and install P&A marker. RD and MOL.

H. Villanueva, NMOCD; W. Ashley, Navajo Minerals; M. Clah, Navajo EPA were on location.

SIGNATURE

William F. Clark
William F. Clark

Contractor

July 31, 2004

(This space for Federal or State Office use)

APPROVED BY

Title

Date

CONDITION OF APPROVAL, if any:

ACCEPTED FOR RECORD

NMOCD

AUG 30 2004

FARMINGTON FIELD OFFICE
BY *Sm*