

**UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT**  
Sundry Notices and Reports on Wells

2004 AUG 27 AM 11 05

1. **Type of Well**  
WIW

2. **Name of Operator**

Central Resources, Inc. c/o NMOCD Aztec District Office

3. **Address & Phone No. of Operator**

1000 Rio Brazos Road, Aztec, NM 87410 505-334-6178

4. **Location of Well, Footage, Sec., T, R, M**

660' FSL and 1980' FWL, Section 13, T-31-N, R-17-W,

RECEIVED

070 FARMINGTON NM

SEP 2004

OIL &amp; GAS DIV.

5. **Lease Number**  
BIA #14-20-603-2022

6. **If Indian, All. or Tribe Name**  
Navajo

7. **Unit Agreement Name**  
Horseshoe Gallup Unit

8. **Well Name & Number**  
HSGU #82

9. **API Well No.**  
30-045-10718

10. **Field and Pool**  
Horseshoe Gallup Unit

11. **County & State**  
San Juan County, NM

**12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA**

**Type of Submission**

☐ Notice of Intent

☒ Subsequent Report

☐ Final Abandonment

**Type of Action**

☒ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☐ Other -

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut off

☐ Conversion to Injection

**13. Describe Proposed or Completed Operations**

A-Plus Well Service Plugged and Abandoned the above well NMSA 1978, Section 13-1-127, Purchase Agreement: 04-521-0700028; Purchase Document: 04-199-000549.

7/9/04 MOL. Spot rig and equipment. Very long rig move over rough and dusty roads. SDFD.

7/12/04 Lay relief line to steel pit. RU and ND wellhead. Release packer. NU BOP, test. TOH and LD 47 joints 2-3/8" tubing and 5-1/2" packer. PU 46 joints A+ workstring and round-trip 5-1/2" casing scraper to 1461'.

7/13/04 Open well, no pressure. TIH with tubing and set 5-1/2" DHS cement retainer at 1461'. Sting out of retainer. Load casing with 19 bbls water then circulate well clean with an additional 17 bbls. Pressure test casing to 500# for 5 minutes, held OK. Sting into retainer and inject waste fluid from pit. Displace with water. Plug #1 with CR at 1461', spot 29 sxs Type III cement (38 cf) inside casing above CR up to 1182' to isolate the Gallup interval. TOH and LD tubing. Perforate 2 squeeze holes at 219'. Establish circulation out bradenhead with 10 bbls of water. Pump additional 7 bbls of water, oil circulating out bradenhead. Wait 15 minutes. Pump additional 7 bbls of water, recover 7 bbls oil out bradenhead. Wait 15 minutes. Pump additional 4 bbls of water, recover 3 bbls oil out bradenhead. Wait 15 minutes. Pump additional 4 bbls of water, recover 2 bbls oil out bradenhead. Plug #2 with 67 sxs Type III cement (88 cf), pump down the 5-1/2" casing from 219' to surface, circulate good cement out bradenhead. Shut in well. SDFD.

7/14/04 Open well, no pressure. ND BOP. Dig out and cut off wellhead. Found cement down 60' in 5-1/2" casing and down 2' in the annulus. Mix 12 sxs cement to fill casing and install P&A marker. RD and MOL. H. Villanueva, NMOCD; V. Euintillie, Navajo Minerals; W. Ashley, Navajo Minerals; J. Walker, Navajo EPA; and L. Lee, Navajo EPA were on location.

SIGNATURE William F. Clark Contractor

July 15, 2004

(This space for Federal or State Office use)

APPROVED BY \_\_\_\_\_

Title \_\_\_\_\_

CONDITION OF APPROVAL, if any: \_\_\_\_\_

**ACCEPTED FOR RECORD**

Date \_\_\_\_\_

**AUG 30 2004**

**NMOCD**

**FARMINGTON FIELD OFFICE**  
BY John