

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
Sundry Notices and Reports on Wells

2004 AUG 27 AM 11:07

1. **Type of Well**
WIW

RECEIVED 6.

070 FARMINGTON NM

Lease Number
BIA #14-20-603-2022

If Indian, All. or
Tribe Name
Navajo

7. **Unit Agreement Name**
Horseshoe Gallup Unit

2. **Name of Operator**
~~Central Resources, Inc.~~ c/o NMOCD Aztec District Office
PLAYA

3. **Address & Phone No. of Operator**
1000 Rio Brazos Road, Aztec, NM 87410 505-334-6178

4. **Location of Well, Footage, Sec., T, R, M**
674' FSL and 679' FEL, Section 14, T-31-N, R-17-W,

8. **Well Name & Number**
HSGU #80

API Well No.
30-045-10719

10. **Field and Pool**
Horseshoe Gallup Unit

11. **County & State**
San Juan County, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission**Type of Action**☐ Notice of Intent☒ Abandonment☐ Change of Plans☒ Subsequent Report☐ Recompletion☐ New Construction☐ Final Abandonment☐ Plugging Back☐ Non-Routine Fracturing☐ Casing Repair☐ Water Shut off☐ Altering Casing☐ Conversion to Injection☐ Other -

13. Describe Proposed or Completed Operations

A-Plus Well Service Plugged and Abandoned the above well NMSA 1978, Section 13-1-127, Purchase Agreement: 04-521-0700028; Purchase Document: 04-199-000549.

7/14/04 MOL and RU. Relief line to steel pit. ND wellhead. Release packer. NU BOP with flange, test.

7/15/04 Open well, no pressure. TOH and LD 47 joints 2-3/8" tubing and 5-1/2" packer. PU 45 joints A+ workstring and round-trip 5-1/2" casing scraper to 1430'. TIH with tubing and set 5-1/2" DHS cement retainer at 1430'. Sting out of retainer. Load casing with 21 bbls of water. Circulate well clean with an additional 15 bbls. Pressure test casing to 500# for 5 minutes, held OK. Sting into retainer and inject waste fluid from pit. Displace with water. Sting out of retainer. Plug #1 with CR at 1430', spot 29 sxs (38 CF) Type III cement inside casing above CR up to 1151' to isolate the Gallup interval. TOH and LD tubing. Perforate squeeze holes at 188'. Establish circulation out bradenhead with 10 bbls of water. Pump additional 2 bbls of water, oil circulating out bradenhead. Wait 15 minutes. Pump 4 bbls of water, circulate 3 bbls oil. Wait 15 minutes. Pump additional 4 bbls of water, circulate 2 bbls oil out bradenhead. Plug #2 with 54 sxs (71 CF) Type III cement, pump down 5-1/2" casing from 188' to surface, circulate good cement out bradenhead.

7/16/04 Open well, no pressure. ND BOP. Cut off wellhead. Mix 10 sxs Type III cement and install P&A marker. RD and MOL.

H. Villanueva, NMOCD; W. Ashley, Navajo Minerals; L. Lee, Navajo EPA were on location.

SIGNATURE William F. Clark Contractor

July 31, 2004

(This space for Federal or State Office use)

APPROVED BY _____ Title _____

ACCEPTED FOR RECORD

CONDITION OF APPROVAL, if any:

AUG 30 2004

NMOCD

FARMINGTON FIELD OFFICE
BY Sun