

**UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT**  
Sundry Notices and Reports on Wells

2004 AUG 27 AM 11:07

1. **Type of Well**  
Oil Well

RECEIVED  
070 FARMINGTON NM

**Lease Number**  
BIA #14-20-603-2022

6. **If Indian, All. or  
Tribe Name**

Navajo

2. **Name of Operator**

Central Resources, Inc. c/o NMOCD Aztec District Office

DIAYA

7. **Unit Agreement Name**  
Horseshoe Gallup Unit

3. **Address & Phone No. of Operator**

1000 Rio Brazos Road, Aztec, NM 87410 505-334-6178

8. **Well Name & Number**  
HSGU #72

9. **API Well No.**  
30-045-10803

**Location of Well, Footage, Sec., T, R, M**

1854' FNL and 2108' FEL, Section 14, T31N, R17W,

10. **Field and Pool**  
Horseshoe Gallup Unit

11. **County & State**  
San Juan County, NM

**12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA**

**Type of Submission**

☐ Notice of Intent

☒ Subsequent Report

☐ Final Abandonment

**Type of Action**

☒ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☐ Other -

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut off

☐ Conversion to Injection

**13. Describe Proposed or Completed Operations**

A-Plus Well Service Plugged and Abandoned the above well NMSA 1978, Section 13-1-127, Purchase Agreement: 04-521-0700028; Purchase Document: 04-199-000747.

7/1/04 MOL and RU. Open well. No pressure. NU BOP, test. Shut in well. SDFD.

7/2/04 No pressure. PU 41 joints A+ workstring and round-trip 5-1/2" casing scraper to 1303'. TIH with tubing and set 5-1/2" DHS cement retainer at 1303'. Sting out of retainer. Load the casing with 12 bbls of water. Pump additional 19 bbls of water to circulate well clean. Pressure test casing to 500# for 5 minutes, Held OK. Sting into retainer and pump fluid from pit below retainer, displace. Sting out of retainer. Plug #1 with CR at 1303', spot 41 sxs Type III cement (54 cf) inside casing above CR up to 908' to isolate the Gallup interval. TOH and LD tubing. Perforate squeeze holes at 163'. Establish circulation out bradenhead with 6 bbls of water. Pump additional 15 bbls of water to circulate BH annulus clean. Plug #2 with 54 sxs Type III cement (71 cf) pump down the 5-1/2" casing from 163' to surface, circulate good cement out bradenhead. Shut in well and SDFD.

7/6/04 ND BOP. Dig out and cut off wellhead. Found cement down 10' in casing and at surface in annulus. Mix 10 sxs Type III cement (13 cf) to fill casing and install P&A marker. RD and MOL.

H. Villanueva, NMOCD was on location.

SIGNATURE William F. Clark Contractor

July 31, 2004

(This space for Federal or State Office use)

APPROVED BY \_\_\_\_\_ Title \_\_\_\_\_

CONDITION OF APPROVAL, if any:

ACCEPTED FOR RECORD

AUG 30 2004

NMOCD

FARMINGTON FIELD OFFICE  
BY Sam