

Submit 3 Copies To Appropriate District Office
District I
1625 N. French Dr., Hobbs, NM 87240
District II
811 South First, Artesia, NM 87210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
2040 South Pacheco, Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION
2040 South Pacheco
Santa Fe, NM 87505

Form C-103
Revised March 25, 1999

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)		WELL API NO. 30-045-31278
1. Type of Well: Oil Well <input type="checkbox"/> Gas Well <input checked="" type="checkbox"/> Other		5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
2. Name of Operator ENERGEN RESOURCES CORPORATION		6. State Oil & Gas Lease No.
3. Address of Operator 2198 Bloomfield Highway, Farmington, NM 87401		7. Lease Name or Unit Agreement Name: Culpepper Martin
4. Well Location Unit Letter D : 1120 feet from the North line and 735 feet from the West line Section 07 Township 31N Range 12W NMPM County San Juan		8. Well No. 10S
10. Elevation (Show whether DR, RKB, RT, GR, etc.) 5817' GL		9. Pool name or Wildcat Basin Fruitland Coal

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☒

OTHER: ☐ OTHER: spud ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation.

Spud @ 5:15 pm on 03/05/03. Drill 12-1/4" hole to 238'. Ran 5 jts. 9-5/8" 32.3# H-40 ST&C casing, set @ 233'. RU Halliburton. Cement with 150 sks Class B, 1/4#/sk flocele, 2% CaCl2 (177 cu.ft.) Plug down @ 2:15 am on 03/06/03. Circulate 75 sks cement to surface. RD Halliburton. WOC. NU BOP. Test BOP & casing to 600 psi - ok.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Vicki Donaghey TITLE Production Assistant DATE 03/10/03

Type or print name Vicki Donaghey Telephone No. 505-325-6800

(This space for State use)

APPROVED BY Charlie Herrin TITLE DEPUTY OIL & GAS INSPECTOR, DIST. #1 DATE MAR 12 2003

Conditions of approval, if any: