This form is <u>not</u> to be used for reporting packer leakage tests in Southeast New Mexico

NEW MEXICO OIL CONSERVATION DIVISION

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST

Page 1 Revised 11/16/98

Well CONOCOPHILLIPS COMPANY 217817 Lease Name SAN JUAN 32-7 UNIT No. 41A Operator Rge 7W API# Location Of Well: Unit Letter N Sec 7 Twp 32N 30-045-25080 Type of Prod. Name of Reservoir or Pool Method of Prod. Prod. Medium (Oil or Gas) (Flow or Art. Lift) (Tbg. Or Csg.) Upper Completion PICTURED CLIFFS GAS **FLOWING** TUBING Lower Completion **MESAVERDE** GAS **FLOWING** TUBING **Pre-Flow Shut-In Pressure Data** Upper Hour, Date, Shut-In Length of Time Shut-In SI Press. Psig Stabilized? (Yes or No) 8/31/04 7 DAYS Completion 840 Hour, Date, Shut-In Lower Length of Time Shut-In SI Press. Psig Stabilized? (Yes or No) 8/3//04 Completion 7 DAYS 50Z Flow Test No. 1 Commenced at (hour, date)* 9/17/04 Zone producing (Upper or Lower): 3:30 Pm Lapsed Time Prod. Zone Time Pressure Remarks (Hour, Date) Since* Upper Compl. Lower Compl. Temp. 9/7/04 840 3:30 Pm 502 9/8/04 465 3:30 7m 503 9/9/04 432 3:30 Pm 504 9/10/04 420 505 3:30 Pm 9/11/04 412 505 3:30 9/12/04 420 505 3:30 Production rate during test Oil: BOPD based on Bbls. In Hrs. Grav. GOR Gas: MCFPD; Test thru (Orifice or Meter): Mid-Test Shut-In Pressure Data Hour, Date, Shut-In Upper Length of Time Shut-In SI Press. Psig Stabilized? (Yes or No) Completion Hour, Date, Shut-In Length of Time Shut-In Lower SI Press. Psig Stabilized? (Yes or No) Completion

(Continue on reverse side)

Flow Test No. 2

Commenced at (hour, date)**				one producing (Upper or Lower):		
Time	Lapsed Time	Pressure		Prod. Zone	Remarks	
(Hour, Date)	Since**	Upper Compl.	Lower Compl.	Temp.		
					-	
Production rate	during test					
Dil:BOPD based onBbls. In Gas:MCFPD; Test thru (Orifice or Meter): _			Bbls. In	Hrs	Grav	GOR
Gas:	MCFPI	O; Test thru (Orif	ice or Meter):			
Remarks:	that the informati	on herein contain	ed is true and con	aplete to the best of	of my knowledg	e
more by contain	SEP 2	1 2004	iod is true and our	ipiete to the best (of my knowledg	C.
Approved			20	Operator	CONOCOPH	ILLIPS COMPANY
New Mexico Oil Conservation Division By Chal The Conservation Division				By Pat	Letelre	Pat Lefebre
By Chal	lot			Title		MSO
Title	7 on a gas highe	CTG2. BIXY AM	Date 9/m	Date 9/10/pd		

Northwest New Mexico Packer Leakage Test Instructions

- 1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- 2. At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided lowever, that they need not remain shut-in more than seven days.
- For Flow Test No. 1, one zone of the dual completion shall be roduced at the normal rate of production while the other zone remains hut-in. Such test shall be continued for seven days in case of a gas well nd 24 hours in the case of an oil well. Note: if, on an initial packer sakage test, a gas well is being flowed to the atmosphere due to the lack f a pipeline connection the flow period shall be three hours.
- Following completion of Flow Test No. 1, the well shall again be utt-in, in accordance with Paragraph 3 above.

- 6. Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hour tests: immediately prior to the beginning of each flow-period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.

24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.

8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 11-16-98, with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).