

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FORM APPROVED  
Budget Bureau No. 1004-0135  
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.

Use "APPLICATION FOR PERMIT - -" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

Pro New Mexico Energy, Inc.

3. Address and Telephone No.

460 St. Michael's Dr., Santa Fe, NM 87505

(505) 988-4171

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

915' FNL & 1840' FWL  
Section 8, T26N, R11W

5. Lease Designation and Serial No.

SF 078899 A

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Gracia Federal 8C No. 2

9. API Well No.

30-045-31819

10. Field and Pool, or Exploratory Area

Basin Fruitland Coal

11. County or Parish, State

San Juan County, NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☐ Notice of Intent  
☒ Subsequent Report  
☐ Final Abandonment Notice

TYPE OF ACTION

☐ Abandonment  
☐ Recompletion  
☐ Plugging Back  
☐ Casing Repair  
☐ Altering Casing  
☒ Other Casing report.

☐ Change of Plans  
☐ New Construction  
☐ Non-Routine Fracturing  
☐ Water Shut-off  
☐ Conversion to Injection  
☐ Dispose Water

(Note: Report results of multiple completions on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Pressure tested surface casing and BOP to 750 psig for 30 min. - Held OK. Drilled 7 7/8" hole to 1760' KB. Ran 41 jts of 5 1/2", 15.5#, J-55 casing. Cemented casing with 220 sx (453.2 cf) of Class B cement containing 2% Sodium Metasilicate and 1/4 #/sk cello flakes and tailed in with 100 sx (118 cf) of Class B cement containing 2% CaCl and 1/4 #/sk cello flakes. Circulated 20 bbls of cement to surface. Casing landed at 1757' KB. PBD of 1714' KB.

14. I hereby certify that the foregoing is true and correct

Signed Dave J. Delmuth Title

Agent Date 9/28/2004

(This space for Federal or State office)

Approved by Title

Conditions of approval, if any:

ACCEPTED FOR RECORD  
Date

OCT 05 2004

FARMINGTON FIELD OFFICE

BY [Signature]

NMOCD