UNITED STATES

DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

Sundry	y Notices and Reports on Wells
	201 00 13 FM 2 50 Lease Number
	(897 Ub 10 11 2 55 Lease Number NMSF-079050B
l. Type of Well	RECEIVED 6. If Indian, All. or
GAS	070 FARMINGTON HIM Tribe Name
0.10	UTU PARMINUTAL TOTAL
·	7. Unit Agreement Name
2. Name of Operator	- Tr'00%
BURLINGTON	7 (NO 10 27 25)
RESOURCES	OIL & GAS COMPANY San Juan 28-6 Unit
	OC) 8. Well Name & Number
Address & Phone No. of	
PO Box 4289, Farmington	n, NM 87499 (505) 326-9700 9. API Well No.
1. Location of Well, Footag	
1590'FSL,195'FEL, Sec.26	6, T-28-N, R-6-W, NMPM Blanco MV/Basin DK
	11. County and State
	Rio Arriba, NM
2. CHECK APPROPRIATE BOX T	TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA
Type of Submission	Type of Action
Notice of Intent	Abandonment Change of Plans
V Colora Dan	Recompletion New Construction Plugging Back Non-Routine Fracturing
_X_Subsequent Report	
- -	Casing Repair Water Shut off
_x_Subsequent Report Final Abandonment	Casing Repair Water Shut off
Final Abandonment	Casing Repair Water Shut off Altering Casing Conversion to Injection X_Other Casing & Cement
Final Abandonment 13.Describe Proposed or	Casing Repair Water Shut off Haltering Casing Conversion to Injection X_Other Casing Cement Completed Operations
Final Abandonment 13.Describe Proposed or 09-26-04 MIRU. PT csg 6	Casing Repair Water Shut off Altering Casing Conversion to Injection X_Other Casing Cement Completed Operations 600 psi for 30 min, OK.
Final Abandonment 13.Describe Proposed or 09-26-04 MIRU. PT csg 6 09-27-04 TIH w/8-3/4" b	Casing Repair Water Shut off Altering Casing Conversion to Injection X_Other Casing Cement Completed Operations 600 psi for 30 min, OK. bit on 9-27-04. Tag cmt @ 95'.
Final Abandonment 13.Describe Proposed or 09-26-04 MIRU. PT csg 6 09-27-04 TIH w/8-3/4" b 09/29/04 Drill to inter	Casing Repair Water Shut off Altering Casing Conversion to Injection X_Other Casing Cement Completed Operations 600 psi for 30 min, OK. bit on 9-27-04. Tag cmt @ 95'. rmediate TD @ 3770'. Circ hole. TOOH. TIH w/88 joints 7",
Final Abandonment 13.Describe Proposed or 09-26-04 MIRU. PT csg 6 09-27-04 TIH w/8-3/4" b 09/29/04 Drill to inter 20#, J-55, ST&C set @ 37 09/30/04 Preflush w/20	Casing Repair Water Shut off Altering Casing Conversion to Injection X_Other Casing Cement Completed Operations 600 psi for 30 min, OK. bit on 9-27-04. Tag cmt @ 95'. rmediate TD @ 3770'. Circ hole. TOOH. TIH w/88 joints 7", 768'. bbls gel wtr, 2 bbls fresh wtr, 9 sx (28 cf-5 bbl slurry) premiur
Final Abandonment 13.Describe Proposed or 09-26-04 MIRU. PT csg 6 09-27-04 TIH w/8-3/4" b 09/29/04 Drill to inter 20#, J-55, ST&C set @ 37 09/30/04 Preflush w/20 Lite scavenger. Cmtd w/3	Casing Repair Water Shut off Altering Casing Conversion to Injection X_Other Casing Cement Completed Operations 600 psi for 30 min, OK. bit on 9-27-04. Tag cmt @ 95'. rmediate TD @ 3770'. Circ hole. TOOH. TIH w/88 joints 7", 768'. bbls gel wtr, 2 bbls fresh wtr, 9 sx (28 cf-5 bbl slurry) premium 33 sks Premium Lite Lead Cmt w/3% CACL2, 0.25 pps celloflake 5 pps
Final Abandonment 13.Describe Proposed or 09-26-04 MIRU. PT csg 6 09-27-04 TIH w/8-3/4" b 09/29/04 Drill to inter 20#, J-55, ST&C set @ 37 09/30/04 Preflush w/20 Lite scavenger. Cmtd w/3 LCM, 0.4% FL-52, 0.4% SM	Casing Repair Water Shut off Altering Casing Conversion to Injection X_Other Casing & Cement Completed Operations 600 psi for 30 min, OK. bit on 9-27-04. Tag cmt @ 95'. rmediate TD @ 3770'. Circ hole. TOOH. TIH w/88 joints 7", 768'. bbls gel wtr, 2 bbls fresh wtr, 9 sx (28 cf-5 bbl slurry) premium 33 sks Premium Lite Lead Cmt w/3% CACL2, 0.25 pps celloflake 5 pps MS. (70 CF-13 bbl slurry). Tailed w/90 Sks Type III w/1% CACL2, 0.
Final Abandonment 13.Describe Proposed or 09-26-04 MIRU. PT csg 6 09-27-04 TIH w/8-3/4" b 09/29/04 Drill to inter 20#, J-55, ST&C set @ 37 09/30/04 Preflush w/20 Lite scavenger. Cmtd w/3 LCM, 0.4% FL-52, 0.4% SM pps celloflake, 0.2% FL-	Casing Repair Water Shut off Altering Casing Conversion to Injection X Other Casing Cement Completed Operations 600 psi for 30 min, OK. bit on 9-27-04. Tag cmt @ 95'. rmediate TD @ 3770'. Circ hole. TOOH. TIH w/88 joints 7", 768'. bbls gel wtr, 2 bbls fresh wtr, 9 sx (28 cf-5 bbl slurry) premium 33 sks Premium Lite Lead Cmt w/3% CACL2, 0.25 pps celloflake 5 pps MS. (70 CF-13 bbl slurry). Tailed w/90 Sks Type III w/1% CACL2, 052 (124 CF-22 bbl slurry). Circ 20 bbls cmt to surface. Plug down
Final Abandonment 13.Describe Proposed or 09-26-04 MIRU. PT csg 6 09-27-04 TIH w/8-3/4" b 09/29/04 Drill to inter 20#, J-55, ST&C set @ 37 09/30/04 Preflush w/20 Lite scavenger. Cmtd w/3 LCM, 0.4% FL-52, 0.4% SM pps celloflake, 0.2% FL- @ 7:55 a.m. Preflush 2nd	Casing Repair Water Shut off Altering Casing Conversion to Injection X Other Casing Cement Completed Operations 600 psi for 30 min, OK. bit on 9-27-04. Tag cmt @ 95'. rmediate TD @ 3770'. Circ hole. TOOH. TIH w/88 joints 7", 768'. bbls gel wtr, 2 bbls fresh wtr, 9 sx (28 cf-5 bbl slurry) premium 33 sks Premium Lite Lead Cmt w/3% CACL2, 0.25 pps celloflake 5 pps MS. (70 CF-13 bbl slurry). Tailed w/90 Sks Type III w/1% CACL2, 052 (124 CF-22 bbl slurry). Circ 20 bbls cmt to surface. Plug down d stage w/20 bbls fresh wtr, 10 bbls mudflush, 10 bbls wtr. Cmtd
Final Abandonment 13.Describe Proposed or 09-26-04 MIRU. PT csg 6 09-27-04 TIH w/8-3/4" b 09/29/04 Drill to inter 20#, J-55, ST&C set @ 37 09/30/04 Preflush w/20 Lite scavenger. Cmtd w/3 LCM, 0.4% FL-52, 0.4% SM pps celloflake, 0.2% FL- @ 7:55 a.m. Preflush 2nd w/365 sks Premium Lite w	Casing Repair Water Shut off Altering Casing Conversion to Injection X Other Casing Cement Completed Operations 600 psi for 30 min, OK. bit on 9-27-04. Tag cmt @ 95'. rmediate TD @ 3770'. Circ hole. TOOH. TIH w/88 joints 7", 768'. bbls gel wtr, 2 bbls fresh wtr, 9 sx (28 cf-5 bbl slurry) premium 33 sks Premium Lite Lead Cmt w/3% CACL2, 0.25 pps celloflake 5 pps MS. (70 CF-13 bbl slurry). Tailed w/90 Sks Type III w/1% CACL2, 052 (124 CF-22 bbl slurry). Circ 20 bbls cmt to surface. Plug down d stage w/20 bbls fresh wtr, 10 bbls mudflush, 10 bbls wtr. Cmtd w/3% CACL2, 0.25% pps celloflake, 5 pps LCM-1, 0.4% FL-52, 0.4% Sh
Final Abandonment 13.Describe Proposed or 09-26-04 MIRU. PT csg 6 09-27-04 TIH w/8-3/4" b 09/29/04 Drill to inter 20#, J-55, ST&C set @ 37 09/30/04 Preflush w/20 Lite scavenger. Cmtd w/3 LCM, 0.4% FL-52, 0.4% SM pps celloflake, 0.2% FL- @ 7:55 a.m. Preflush 2nd w/365 sks Premium Lite w	Casing Repair Water Shut off Altering Casing Conversion to Injection X Other Casing Cement Completed Operations 600 psi for 30 min, OK. bit on 9-27-04. Tag cmt @ 95'. rmediate TD @ 3770'. Circ hole. TOOH. TIH w/88 joints 7", 768'. bbls gel wtr, 2 bbls fresh wtr, 9 sx (28 cf-5 bbl slurry) premium 33 sks Premium Lite Lead Cmt w/3% CACL2, 0.25 pps celloflake 5 pps MS. (70 CF-13 bbl slurry). Tailed w/90 Sks Type III w/1% CACL2, 052 (124 CF-22 bbl slurry). Circ 20 bbls cmt to surface. Plug down d stage w/20 bbls fresh wtr, 10 bbls mudflush, 10 bbls wtr. Cmtd
Final Abandonment 13.Describe Proposed or 09-26-04 MIRU. PT csg 6 09-27-04 TIH w/8-3/4" b 09/29/04 Drill to inter 20#, J-55, ST&C set @ 37 09/30/04 Preflush w/20 Lite scavenger. Cmtd w/3 LCM, 0.4% FL-52, 0.4% SM pps celloflake, 0.2% FL- @ 7:55 a.m. Preflush 2nd w/365 sks Premium Lite w (777 cf-138 bbls slurry. 10/01/04 PT csg to 1500	Casing Repair Water Shut off Altering Casing Conversion to Injection X Other Casing Cement Completed Operations 600 psi for 30 min, OK. bit on 9-27-04. Tag cmt @ 95'. rmediate TD @ 3770'. Circ hole. TOOH. TIH w/88 joints 7", 768'. bbls gel wtr, 2 bbls fresh wtr, 9 sx (28 cf-5 bbl slurry) premium 33 sks Premium Lite Lead Cmt w/3% CACL2, 0.25 pps celloflake 5 pps MS. (70 CF-13 bbl slurry). Tailed w/90 Sks Type III w/1% CACL2, 052 (124 CF-22 bbl slurry). Circ 20 bbls cmt to surface. Plug down di stage w/20 bbls fresh wtr, 10 bbls mudflush, 10 bbls wtr. Cmtd w/3% CACL2, 0.25% pps celloflake, 5 pps LCM-1, 0.4% FL-52, 0.4% Sh .) Circ 19 bbls cmt to surface. Bump Plug 2:00 pm 09/30/04. O psi for 30 min, OK. TIH w/6.25" bit. Drill cmt, shoe, and then the
Final Abandonment 13.Describe Proposed or 09-26-04 MIRU. PT csg 6 09-27-04 TIH w/8-3/4" b 09/29/04 Drill to inter 20#, J-55, ST&C set @ 37 09/30/04 Preflush w/20 Lite scavenger. Cmtd w/3 LCM, 0.4% FL-52, 0.4% SM pps celloflake, 0.2% FL- @ 7:55 a.m. Preflush 2nd w/365 sks Premium Lite w (777 cf-138 bbls slurry. 10/01/04 PT csg to 1500 TD @ 7970' reached on 10	Casing Repair Water Shut off Altering Casing Conversion to Injection X Other Casing Cement Completed Operations 600 psi for 30 min, OK. Oit on 9-27-04. Tag cmt @ 95'. Ormediate TD @ 3770'. Circ hole. TOOH. TIH w/88 joints 7", 768'. bbls gel wtr, 2 bbls fresh wtr, 9 sx (28 cf-5 bbl slurry) premium 33 sks Premium Lite Lead Cmt w/3% CACL2, 0.25 pps celloflake 5 pps MS. (70 CF-13 bbl slurry). Tailed w/90 Sks Type III w/1% CACL2, 052 (124 CF-22 bbl slurry). Circ 20 bbls cmt to surface. Plug down di stage w/20 bbls fresh wtr, 10 bbls mudflush, 10 bbls wtr. Cmtd w/3% CACL2, 0.25% pps celloflake, 5 pps LCM-1, 0.4% FL-52, 0.4% Sh .) Circ 19 bbls cmt to surface. Bump Plug 2:00 pm 09/30/04. O psi for 30 min, OK. TIH w/6.25" bit. Drill cmt, shoe, and then to 0/03/04. Circ hole. TIH w/186 Jts 4.5", 10.5#, J-55, ST&C csg set
Final Abandonment 13.Describe Proposed or 09-26-04 MIRU. PT csg 6 09-27-04 TIH w/8-3/4" b 09/29/04 Drill to inter 20#, J-55, ST&C set @ 37 09/30/04 Preflush w/20 Lite scavenger. Cmtd w/3 LCM, 0.4% FL-52, 0.4% SM pps celloflake, 0.2% FL- @ 7:55 a.m. Preflush 2nd w/365 sks Premium Lite w (777 cf-138 bbls slurry. 10/01/04 PT csg to 1500 TD @ 7970' reached on 10 @ 7965'. Preflush w/10 b	Casing Repair Water Shut off Altering Casing Conversion to Injection X_Other Casing & Cement Completed Operations 600 psi for 30 min, OK. Ott on 9-27-04. Tag cmt @ 95'. Other Casing End Conversion to Injection Other Casing & Cement Completed Operations 600 psi for 30 min, OK. Other Casing End Conversion to Injection Injection Other Casing End Conversion to Injection Injection Other Casing End Conversion to Injection Injection Other Cas
Final Abandonment 13.Describe Proposed or 09-26-04 MIRU. PT csg 6 09-27-04 TIH w/8-3/4" b 09/29/04 Drill to inter 20#, J-55, ST&C set @ 37 09/30/04 Preflush w/20 Lite scavenger. Cmtd w/3 LCM, 0.4% FL-52, 0.4% SM pps celloflake, 0.2% FL- @ 7:55 a.m. Preflush 2nd w/365 sks Premium Lite w (777 cf-138 bbls slurry. 10/01/04 PT csg to 1500 TD @ 7970' reached on 10 @ 7965'. Preflush w/10 b Tail w/275 sks Prem Lite	Casing Repair — Water Shut off Altering Casing — Conversion to Injection X_Other Casing & Cement Completed Operations 600 psi for 30 min, OK. bit on 9-27-04. Tag cmt @ 95'. rmediate TD @ 3770'. Circ hole. TOOH. TIH w/88 joints 7", 768'. bbls gel wtr, 2 bbls fresh wtr, 9 sx (28 cf-5 bbl slurry) premiur 33 sks Premium Lite Lead Cmt w/3% CACL2, 0.25 pps celloflake 5 pps MS. (70 CF-13 bbl slurry). Tailed w/90 Sks Type III w/1% CACL2, 052 (124 CF-22 bbl slurry). Circ 20 bbls cmt to surface. Plug down di stage w/20 bbls fresh wtr, 10 bbls mudflush, 10 bbls wtr. Cmtd w/3% CACL2, 0.25% pps celloflake, 5 pps LCM-1, 0.4% FL-52, 0.4% SM D.) Circ 19 bbls cmt to surface. Bump Plug 2:00 pm 09/30/04. Opsi for 30 min, OK. TIH w/6.25" bit. Drill cmt, shoe, and then to 0/03/04. Circ hole. TIH w/186 Jts 4.5", 10.5#, J-55, ST&C csg set bbls chem wash, 2 bbls FW. Cmtd w/9 sks prem lite HS FM (28 cf-5 bbls chem wash, 2 bbls FW. Cmtd w/9 sks prem lite HS FM (28 cf-5 bbls chem wash, 2 bbls FW. Cmtd w/9 sks prem lite HS FM (28 cf-5 bbls chem wash, 2 bbls FW. Cmtd w/9 sks prem lite HS FM (28 cf-5 bbls chem wash, 2 bbls FW. Cmtd w/9 sks prem lite HS FM (28 cf-5 bbls chem wash, 2 bbls FW. Cmtd w/9 sks prem lite HS FM (28 cf-5 bbls chem wash, 2 bbls FW. Cmtd w/9 sks prem lite HS FM (28 cf-5 bbls chem wash, 2 bbls FW. Cmtd w/9 sks prem lite HS FM (28 cf-5 bbls chem wash, 2 bbls FW. Cmtd w/9 sks prem lite HS FM (28 cf-5 bbls chem wash, 2 bbls FW. Cmtd w/9 sks prem lite HS FM (28 cf-5 bbls chem wash, 2 bbls FW. Cmtd w/9 sks prem lite HS FM (28 cf-5 bbls chem wash, 2 bbls FW. Cmtd w/9 sks prem lite HS FM (28 cf-5 bbls chem wash, 2 bbls FW. Cmtd w/9 sks prem lite HS FM (28 cf-5 bbls chem wash, 2 bbls FW. Cmtd w/9 sks prem lite HS FM (28 cf-5 bbls chem wash, 2 bbls FW. Cmtd w/9 sks prem lite HS FM (28 cf-5 bbls chem wash, 2 bbls FW. Cmtd w/9 sks prem lite HS FM (28 cf-5 bbls chem wash)
Final Abandonment 13.Describe Proposed or 09-26-04 MIRU. PT csg 6 09-27-04 TIH w/8-3/4" b 09/29/04 Drill to inter 20#, J-55, ST&C set @ 37 09/30/04 Preflush w/20 Lite scavenger. Cmtd w/3 LCM, 0.4% FL-52, 0.4% SM pps celloflake, 0.2% FL- @ 7:55 a.m. Preflush 2nd w/365 sks Premium Lite w (777 cf-138 bbls slurry. 10/01/04 PT csg to 1500 TD @ 7970' reached on 10 @ 7965'. Preflush w/10 b Tail w/275 sks Prem Lite 6.35 pps LCM-1, 1% FL-52	Casing Repair — Water Shut off Altering Casing — Conversion to Injection X_Other Casing & Cement Completed Operations 600 psi for 30 min, OK. bit on 9-27-04. Tag cmt @ 95'. rmediate TD @ 3770'. Circ hole. TOOH. TIH w/88 joints 7", 768'. bbls gel wtr, 2 bbls fresh wtr, 9 sx (28 cf-5 bbl slurry) premium 33 sks Premium Lite Lead Cmt w/3% CACL2, 0.25 pps celloflake 5 pps MS. (70 CF-13 bbl slurry). Tailed w/90 Sks Type III w/1% CACL2, 052 (124 CF-22 bbl slurry). Circ 20 bbls cmt to surface. Plug down di stage w/20 bbls fresh wtr, 10 bbls mudflush, 10 bbls wtr. Cmtd a/3% CACL2, 0.25% pps celloflake, 5 pps LCM-1, 0.4% FL-52, 0.4% St. b) Circ 19 bbls cmt to surface. Bump Plug 2:00 pm 09/30/04. O psi for 30 min, OK. TIH w/6.25" bit. Drill cmt, shoe, and then to 0/03/04. Circ hole. TIH w/186 Jts 4.5", 10.5#, J-55, ST&C csg set obls chem wash, 2 bbls FW. Cmtd w/9 sks prem lite HS FM (28 cf-5 bels Chem wash, 2 bbls FW. Cmtd w/9 sks prem lite HS FM (28 cf-5 bels Chem wash, 2 bbls FW. Cmtd w/9 sks prem lite HS FM (28 cf-5 bels Chem wash, 2 bbls FW. Cmtd w/9 sks prem lite HS FM (28 cf-5 bels Chem wash, 2 bbls FW. Cmtd w/9 sks prem lite HS FM (28 cf-5 bels Chem wash, 2 bbls FW. Cmtd w/9 sks prem lite HS FM (28 cf-5 bels Chem wash, 2 bbls FW. Cmtd w/9 sks prem lite HS FM (28 cf-5 bels Chem wash, 2 bbls FW. Cmtd w/9 sks prem lite HS FM (28 cf-5 bels Chem wash, 2 bbls FW. Cmtd w/9 sks prem lite HS FM (28 cf-5 bels Chem wash, 2 bbls FW. Cmtd w/9 sks prem lite HS FM (28 cf-5 bels Chem wash, 2 bbls FW. Cmtd w/9 sks prem lite HS FM (28 cf-5 bels Chem wash, 2 bbls FW. Cmtd w/9 sks prem lite HS FM (28 cf-5 bels Chem wash, 2 bbls FW. Cmtd w/9 sks prem lite HS FM (28 cf-5 bels Chem wash, 2 bbls FW. Cmtd w/9 sks prem lite HS FM (28 cf-5 bels Chem wash, 2 bbls FW. Cmtd w/9 sks prem lite HS FM (28 cf-5 bels Chem wash, 2 bbls FW. Cmtd w/9 sks prem lite HS FM (28 cf-5 bels Chem wash)
Final Abandonment 13.Describe Proposed or 09-26-04 MIRU. PT csg 6 09-27-04 TIH w/8-3/4" b 09/29/04 Drill to inter 20#, J-55, ST&C set @ 37 09/30/04 Preflush w/20 Lite scavenger. Cmtd w/3 LCM, 0.4% FL-52, 0.4% SM pps celloflake, 0.2% FL- @ 7:55 a.m. Preflush 2nd w/365 sks Premium Lite w (777 cf-138 bbls slurry. 10/01/04 PT csg to 1500 TD @ 7970' reached on 10 @ 7965'. Preflush w/10 b Tail w/275 sks Prem Lite 6.35 pps LCM-1, 1% FL-52	Casing Repair Water Shut off Altering Casing Conversion to Injection X Other Casing & Cement Completed Operations 600 psi for 30 min, OK. bit on 9-27-04. Tag cmt @ 95'. rmediate TD @ 3770'. Circ hole. TOOH. TIH w/88 joints 7", 768'. bbls gel wtr, 2 bbls fresh wtr, 9 sx (28 cf-5 bbl slurry) premium 33 sks Premium Lite Lead Cmt w/3% CACL2, 0.25 pps celloflake 5 pps MS. (70 CF-13 bbl slurry). Tailed w/90 Sks Type III w/1% CACL2, 052 (124 CF-22 bbl slurry). Circ 20 bbls cmt to surface. Plug down di stage w/20 bbls fresh wtr, 10 bbls mudflush, 10 bbls wtr. Cmtd w/3% CACL2, 0.25% pps celloflake, 5 pps LCM-1, 0.4% FL-52, 0.4% SM b) Circ 19 bbls cmt to surface. Bump Plug 2:00 pm 09/30/04. O psi for 30 min, OK. TIH w/6.25" bit. Drill cmt, shoe, and then to 0/03/04. Circ hole. TIH w/186 Jts 4.5", 10.5#, J-55, ST&C csg set bbls chem wash, 2 bbls FW. Cmtd w/9 sks prem lite HS FM (28 cf-5 bels SFM (545 cf-97 bbl slurry) w/0.25 pps Celloflake 0.3% CD-32, 20 Bump Plug. Rig Released 10/04/04. On next report. PT will be conducted by completion right.
Final Abandonment 13.Describe Proposed or 09-26-04 MIRU. PT csg 6 09-27-04 TIH w/8-3/4" b 09/29/04 Drill to inter 20#, J-55, ST&C set @ 37 09/30/04 Preflush w/20 Lite scavenger. Cmtd w/3 LCM, 0.4% FL-52, 0.4% SM pps celloflake, 0.2% FL- @ 7:55 a.m. Preflush 2nd w/365 sks Premium Lite w (777 cf-138 bbls slurry. 10/01/04 PT csg to 1500 TD @ 7970' reached on 10 @ 7965'. Preflush w/10 b Tail w/275 sks Prem Lite 6.35 pps LCM-1, 1% FL-52 TOC and csg PT will be o	Casing Repair Conversion to Injection X Other Casing & Cement Completed Operations 600 psi for 30 min, OK. bit on 9-27-04. Tag cmt @ 95'. cmediate TD @ 3770'. Circ hole. TOOH. TIH w/88 joints 7", 768'. bbls gel wtr, 2 bbls fresh wtr, 9 sx (28 cf-5 bbl slurry) premium 33 sks Premium Lite Lead Cmt w/3% CACL2, 0.25 pps celloflake 5 pps MS. (70 CF-13 bbl slurry). Tailed w/90 Sks Type III w/1% CACL2, 052 (124 CF-22 bbl slurry). Circ 20 bbls cmt to surface. Plug down di stage w/20 bbls fresh wtr, 10 bbls mudflush, 10 bbls wtr. Cmtd w/3% CACL2, 0.25% pps celloflake, 5 pps LCM-1, 0.4% FL-52, 0.4% SN c) Circ 19 bbls cmt to surface. Bump Plug 2:00 pm 09/30/04. D psi for 30 min, OK. TIH w/6.25" bit. Drill cmt, shoe, and then to 0/03/04. Circ hole. TIH w/186 Jts 4.5", 10.5#, J-55, ST&C csg set bbls chem wash, 2 bbls FW. Cmtd w/9 sks prem lite HS FM (28 cf-5) c HS FM (545 cf-97 bbl slurry) w/0.25 pps Celloflake 0.3% CD-32, c Bump Plug. Rig Released 10/04/04. con next report. PT will be conducted by completion rig ACCEPTED FOR RECORD
Final Abandonment 13.Describe Proposed or 09-26-04 MIRU. PT csg 6 09-27-04 TIH w/8-3/4" b 09/29/04 Drill to inter 20#, J-55, ST&C set @ 37 09/30/04 Preflush w/20 Lite scavenger. Cmtd w/3 LCM, 0.4% FL-52, 0.4% SM pps celloflake, 0.2% FL- @ 7:55 a.m. Preflush 2nd w/365 sks Premium Lite w (777 cf-138 bbls slurry. 10/01/04 PT csg to 1500 TD @ 7970' reached on 10 @ 7965'. Preflush w/10 b Tail w/275 sks Prem Lite 6.35 pps LCM-1, 1% FL-52	Casing Repair Water Shut off Altering Casing Conversion to Injection X_Other Casing & Cement Completed Operations 600 psi for 30 min, OK. bit on 9-27-04. Tag cmt @ 95'. rmediate TD @ 3770'. Circ hole. TOOH. TIH w/88 joints 7", 768'. bbls gel wtr, 2 bbls fresh wtr, 9 sx (28 cf-5 bbl slurry) premium 33 sks Premium Lite Lead Cmt w/3% CACL2, 0.25 pps celloflake 5 pps MS. (70 CF-13 bbl slurry). Tailed w/90 Sks Type III w/1% CACL2, 052 (124 CF-22 bbl slurry). Circ 20 bbls cmt to surface. Plug down di stage w/20 bbls fresh wtr, 10 bbls mudflush, 10 bbls wtr. Cmtd w/3% CACL2, 0.25% pps celloflake, 5 pps LCM-1, 0.4% FL-52, 0.4% SN .) Circ 19 bbls cmt to surface. Bump Plug 2:00 pm 09/30/04. Desi for 30 min, OK. TIH w/6.25" bit. Drill cmt, shoe, and then to complete the complete of the complete o
Final Abandonment 13.Describe Proposed or 09-26-04 MIRU. PT csg 6 09-27-04 TIH w/8-3/4" b 09/29/04 Drill to inter 20#, J-55, ST&C set @ 37 09/30/04 Preflush w/20 Lite scavenger. Cmtd w/3 LCM, 0.4% FL-52, 0.4% SM pps celloflake, 0.2% FL- @ 7:55 a.m. Preflush 2nd w/365 sks Premium Lite w (777 cf-138 bbls slurry. 10/01/04 PT csg to 1500 TD @ 7970' reached on 10 @ 7965'. Preflush w/10 b Tail w/275 sks Prem Lite 6.35 pps LCM-1, 1% FL-52 TOC and csg PT will be o	Casing Repair Altering Casing Conversion to Injection X Other Casing & Cement Completed Operations 600 psi for 30 min, OK. Oit on 9-27-04. Tag cmt @ 95'. Comediate TD @ 3770'. Circ hole. TOOH. TIH w/88 joints 7", 768'. bbls gel wtr, 2 bbls fresh wtr, 9 sx (28 cf-5 bbl slurry) premium 33 sks Premium Lite Lead Cmt w/3% CACL2, 0.25 pps celloflake 5 pps MS. (70 CF-13 bbl slurry). Tailed w/90 Sks Type III w/1% CACL2, 0. -52 (124 CF-22 bbl slurry). Circ 20 bbls cmt to surface. Plug down id stage w/20 bbls fresh wtr, 10 bbls mudflush, 10 bbls wtr. Cmtd M/3% CACL2, 0.25% pps celloflake, 5 pps LCM-1, 0.4% FL-52, 0.4% SN Circ 19 bbls cmt to surface. Bump Plug 2:00 pm 09/30/04. O psi for 30 min, OK. TIH w/6.25" bit. Drill cmt, shoe, and then to 0/03/04. Circ hole. TIH w/186 Jts 4.5", 10.5#, J-55, ST&C csg set obls chem wash, 2 bbls FW. Cmtd w/9 sks prem lite HS FM (28 cf-5) CH HS FM (545 cf-97 bbl slurry) w/0.25 pps Celloflake 0.3% CD-32, CH Bump Plug. Rig Released 10/04/04. On next report. PT will be conducted by completion rig. ACCEPTED FOR RECORD OUT 2 3 2004
Final Abandonment 13.Describe Proposed or 09-26-04 MIRU. PT csg 6 09-27-04 TIH w/8-3/4" b 09/29/04 Drill to inter 20#, J-55, ST&C set @ 37 09/30/04 Preflush w/20 Lite scavenger. Cmtd w/3 LCM, 0.4% FL-52, 0.4% SM pps celloflake, 0.2% FL- @ 7:55 a.m. Preflush 2nd w/365 sks Premium Lite w (777 cf-138 bbls slurry. 10/01/04 PT csg to 1500 TD @ 7970' reached on 10 @ 7965'. Preflush w/10 b Tail w/275 sks Prem Lite 6.35 pps LCM-1, 1% FL-52 TOC and csg PT will be o	Casing Repair Altering Casing Conversion to Injection X_Other Casing & Conversion to Injection X_Other Casing & Conversion to Injection Completed Operations 600 psi for 30 min, OK. bit on 9-27-04. Tag cmt @ 95'. cmediate TD @ 3770'. Circ hole. TOOH. TIH w/88 joints 7", 768'. bbls gel wtr, 2 bbls fresh wtr, 9 sx (28 cf-5 bbl slurry) premium 33 sks Premium Lite Lead Cmt w/3% CACL2, 0.25 pps celloflake 5 pps MS. (70 CF-13 bbl slurry). Tailed w/90 Sks Type III w/1% CACL2, 0. 52 (124 CF-22 bbl slurry). Circ 20 bbls cmt to surface. Plug down di stage w/20 bbls fresh wtr, 10 bbls mudflush, 10 bbls wtr. Cmtd w/3% CACL2, 0.25% pps celloflake, 5 pps LCM-1, 0.4% FL-52, 0.4% Sh .) Circ 19 bbls cmt to surface. Bump Plug 2:00 pm 09/30/04. O psi for 30 min, OK. TIH w/6.25" bit. Drill cmt, shoe, and then to 0/03/04. Circ hole. TIH w/186 Jts 4.5", 10.5#, J-55, ST&C csg set bels chem wash, 2 bbls FW. Cmtd w/9 sks prem lite HS FM (28 cf-5 he ch HS FM (545 cf-97 bbl slurry) w/0.25 pps Celloflake 0.3% CD-32, 2. Bump Plug. Rig Released 10/04/04. con next report. PT will be conducted by completion rig ACCEPTED FOR RECORL ACCEPTED FOR RECORL ACCEPTED FOR RECORL ACCEPTED FOR RECORL
Final Abandonment 13.Describe Proposed or 09-26-04 MIRU. PT csg 6 09-27-04 TIH w/8-3/4" b 09/29/04 Drill to inter 20#, J-55, ST&C set @ 37 09/30/04 Preflush w/20 Lite scavenger. Cmtd w/3 LCM, 0.4% FL-52, 0.4% SM pps celloflake, 0.2% FL- @ 7:55 a.m. Preflush 2nd w/365 sks Premium Lite w (777 cf-138 bbls slurry. 10/01/04 PT csg to 1500 TD @ 7970' reached on 10 @ 7965'. Preflush w/10 b Tail w/275 sks Prem Lite 6.35 pps LCM-1, 1% FL-52 TOC and csg PT will be o 4. I hereby certify that the foreg igned	Casing Repair
Final Abandonment 13.Describe Proposed or 09-26-04 MIRU. PT csg 6 09-27-04 TIH w/8-3/4" b 09/29/04 Drill to inter 20#, J-55, ST&C set @ 37 09/30/04 Preflush w/20 Lite scavenger. Cmtd w/3 LCM, 0.4% FL-52, 0.4% SM pps celloflake, 0.2% FL- @ 7:55 a.m. Preflush 2nd w/365 sks Premium Lite w (777 cf-138 bbls slurry. 10/01/04 PT csg to 1500 TD @ 7970' reached on 10 @ 7965'. Preflush w/10 b Tail w/275 sks Prem Lite 6.35 pps LCM-1, 1% FL-52 TOC and csg PT will be o	Casing Repair Water Shut off Altering Casing Conversion to Injection X_Other Casing & Cement Cement Completed Operations Completed Operations Completed To g 3770'. Circ hole. TOOH. TIH w/88 joints 7", 768' Circ hole. TOOH. TIH w/88 joints 7", 768' Circ hole. TOOH. TIH w/88 joints 7", 768' Circ Jobls gel wtr, 2 bbls fresh wtr, 9 sx (28 cf-5 bbl slurry) premium Sx (70 cF-13 bbl slurry). Tailed w/90 Sks Type III w/1% CACL2, 0.52 (124 cF-22 bbl slurry). Circ 20 bbls cmt to surface. Plug down distage w/20 bbls fresh wtr, 10 bbls mudflush, 10 bbls wtr. Cmtd w/3% CACL2, 0.25% pps celloflake, 5 pps LCM-1, 0.4% FL-52, 0.4% SN.) Circ 19 bbls cmt to surface. Bump Plug 2:00 pm 09/30/04. Dist for 30 min, OK. TIH w/6.25" bit. Drill cmt, shoe, and then to 0/03/04. Circ hole. TIH w/186 Jts 4.5", 10.5#, J-55, ST&C csg set obls chem wash, 2 bbls FW. Cmtd w/9 sks prem lite HS FM (28 cf-5 left) FM (545 cf-97 bbl slurry) w/0.25 pps Celloflake 0.3% CD-32, 2. Bump Plug. Rig Released 10/04/04. On next report. PT will be conducted by completion rig completion rig going is true and correct. Title Regulatory Specialist Date 10/12/04