NEW MEXICO ENERGY, MINERALS and NATURAL RESOURCES DEPARTMENT

This form is not to be used for reporting packer leakage tests in Southeast New Mexico

	···· ··· ···· ························						$\mathcal{K} = \mathcal{K}_{i}$	1 2000 19\	
								Page 1 Revised 11/16/98	
		NORTHWE	EST N	IEW MEXIC	O PACKER	-LEAKAGE	ETEST		
Оре	erator Willian	ns Produ	de	on_Lea	ase Name_	Rosa		Well No 14:	
Location of	of Well:Unit Lette	r_ <i>Ó</i> Sec	2	_Twp <u><i>3</i>]</u>	N Rge6V	<u>V</u> API#:	30-0 39:	2549300	
	NAME OF RES)L		OF PROD. or Gas)	METHOD OF PROD. (Flow or Art. Lift)		PROD.MEDIUM (Tbg. or Csg.)		
Upper Completion	Rosa 148 M		GAI		Floh		769		
Lower Completion	ROSA 148 MAKOTA			BAS		Flow		The	
		PRI	E-FL	OW SHUT-	IN PRESSU	RE DATA			
Upper Completion	Hour, date shut-in 4-10-43 0 640			Length of time shut-in		SI press. Psig		Stabilized? (Yes or No)	
Lower Completion	Hour, date shut-in 4-10-03 0 5:40			Length of time shut-in		SI press. Psig		Stabilized? (Yes or No)	
				FLOW T	EŚŤ NO. 1			7 0	
Commenced at (hour, date): 4-14-03 08:40				Zone producing (Upper or Lower): Low					
TIME (hour,date)	LAPSED TIME SINCE	SINCE.			RE PROD. ZON TEMP.			REMARKS	
4-15-03 0910 4-16-03	24 601	1774	1	15#	500				
0920	48201	177#	1/	10#	500			·	
0955	725a1	1707	10	60 H	520				
			┼						
Production r	ate during test								
Dil: BOPD based o				onBbls. inHoursGravGOF					
Gas:	85	M	CFP); Tested th	nru (Orifice)	r Meter):			
		MID	-TES	T SHUT-IN	PRESSUR	E DATA			
Upper Completion	Hour, date shursin		Length of time :		SI press psig		Stabilized? (Yes or No)		
Lower	Hour, date shut-in		Length of time :	shut-in	SI press. psig		Stabilized? (Yes or No)		

FLOW TEST NO. 2

Commenced	d at (hour, date)	••		Zone producing (Upper or Lowr):				
TIME (hour,date)	LAPSED TIME Since**	PRESS Upper Completion	URE Lower Completion	PROD. ZONE	REMARKS			
			, , , , , , , , , , , , , , , , , , , ,					
				·				
					·			
Production ra	te during test							
Oil: Gas:	ВОР[D based onMC	Bt FPD:Tested thru	ols. inHo (Orfice or Meter):	ursGravGOF	₹ -		
Remarks:								
I hereby certif	fy that the infor	mation herein co	ontained is true a	nd complete to the	bes of my knowledge.			
	MAY - 7		Operate	or williams	- PRoducTion			
			Ву _	-Jell Z				
ву <i>(М</i>	ule TY		Title _	TecH III				
Title OEPUTY CI	L & GAS PASTECT	TOR, DIST. \$50	Date -	4-17-03				

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- 1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- At least 72 hours prior to the commencement of any packer leakage test, the
 operator shall notify the Division in writing of the exact time the test is to be
 commenced. Offset operators shall also be so notified.
- 3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production white the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial
- packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.
- 5. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.
- 6. Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test no. 2 is to be the same as for Flow Test No. 1 except

that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.

7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow-period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test date.

24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.

8. The result s of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico oil Conservation Division on northwest new Mexico packer leakage Test Form Revised 11-16-98 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only)