

State of New Mexico
Energy, Minerals and Natural Resources Department
Oil Conservation Division

Sundry Notices and Reports on Wells


1. Type of Well
GAS

2. Name of Operator
BURLINGTON
RESOURCES OIL & GAS COMPANY LP

3. Address & Phone No. of Operator
PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M
890' FSL, 1750' FWL, Sec. 16, T-26-N, R-10-W, NMPM, San Juan County

API # (assigned by OCD)
30-045-26232
5. Lease Number
6. State Oil & Gas Lease #
E-2942-2
7. Lease Name/Unit Name
Huerfano Unit NP
8. Well No.
194E
9. Pool Name or Wildcat
Gallegos Gallup
10. Elevation:



Type of Submission	Type of Action
☐ Notice of Intent	☐ Abandonment
☒ Subsequent Report	☐ Recompletion
☐ Final Abandonment	☐ Plugging Back
	☐ Casing Repair
	☐ Altering Casing
	☒ Other - Temporarily abandon
	☐ Change of Plans
	☐ New Construction
	☐ Non-Routine Fracturing
	☐ Water Shut off
	☐ Conversion to Injection

13. Describe Proposed or Completed Operations

10-21-04 MIRU. TOOH w/238 3/4" rods & pump. SDON.
10-22-04 ND WH. NU BOP. TOOH w/195 jts 2 3/8" tbg. TIH w/gauge ring to 5702'. TOOH. TIH w/4 1/2" cmt retainer. Attempt to set cmt retainer @ 5702'. TOOH w/cmt retainer. TIH w/4 1/2" CIBP, set @ 5702'. TOOH. TIH, tag CIBP @ 5702'. Load hole w/90 bbl wtr & circ hole clean. PT 4 1/2" csg to 500 psi, OK. SD for weekend.
10-25-04 Load csg w/10 bbl wtr. Plug #1: pump 8 sx Type III cmt inside csg @ 5584-5702' to cover Gallup perforations. TOOH. TIH, perf 3 sqz holes @ 5575'. TOOH. Load hole w/20 bbl wtr. Establish injection into perfs @ 5575'. TOOH. TIH w/4 1/2" cmt retainer, set @ 5525'. PT csg to 1200 psi, OK. Establish injection into sqz holes @ 5575'. Plug #2: pump 35 sx Type III cmt outside csg @ 5475-5575'. Pump 11 sx Type III cmt inside csg to 5422-5525' cover Gallup top. TOOH to 3660'. Plug #3: pump 11 sx Type III cmt inside csg @ 3498-3660' to cover Mesaverde top. TOOH. TIH, perf 3 sqz holes @ 2985'. TOOH. TIH w/cmt retainer, set @ 2935'. TOOH. Establish injection into sqz holes. Plug #4: pump 35 sx Type III cmt outside csg @ 2885-2985'. Pump 11 sx Type III cmt inside csg @ 2832-2935' to cover Chacra top. TOOH. SDON.
10-26-04 ND BOP. Load csg w/wtr. NU WH. RU chart recorder. PT 4 1/2" csg to 500 psi/30 min, OK. RD. Rig released.
(Henry Villeneuve & Bruce Martin from OCD on location for plugging & casing test)
Test chart attached
Well temporarily abandoned 10-26-04

SIGNATURE Nancy Altman Senior Staff Specialist November 30, 2004

(This space for State Use)

Approved by

Charles R.

Title

DEPUTY OIL & GAS INSPECTOR, DIST. #1

Date

DEC - 1 2004

Cameron Valves Linda 327-0454

