

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

Sundry Notices and Reports on Wells

1. Type of Well  
GAS

2004 NOV 30 PM 12 51

RECEIVED  
070 FARMINGTON NM

5. Lease Number  
NMSF-080714  
6. If Indian, All. or  
Tribe Name  
7. Unit Agreement Name

2. Name of Operator  
**BURLINGTON**  
RESOURCES OIL & GAS COMPANY LP

3. Address & Phone No. of Operator  
PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M  
945' FNL, 1620' FWL, Sec.11, T-30-N, R-6-W, NMPM

8. Well Name & Number  
San Juan 30-6 Unit  
San Juan 30-6 U #136  
9. API Well No.  
30-039-26334  
10. Field and Pool  
Basin Fruitland Coal  
11. County and State  
Rio Arriba Co, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission

Type of Action

<input type="checkbox"/> Notice of Intent	<input checked="" type="checkbox"/> Abandonment	<input type="checkbox"/> Change of Plans
<input checked="" type="checkbox"/> Subsequent Report	<input type="checkbox"/> Recompletion	<input type="checkbox"/> New Construction
<input type="checkbox"/> Final Abandonment	<input type="checkbox"/> Plugging Back	<input type="checkbox"/> Non-Routine Fracturing
	<input type="checkbox"/> Casing Repair	<input type="checkbox"/> Water Shut off
	<input type="checkbox"/> Altering Casing	<input type="checkbox"/> Conversion to Injection
	<input type="checkbox"/> Other -	

13. Describe Proposed or Completed Operations

11-1-04 MIRU. ND WH. NU BOP. SDON.  
11-2-04 TIH w/4 1/2" scraper to 2900'. TOOH. TIH w/cmt retainer, set @ 2875'.  
PT bradenhead annulus to 1000 psi, OK. Load bradenhead annulus w/7.5 bbl  
wtr. Calculated TOC in bradenhead annulus @ 170'. Load 4 1/2" csg w/48 bbl wtr.  
Roll hole w/wtr. PT csg to 600 psi, failed. TOOH. TIH. Plug #1: pump 11 sx  
Type III cmt inside csg @ 2713-2875' to isolate Fruitland Coal top. WOC. SDON.  
11-3-04 TIH, tag TOC @ 2811'. TOOH to 2505'. Load csg w/wtr. PT 4 1/2" csg to 500 psi,  
OK. Plug #2: pump 25 sx Class "B" neat cmt inside csg @ 2166-2505' to cover  
Kirtland & Ojo Alamo tops. TOOH to 1100'. Plug #3: pump 11 sx Class "B" neat  
cmt inside csg @ 938-1100' to cover Nacimiento top. TOOH. (Changed procedure  
to fill bradenhead annulus w/cmt). TIH, perf 3 sqz holes @ 170'. Establish  
circ down csg & out bradenhead valve w/5 bbl wtr. TIH to 273'. Plug #4: pump  
65 sx Class "B" neat cmt: (1) fill 4 1/2" csg @ 0-273'; (2) close surface valve  
(3) fill bradenhead annulus @ 0-170'. Circ 1 bbl cmt out bradenhead valve.  
ND BOP. Cut off WH. Found cmt down 5' in 4 1/2" csg & at surface in annulus.  
Fill 4 1/2" csg & install dry hole marker w/20 sx Class "B" neat cmt. SDON.  
11-4-04 RD. Rig released. (Virgil Lucero, BLM was on location for plugging).

Well plugged and abandoned 11-4-04.

14. I hereby certify that the foregoing is true and correct.

Signed Nancy Oltmanns Title Senior Staff Specialist Date 11/30/04

(This space for Federal or State Office use)

APPROVED BY \_\_\_\_\_ Title \_\_\_\_\_ Date \_\_\_\_\_  
CONDITION OF APPROVAL, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

NMOCDD