Submit 3 Copies To Appropriate District Office District I State of New Mexico Energy, Minerals and Natural Resources	Form C-103 May 27, 2004
1625 N. French Dr., Hobbs, NM 87240 District II 1301 W. Grand Ave., Artesia, NM 88210 1220 South St. Francis Dr.	WELL API NO. 30-045-31705 5. Indicate Type of Lease
1000 Rio Brazos Rd., Aztec, NM 87410 Santa Fe, NM 87505	STATE 🔀 FEE 🗆
District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505	6. State Oil & Gas Lease No.
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-100 FOR SUCH PROPOSALS.)	7. Lease Name or Unit Agreement Name: Santa Rosa 6
1. Type of Well:	8. Well Number
Oil Well Gas Well X Other	4
2. Name of Operator	9. OGRID Number
Energen Resources Corporation 3. Address of Operator	162928 10. Pool name or Wildcat
2198 Bloomfield Highway - Farmington, NM 87401	Basin Fruitland Coal
4. Well Location	
Unit Letter I : 1995 feet from the South line and	660 feet from the East line
Section 06 Township 29N Range 09W	NMPM County San Juan
11. Elevation (Show whether DR, RKB, RT, GR, 5605' GL	etc.)
Pit or Below-grade Tank Application or Closure	Discharge Control and Control
Pit type Depth to Groundwater Distance from nearest fresh water well Distance from nearest surface water	
Pit Liner Thickness: mil Below-Grade Tank: Volumebbls; Constru	ction Material
12. Check Appropriate Box to Indicate Nature of Notice NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WOR TEMPORARILY ABANDON CHANGE PLANS COMMENCE DRI	JBSEQUENT REPORT OF: K
PULL OR ALTER CASING	ABANDONMENT
OTHER: OTHER: set ca	sing X
13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.	
11/05/04 TD:2504' PBTD:2448' Ran 57 jts. 5-1/2" 15.5# J-55 casing, set @ 2493' RU Halliburton. Cement with 370 sks 65/35 Std. poz, 6% gel, 2% CaCl2, 10#sk gilsonite, 1/4#/sk flocele tailed by 160 sks Class B, 1/4#/sk flocele, 5#/sk gilsonite (923 cu.ft.). Plug down @ 10:45 pm on 11/04/04. Circulate 30 bbls cement to surface. RDMO. Rig released @ 12:00 pm 11/05/04.	
I hereby certify that the information above is true and complete to the best of my knowle	
_ · · · · · · · · · · · · · · · · · · ·	dge and belief. I further certify that any pit or below-
grade tank has been will be constructed or closed according to NMOCD guidelines, a general peri	nit or an (attached) alternative OCD-approved plan
SIGNATURE SIGNATURE Product	nit or an (attached) alternative OCD-approved plan DATE 11/10/04
SIGNATURE TITLE Product E-mail address:	nit or an (attached) alternative OCD-approved plan occur. DATE 11/10/04 vdonaghe@energen.com Telephone No. 505-325-6800
SIGNATURE TITLE Product E-mail address:	nit or an (attached) alternative OCD-approved plan occur. DATE 11/10/04 vdonaghe@energen.com