NEW MEXICO ENERGY, MINERALS and NATURAL RESOURCES DEPARTMENT

This form is not to be used for reporting packer leakage tests in Southeast New Mexico

Hour, date shut-in

9:00 AM

Lower Completion Page 1

Revised 11/16/98 NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST Operator ENERGEN Resources Lease Name Jichtallia 98 Well No 12A Location of Well: Unit Letter N Sec & Twp 26N Rge 3W API # 30-0 39 - 27312 NAME OF RESERVOIR OR POOL METHOD OF PROD. PROD.MEDIUM TYPE OF PROD. (Flow or Art. Lift) (Tbg. or Csg.) (Oil or Gas) Upper TAPACITO - PC Completion Flow TB6 Lower Blanco - MV GAS- Dil ART. LIFT Completion PRE-FLOW SHUT-IN PRESSURE DATA Hour, date shut-in Length of time shut-in SI press. Psig Stabilized? (Yes or No) Upper Completion 8:30A 10/1/04 72 hrs. 107 Hour, date shut-in Length of time shut-in SI press. Psig Stabilized? (Yes or No) Lower 8:30 A Completion 72 hrs. Ves FLOW TEST NO. 1 Commenced at (hour, date)* /0/4/04 Zone producing (Upper or Lower): OWER LAPSED TIME **PRESSURE** PROD. ZONE TIME (hour,date) SINCE* TEMP. Upper Completion **Lower Completion** 101 10-4-04 0 271 TB6 10-5-04 9:00A 107 107 24 121 786 107 10% 48 120 TBG 9:00 A T06 72 120 TBG 9:00 A 10-8-04 96 120 TBG Production rate during test BOPD based on Bbls. in Hours Grav. **GOR** Oil: Gas: _MCFPD; Tested thru (Orifice or Meter): **MID-TEST SHUT-IN PRESSURE DATA** Length of time shut-in Stabilized? (Yes or No) Hour, date shut-in SI press psia Upper 9:00 Am 10/11/04 Completion

(Continue on reverse side)

72 hrs,

12hrs.

Length of time shut-in

107 TBG

270 TB6

SI press. psig

Stabilized? (Yes or No)

FLOW TEST NO. 2

Commenced at (hour, date)** 10/11/04 8/30 k				Zone producing (Upper or Lowr): Upper ~ PC		
TIME (hour,date) & 30 A (0 04	LAPSED TIME Since**	PRESS Upper Completion 107 107 786 C59	URE Lower Completion 270 786	PROD. ZONE	REMARKS	
8:30 A 10112104	a4	34 55 ' 186 CS9	270 TBG		START COMPRESSOR - PC	
8130 A 10/13/04	48	786 / C59	270 736		START COMPRESSOR - PC COMPRESSOR RUNNING	
8:30A 10/14/04	72	14 55 186 059	270 786		"// 11	
·					•	
		<u>`</u> ,				

	. •				
Oil:	BOPD based on	Bols. in	Hours	Grav	GOR
Gas:	MCFPD:	Tested thru (Orfice or	Meter):		
Remarks:					
I hereby certify	that the information herein contain	ed is true and comple	te to the best of	my knowledge	∍.
Approved	Conservation Division 20019	Operator <u>ENER</u>	GEN ROSO	URCES	
New Mexico Oil	Conservation Division 2, 2004	Ву Е	Maso	<u>. </u>	
By Cha	h Nerry	Title	apen		
Title OSPIII	Y OIL R GAS INSPECTING INSTERNAL	Date 1/1 -	19-04		

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.

Production rate during test

- 2. At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to the lack

of a pipeline connection the flow period shall be three hours.

- 5. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.
- 6. Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test no. 2 is to be the same as for Flow Test No. 1 except

that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.

7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: ueauweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow-period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as decired or may be approached as timely which hour products to the conclusion of each flow period. taken as desired, or may be requested on wells which have previously shown questionable test date.

24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on

8. The result s of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico oil Conservation Division on northwest new Mexico packer leakage Test Form Revised 11-16-98 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).