jts 7" 20# J-55 ST&C csg, set @ 3157'. Cmtd w/9 sxs Scavenger
cmt, 372 sxs Premium Lite cmt w/3% calcium chloride, 0.25 pps
celloflake, 5 pps LCM-1, 0.4% fluid loss, 0.4% SMS (792 cu.ft.).
Tail w/90 sxs Type III cmt w/1% calcium chloride, 0.25 pps
celloflake, 0.2% fluid loss (124 cu.ft.). Circ 10 bbls cmt to
surface. ND BOP. NU WH. RD. Rig released.
MIRU. ND WH. NU BOP. PT BOP & csg to 1500 psi/30 mins, OK. Drilling
ahead.
Drill to TD @ 3460'. Circ hole clean. TOOH.
TIH w/underreamer. Underream @ 3166-3460'. Circ hole clean. TOOH
w/underreamer. SDON.
TIH w/9 jts 5-1/2" 15.5# J-55 LT&C csg, set @ 3460'. Lnr top @ 3130'.
Lnr pre-perf @ 3176-3220', 3415-3436' across coal interval. SDON.
TIH w/perf mill. Mill perf plugs. TOOH w/perf mill. TIH w/110 jts
2-3/8" 4.7# J-55 tbg, set @ 3450'. ND BOP. NU WH.
TIH w/pump & rods. PT & pump action, OK. RD. Rig released.

14. I hereby certify that the fores	going is	true and co	errect.	
Signed Tammy Smed	Title	Regulatory	Specialist	DACCEPTED FOR RECORL
(This space for Federal or State Off: APPROVED BY	ice use) Title		Date	JAN n 7 2005
CONDITION OF APPROVAL, if any: Title 18 U.S.C. Section 1001, makes it a crime for any persor United States any false, fictitious or fraudulent statements	n knowingly an	d willfully to make	e to any department tter within its juri	or FARMING LUM FIELD OFFICE