

Submit 3 Copies To Appropriate District Office

DISTRICT I

1625 N. French Dr., Hobbs, NM 88240

DISTRICT II

1301 W. Grand Ave., Artesia, NM 87210

DISTRICT III

1000 Rio Brazos Rd., Aztec, NM 87410

DISTRICT IV

1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION
1220 South St. Francis Drive
Santa Fe, NM 87505

Form C-103
Revised March 25, 1999

WELL API NO.

30-045-32602

5. Indicate Type of Lease

STATE ☐

FEE ☒

6. State Oil & Gas Lease No.

34332

7. Lease Name or Unit Agreement Name

ALBERDING 03

8. Well No.

15

9. Pool name or Wildcat

BASIN DAKOTA/ BLANCO MESA VERDE

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

OIL

GAS

WELL ☐

WELL ☒

OTHER

2. Name of Operator

PATINA SAN JUAN, INC.

3. Address of Operator

5802 HIGHWAY 64, FARMINGTON, NEW MEXICO 87401

4. Well Location

Unit Letter O : 910 Feet From The SOUTH Line and 1980 Feet From The EAST Line

Section 3 Township 31N Range 13W NMPM County SAN JUAN

10. Elevat (Show whether DR, RKB, RT, GR, etc.)

5762' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

MULTIPLE ☐

COMPLETION ☐

OTHER: _____

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐

ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐

PLUG & ABANDONMENT ☐

CASING TEST & CEMENT JOB ☐

OTHER: Set 7" Casing ☒

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

12/23/04 TIH w/93 jts 7", 23#, N80 LTC casing. Land casing @ 4329'. Stage tool @ 3483'. Circ hole clean. Cement 1st stage w/65 sx (20bbl) scavenger of San Juan POZ, 4% gel, 0.2% Halad 9, 0.15#/sx FE-2, lead cement of 35 bbl (100 sx) 65/35 Cls B/Poz w/2% CaCl₂, 1/4# cellophane, 6% gel, 5#/sx Gilsonite @ 12.4ppg w/10.6 gpsx water to yield 2.02 cuft/sx, tail cement of 21 bbl (100 sx) Cls B w/2% CaCl₂, 1/4#/sx cellophane mixed @ 15.6ppg w/5.2 g/sx water yielding 1.18 cuft/sx. Circ for 2nd stage. Recover 20bbl 1st stage cement. Cement 2nd stage w/65sx (20bbl) scavenger of SJ POZ, 4% gel, 0.2% Halad 9, 0.15#/sx Gilsonite @ 12.4ppg w/10.6 gpsx wtr to yield 2.02 cuft/sx tail cement of 12 bbl (50sx) 50/50 standard Poz w/0.3% Halad 344, 5#/sx Gilsonite, 1/4#/sx cellophane @ 13.5ppg w/ 5.19 gal/sx water to yield 1.30 cuft/sx. Circ 95bbl cement.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

Kay S. Eckstein

TITLE

PRODUCTION TECHNICIAN DATE

29-Dec-04

TYPE OR PRINT NAME

KAY S. ECKSTEIN

TELEPHONE NO. (505) 632-8056

(This space for State Use)

APPROVED BY

Chad Herrin

TITLE

Acting SUPERVISOR DISTRICT # 3

DATE

JAN - 4 2005

CONDITIONS OF APPROVAL, IF ANY: