Form 3160-5 (November 1994)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or reenter an abandoned well. Use Form 3160-3 (APD) for such proposals.

| | FORM AL | PPROVEI | |
|---|------------|------------|--|
| / | OMB No. | 1004-013 | |
| | Expires Ju | lv 31, 199 | |

Lease Serial No.

AM-078863

6. If Indian, Allottee or Tribe Name

| | | | 2004 L | 7[If Unit or C | A/Agreement, Name and/or No. | | |
|--|--|---|---|---|--|--|--|
| SUBMIT IN TRIPL | ICATE – Other instru | ctions on reverse | side | RECEIN | /Fh | | |
| 1. Type of Well 07 | | | | | D FARMINGTON AM | | |
| Oil Well X Gas Well Other | | | | | 8. Well Name and No. | | |
| 2. Name of Operator | | | | | KRAUSE #7s | | |
| M & G Drilling Company Inc | LC (Agent) | | 9. API Well N | 0. | | | |
| 3a. Address | 3b. Phone No. (include area code) | | 30-045-32471 | | | | |
| c/o: Pippin, 3104 N. Sullivar | 505-327-4573 | | 10. Field and Pool, or Exploratory Area | | | | |
| 4. Location of Well (Footage, Sec., 7 | | | Basin Fruitland Coal | | | | |
| 760' FSL 890' FEL (P) Sec. | | | 11. County or Parish, State | | | | |
| , , | | | | San Juan (| County, New Mexico | | |
| 12 CHECK APPROPRIATE DO | VCC) TO BIDICATE NAT | THE OF NOTICE DE | DORT OR OT | <u>L</u> | | | |
| 12. CHECK APPROPRIATE BO | | UKE OF NOTICE, RE | roki, ok oi | DER DATA | · · · · · · · · · · · · · · · · · · · | | |
| TYPE OF SUBMISSION | TYPE OF ACTION | | | ··· | | | |
| Notice of Intent | Acidize | Deepen | | (Start/Resume) | ☐ Water Shut-Off | | |
| | Alter Casing | Fracture Treat | Reclamation | | Well Integrity | | |
| X Subsequent Report | Casing Repair Change Plans | New Construction Plug and Abandon | ☐ Recomplete ☐ Temporarily | | Other DRILLING | | |
| Final Abandonment Notice | Convert to Injection | Plug Back | Water Disp | | Officiality | | |
| 12/1/2004: | | | | | | | |
| Drilled 6-1/4" hole to 17 w/2% SM, 3#/sx gilsonit w/2% SM & 3#/gal gilso cl "B" w/4% gel, 2% Cargood cmt to surface. | te, 1/4#/sx celloflake m inite & 1/4#/gal celloflal | ixed @ 10.5 ppg & ke mixed at 12.5 #/ | 5.2 cf/sx. F gal w/ yeild | followed w/1 of 2.06 cf/sx | 28 sx (264 cf) CI "B" c. Tail w/37 sx (52 cf) | | |
| Drilled 6-1/4" hole to 17 w/2% SM, 3#/sx gilsonit w/2% SM & 3#/gal gilso cl "B" w/4% gel, 2% Car good cmt to surface. | te, 1/4#/sx celloflake m nite & 1/4#/gal celloflal cl2, 3#/sx gilsonite& 1/4 | ixed @ 10.5 ppg & ke mixed at 12.5 #/ | 5.2 cf/sx. F gal w/ yeild | followed w/1 of 2.06 cf/sx | 28 sx (264 cf) CI "B" c. Tail w/37 sx (52 cf) | | |
| Drilled 6-1/4" hole to 17 w/2% SM, 3#/sx gilsonit w/2% SM & 3#/gal gilso cl "B" w/4% gel, 2% Cargood cmt to surface. 14. Thereby certify that the foregoing Name (<i>Printed/Typed</i>) | te, 1/4#/sx celloflake menite & 1/4#/gal celloflal cl2, 3#/sx gilsonite& 1/4 | ixed @ 10.5 ppg & ke mixed at 12.5 #/ | 5.2 cf/sx. F gal w/ yeild ced @ 14.5 p | followed w/1 of 2.06 cf/sappg, & 1.40 | 28 sx (264 cf) CI "B" (. Tail w/37 sx (52 cf) cf/sx. Circ. 20 bbls | | |
| Drilled 6-1/4" hole to 17 w/2% SM, 3#/sx gilsonit w/2% SM & 3#/gal gilso cl "B" w/4% gel, 2% Cad good cmt to surface. 14. I hereby certify that the foregoing Name (Printed/Typed) Mike | te, 1/4#/sx celloflake m nite & 1/4#/gal celloflal cl2, 3#/sx gilsonite& 1/4 | ixed @ 10.5 ppg & ke mixed at 12.5 #/ 1#/sx celloflake mix | 5.2 cf/sx. F gal w/ yeild ced @ 14.5 p | followed w/1 of 2.06 cf/sx | 28 sx (264 cf) CI "B" (. Tail w/37 sx (52 cf) cf/sx. Circ. 20 bbls | | |
| Drilled 6-1/4" hole to 17 w/2% SM, 3#/sx gilsonit w/2% SM & 3#/gal gilso cl "B" w/4% gel, 2% Cargood cmt to surface. 14. Thereby certify that the foregoing Name (<i>Printed/Typed</i>) | te, 1/4#/sx celloflake menite & 1/4#/gal celloflal cl2, 3#/sx gilsonite& 1/4 | ixed @ 10.5 ppg & ke mixed at 12.5 #/ 1#/sx celloflake mix | 5.2 cf/sx. F gal w/ yeild ced @ 14.5 p | followed w/1 of 2.06 cf/sappg, & 1.40 | 28 sx (264 cf) CI "B" (. Tail w/37 sx (52 cf) cf/sx. Circ. 20 bbls | | |
| Drilled 6-1/4" hole to 17 w/2% SM, 3#/sx gilsonit w/2% SM & 3#/gal gilso cl "B" w/4% gel, 2% Car good cmt to surface. 14. I hereby certify that the foregoing Name (Printed/Typed) Mike | te, 1/4#/sx celloflake menite & 1/4#/gal celloflal cl2, 3#/sx gilsonite& 1/4 sistrue and correct | ixed @ 10.5 ppg & ke mixed at 12.5 #/ 1#/sx celloflake mix | 5.2 cf/sx. F gal w/ yeild ked @ 14.5 p Petr. I | Followed w/1 of 2.06 cf/s opg, & 1.40 Engr. (Agen | 28 sx (264 cf) CI "B" (. Tail w/37 sx (52 cf) cf/sx. Circ. 20 bbls | | |
| Drilled 6-1/4" hole to 17 w/2% SM, 3#/sx gilsonit w/2% SM & 3#/gal gilso cl "B" w/4% gel, 2% Car good cmt to surface. 14. I hereby certify that the foregoing Name (Printed/Typed) Mike | te, 1/4#/sx celloflake menite & 1/4#/gal celloflal cl2, 3#/sx gilsonite& 1/4 sistrue and correct | ixed @ 10.5 ppg & ke mixed at 12.5 #/ 1#/sx celloflake mix Title Date | 5.2 cf/sx. F gal w/ yeild ked @ 14.5 p Petr. I | Followed w/1 of 2.06 cf/s opg, & 1.40 Engr. (Agen | 28 sx (264 cf) CI "B" (. Tail w/37 sx (52 cf) cf/sx. Circ. 20 bbls | | |

fraudulent statements or representations as to any matter within its jurisdiction.