

State of New Mexico
Energy, Minerals and Natural Resources Department
Oil Conservation Division

Sundry Notices and Reports on Wells

1. Type of Well
GAS

2. Name of Operator

**BURLINGTON
RESOURCES**

OIL & GAS COMPANY

3. Address & Phone No. of Operator

PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M

1200' FNL, 2390' FEL, Sec. 22, T-30-N, R-11-W, NMPM, San Juan County

API # (assigned by OCD)
30-045-29936

5. Lease Number
Fee

6. State Oil&Gas Lease #

7. Lease Name/Unit Name

Vasaly Com

8. Well No.
#2

9. Pool Name or Wildcat
Wildcat Pennsylvanian

10. Elevation:

Type of Submission

Type of Action

☐ Notice of Intent

☐ Abandonment

☐ Change of Plans

☒ Subsequent Report

☐ Recompletion

☐ New Construction

☐ Final Abandonment

☐ Plugging Back

☐ Non-Routine Fracturing

☐ Casing Repair

☐ Water Shut off

☐ Altering Casing

☐ Conversion to Injection

☒ Other - casing & cement

13. Describe Proposed or Completed Operations

11-12-99 Drill to intermediate TD @ 6994'. Circ hole clean.

11-13-99 TOOH. TIH w/155 jts 9 5/8" 47# L-80 LT&C csg, set @ 6994'. Circ.

11-14-99 PT lines to 4000 psi, OK. Cmt'd w/1570 sx Class "H" 50/50 poz w/ 2% gel, 0.25 pps flocele, 5 pps gilsonite, 0.4% Halad-344, 0.15% HR-5, 0.2% CFR-3 (1994 cu ft). Circ 50 bbl cmt to surface. Cmt 2nd stage w/1340 sx Class "B" 65/35 poz w/6% gel, 0.25 pps flocele, 5 pps gilsonite (2412 cu ft). Circ 50 bbl cmt to surface. WOC.

11-15-99 NU BOP. PT csg to 4800 psi/30 mins, OK. PT lower & upper pipe rams to 7500 psi/15 min, OK. PT annular to 5000 psi/15 min, OK. PT blind rams & manifold valves to 7500 psi/15 min, OK. Drilling ahead.

CONFIDENTIAL

SIGNATURE

Regina Cole

Regulatory Administrator December 20, 1999

TLW

(This space for State Use)

DEPUTY OIL & GAS INSPECTOR, DIST. 03

Approved by

Charles T. H.

Title

Date

12-21-99