

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS
Do not use this form for proposals to drill or to re-enter an abandoned well. Use form 3160-3 (APD) for such proposals.

FORM APPROVED
OMB NO. 1004-0135
Expires: November 30, 2000

5. Lease Serial No.
NMSF078278

6. If Indian, Allottee or Tribe Name

7. If Unit or CA/Agreement, Name and/or No.
NMNM78416B

8. Well Name and No.
SAN JUAN 29-6 UNIT 90F

9. API Well No.
PHIL 10-933-07623-00-X1

10. Field and Pool, or Exploratory
BASIN DAKOTA
BLANCO MESAVERDE

11. County or Parish, and State
RIO ARriba COUNTY, NM

SUBMIT IN TRIPLICATE - Other instructions on reverse side.

1. Type of Well
☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator
CONOCOPHILLIPS COMPANY

Contact: CHRIS GUSTARTIS
E-Mail: CHRISTINA.GUSTARTIS@CONOCO

3a. Address
P O BOX 2197 WL 6106
HOUSTON, TX 77252

3b. Phone No. (include area code)
Ph: 832.486.2463

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

Sec 15 T29N R6W NENE 400FNL 400FEL
36.73185 N Lat, 107.44212 W Lon

12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION	TYPE OF ACTION			
<input type="checkbox"/> Notice of Intent	<input type="checkbox"/> Acidize	<input type="checkbox"/> Deepen	<input type="checkbox"/> Production (Start/Resume)	<input type="checkbox"/> Water Shut-Off
<input checked="" type="checkbox"/> Subsequent Report	<input type="checkbox"/> Alter Casing	<input type="checkbox"/> Fracture Treat	<input type="checkbox"/> Reclamation	<input type="checkbox"/> Well Integrity
<input type="checkbox"/> Final Abandonment Notice	<input type="checkbox"/> Casing Repair	<input type="checkbox"/> New Construction	<input type="checkbox"/> Recomplete	<input checked="" type="checkbox"/> Other
	<input type="checkbox"/> Change Plans	<input type="checkbox"/> Plug and Abandon	<input type="checkbox"/> Temporarily Abandon	Drilling Operations
	<input type="checkbox"/> Convert to Injection	<input type="checkbox"/> Plug Back	<input type="checkbox"/> Water Disposal	

13. Describe Proposed or Completed Operation (clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recompleate horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompleation in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the site is ready for final inspection.)

Casing was set in this well as per the attached wellbore schematic.



14. I hereby certify that the foregoing is true and correct.

Electronic Submission #51801 verified by the BLM Well Information System

For CONOCOPHILLIPS COMPANY, sent to the Farmington

Committed to AFMSS for processing by ADRIENNE BRUMLEY on 12/17/2004 (05AXB0502SE)

Name (Printed/Typed) CHRIS GUSTARTIS

Title AUTHORIZED REPRESENTATIVE

Signature (Electronic Submission)

Date 12/13/2004

THIS SPACE FOR FEDERAL OR STATE OFFICE USE

Approved By

ACCEPTED

ADRIENNE BRUMLEY
Title PETROLEUM ENGINEER

Date 12/17/2004

Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Office Farmington

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

**** BLM REVISED ** BLM REVISED ** BLM REVISED ** BLM REVISED ** BLM REVISED ****

RECEIVED

Well Name: San Juan 29-6 #90F
 API #: 30-039-27623
 Location: 400' FNL & 400' FEL
 Sec. 15 - T29N - R6W
 Rio Arriba County, NM
 Elevation: 6748' GL (above MSL)
 Dri Rig RKB: 13' above Ground Level
 Datum: Dri Rig RKB = 13' above GL

Spud: 28-Nov-04
 Spud Time: 4:30
 Date TD Reached: 9-Dec-04
 Release Dri Rig: 13-Nov-04
 Release Time: 0:00

11" 3M x 7 1/16" 5M Tubing Head
 11" 3M x 11" 3M Casing Spool
 9-5/8" 8 RD x 11" 3M Casing Head

Surface Casing Date set: 28-Nov-04
 Size 9 5/8 in
 Set at 255 ft # Jnts: 5
 Wt. 32.3 ppf Grade H-40
 Hole Size 12 1/4 in Conn STC
 Excess Cmt 125 %
 T.O.C. SURFACE
 Csg Shoe 255 ft
 TD of 12-1/4" hole 285 ft

Notified BLM @ 17:00 hrs on 26-Nov-04
 Notified NMOCD @ 17:02 hrs on 26-Nov-04

Intermediate Casing Date set: 6-Dec-04
 Size 7 in 93 jts
 Set at 3922 ft 0 pups
 Wt. 20 ppf Grade J-55
 Hole Size 8 3/4 in Conn STC
 Excess Cmt 150 % Top of Float Collar 3876 ft
 T.O.C. SURFACE Bottom of Casing Shoe 3922 ft
 Pup @ ft TD of 8-3/4" Hole 3928 ft
 Pup @ ft
 Notified BLM @ 10:29 hrs on 02-Dec-04
 Notified NMOCD @ 10:31 hrs on 02-Dec-04

Production Casing: Date set: 10-Dec-04
 Size 4 1/2 in 193 jts
 Set at 8161 ft 1 pups
 Wt. 11.6 ppf Grade N-80
 Hole Size 6 1/4 in Conn LTC
 Excess Cmt 50 % Top of Float Collar 8159 ft
 T.O.C. (est) Bottom of Casing Shoe 8161 ft
 Marker Jt @ 5261.9 ft TD of 8-3/4" Hole 8161 ft
 Marker Jt @ 7810.5 ft
 Marker Jt @ ft

Notified BLM @ hrs on
 Notified NMOCD @ hrs on

Top of Float Collar 8159 ft
 Bottom of Casing Shoe 8161 ft

TD of 8-3/4" Hole: 8161 ft

Surface Cement
 Date cmt'd: 28-Nov-04
 Lead : 150' sx Class G Cement
 + 3% S001 Calcium Chloride
 + 0.25 lb/sx D029 Cellophane Flakes
 1.16 cuft/sx, 174.0 cuft slurry at 15.8 ppg
 Displacement: bbls fresh wtr
 Bumped Plug at: 21:36 hrs w/ 850 psi
 Final Circ Press:
 Returns during job: YES
 CMT Returns to surface: 12 bbls
 Floats Held: No floats used
 W.O.C. for 6.00 hrs (plug bump to start NU BOP)
 W.O.C. for 15.00 hrs (plug bump to test csg)

Intermediate Cement
 Date cmt'd: 6-Dec-04
 Lead : 420' sx Class G Cement
 + 0.25 lb/sx D029 Cellophane Flakes
 + 3% D079 Extender
 + 0.20% D046 Antifoam
 + 10.00 lb/sx Phenoseal
 2.72 cuft/sx, 1142.4 cuft slurry at 11.7 ppg
 Tail : 235' sx 50/50 POZ : Class G Cement
 + 0.25 lb/sx D029 Cellophane Flakes
 + 2% D020 Bentonite
 + 1.50 lb/sx D024 Gilsonite Extender
 + 2% S001 Calcium Chloride
 + 0.20% D046 Antifoam
 + 6 lb/sx Phenoseal
 1.31 cuft/sx, 307.85 cuft slurry at 13.5 ppg
 Displacement: 157 bbls
 Bumped Plug at: 04:46 hrs w/ 1600 psi
 Final Circ Press: 1130 psi @ 2 bpm
 Returns during job: YES
 CMT Returns to surface: 30 bbls
 Floats Held: X Yes No
 W.O.C. for 6.00 hrs (plug bump to start NU BOP)
 W.O.C. for 13.50 hrs (plug bump to test csg)

Production Cement
 Date cmt'd: 10-Dec-04
 Cement : 465' sx 50/50 POZ : Class G Cement
 + 0.25 lb/sx D029 Cellophane Flakes
 + 3% D020 Bentonite
 + 1.00 lb/sx D024 Gilsonite Extender
 + 0.25% D167 Fluid Loss
 + 0.15% D065 Dispersant
 + 0.10% D800 Retarder
 + 0.10% D046 Antifoam
 + 3.5 lb/sx Phenoseal
 1.45 cuft/sx, 674.25 cuft slurry at 13.0 ppg
 Displacement: 126.5 bbls
 Bumped Plug: 11:24 hrs w/ 2000 psi
 Final Circ Press: 1350 psi @ 2.0 bpm
 Returns during job: None Planned
 CMT Returns to surface: None Planned
 Floats Held: X Yes No

Schematic prepared by:
 Michael P. Neuschaefer, Drilling Engineer
 12-December-2004

COMMENTS:

9-5/8" Surf:	No float equipment was run. Ran a guide shoe and an aluminum baffle plate 1 jt above the guide shoe @ 213'. Displaced top wiper plug with water. Shut in casing head and WOC before backing out landing jt.	Total:
7" Intermediate	DISPLACED W/ 149.5 BBLs. DRILL WATER. CENTRALIZERS @ 3912', 3833', 3747', 3660', 3574', 3488', 246', 81', 39'. TURBOLIZERS @ 2969', 2926', 2883', 2839', 2796'.	Total: 9 Total: 5
4-1/2" Prod.	NONE.	