

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

Sundry Notices and Reports on Wells

1. Type of Well

GAS

2. Name of Operator

BURLINGTON**RESOURCES OIL & GAS COMPANY**

3. Address & Phone No. of Operator

PO Box 4289, Farmington, NM 87499 (505) 326-9200

4. Location of Well, Footage, Sec., T, R, M

1650' FSL, 990' FWL, Sec. 2, T-29-N, R-11-W, NMPM

5. Lease Number

NMSF-080469

6. If Indian, All. or

Tribe Name

7. Unit Agreement Name

Well Name & Number

Murphy A Com #1

API Well No.

30-045-08689

Field and Pool

Basin Fruitland Coal/

Aztec Pictured Cliffs

11. County and State

San Juan Co, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission

Type of Action

<input type="checkbox"/> Notice of Intent	<input checked="" type="checkbox"/> Abandonment	<input type="checkbox"/> Change of Plans
<input checked="" type="checkbox"/> Subsequent Report	<input type="checkbox"/> Recompletion	<input type="checkbox"/> New Construction
<input type="checkbox"/> Final Abandonment	<input type="checkbox"/> Plugging Back	<input type="checkbox"/> Non-Routine Fracturing
	<input type="checkbox"/> Casing Repair	<input type="checkbox"/> Water Shut off
	<input type="checkbox"/> Altering Casing	<input type="checkbox"/> Conversion to Injection
	<input type="checkbox"/> Other -	

13. Describe Proposed or Completed Operations

10/8/04 MIRU. ND WH. NU BOP. TOO H w/tbg.

10/11/04 TIH w/bailer, CO to PBDT @ 1986'. TOO H w/bailer. TIH w/pkr, set @ 1702'. PT csg to 500 psi (bled off from 500 psi to 250 psi in 1 min). Isolate hole in casing between 197' & 163'. TOO H w/pkr. SDON.

10/12/04 TIH w/RBP & pkr, pressure test casing. SDON.

10/13/04 Isolated holes in casing between 164' & 257', 340' & 351', 620' & 631', 851' & 879'. TOO H w/RBP & pkr. ND BOP. NU WH. RD. Rig released.

11/4/04 MIRU. ND WH. NU BOP. SDON.

11/5/04 TIH w/5 1/2" cement retainer, set @ 1718'. PT tbg to 1000 psi, OK. Load & roll csg, PT to 500 psi, failed 2 BPM @ 300 psi. Plug #1 w/75 sxs Type III cmt (99 cu. ft.) @ 1986' to 1597'. TOO H. SDON.

11/8/04 TIH, tag Plug #1 @ 1536'. PT csg, failed 2.5 BPM @ 300 psi. TOO H. Perf 3 holes @ 862'. TIH w/cement retainer, set @ 812'. Load hole, sting into cement retainer, establish rate below 2 BPM @ 500 psi. Plug #2 w/84 sxs Type III cmt (111 cu. ft.) @ 862' to 560'. WOC. TIH, tag Plug #2 @ 560'. Load bradenhead 3 bbl, PT BH to 300 psi, holding. Perf @ 60'. TIH to 286'. Circ hole. Could not break circ out BH. Plug #3 w/37 sxs Type III cmt (49 cu. ft.) @ 286' to surface. ND BOP. Dig out & cut off WH. Set dry hole marker. RD. Rig released.

Well plugged and abandoned 11/8/2004.

14. I hereby certify that the foregoing is true and correct.

Signed Tammy Jones Title Regulatory Specialist Date 12/30/04

(This space for Federal or State Office use)

APPROVED BY

Title

Date

ACCEPTED FOR RECORD

CONDITION OF APPROVAL, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

JAN 05 2005

NMOC

FARMINGTON FIELD OFFICE
RY Sun