Form 3160-5 (August 1999)

UNITED STATES DEPARTMENT OF THE INTERIOR **BUREAU OF LAND MANAGEMENT**

FORM APPROVED
OMB NO. 1004-0135
Expires: November 30, 2000

5. Lease Serial No.

SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to re-enter an			NMNM19163		
abandoned well. Use form 3160-3 (APD) for such proposals.				6. If Indian, Allottee or Tribe Name	
SUBMIT IN TRIPLICATE - Other instructions on reverse side.				7. If Unit or CA/Agreement, Name and/or No.	
1. Type of Well				8. Well Name and No. WF FEDERAL 19 4	
☐ Oil Well ☐ Other 2. Name of Operator Contact: DREW CARNES					•
2. Name of Operator Contact: DREW CARNES E-Mail: dcarnes@digii.net				9. API Well No. 30-045-31063-00-X1	
a. Address 3100 LA PLATA HWY FARMINGTON, NM 87401		3b. Phone No. (include area cod Ph: 505.564.3109 18 19 20 Fx: 505.564.3109	le)	10. Field and Pool, or Exploratory HARPER HILL	
4. Location of Well (Footage, Sec., T., R., M., or Survey Description)			K. V.	11. County or Parish, a	nd State
Sec 19 T30N R14W SESE 12	APR 2	003	SAN JUAN COU	NTY, NM	
12. CHECK APPI	ROPRIATE BOX(ES) TO	INDICATÉ NATURE OF	NOTICE, RE	EPORT, OR OTHER	DATA
TYPE OF SUBMISSION			OF ACTION		· · · · · · · · · · · · · · · · · · ·
- Notice of Intent	☐ Acidize	Deepen		ion (Start/Resume)	☐ Water Shut-Off
□ Notice of Intent	☐ Alter Casing	Fracture Treat	☐ Reclama		☐ Well Integrity
Subsequent Report	☐ Casing Repair	☐ New Construction	Recomp	lete	Other
☐ Final Abandonment Notice	☐ Change Plans	Plug and Abandon	Tempora	arily Abandon	Drilling Operations
_	Convert to Injection	☐ Plug Back	□ Water D	Pisposal	
following completion of the involved testing has been completed. Final At determined that the site is ready for fr 4-5-03 Spud 8 3/4" surface ho with 65 sx (77 cf) Class B w/ 2 pit. SDFN, WOC 36 hours. 4-7-03 Install and test BOP to good. Drill 6 1/4" hole 710'. SI 4-8-03 Drill 6 1/4" hole to 1205 Cemented with 47 sx (97 cf) C sx (68 cf) Class B w 1/4 #/sk cf	pandonment Notices shall be file inal inspection.) ble. Drill to 140'. Ran 4 jts. CaCl2, 1/4#/sk celloflal 600 psi, test good. Test s DFN. The Ran 28 joints 4 1/2' Class B w/ 2% metasilicate	d only after all requirements, incl 7" 17# casing; set at 138' k ke; 15.6 ppg slurry. Circ 4 E urface casing to 600 psi for ' K-55 10.5# casing; set at . 1/4 #/sk celloflake. 12.6 p	KB. Cemented bl cement to 30 min.; test 1203.05' KB.	n, have been completed, a	and the operator has
	#2 Electronic Submission For RICHARDSOM Dommitted to AFMSS for prod	20431 verified by the BLM We N OPERATING CO, sent to the cessing by Seve Mason on C	ne Farmington 04/17/2003 (03S	_	
Name (Printed/Typed) DREW CA	KNES	Title MANA	GER	···	
Signature (Electronic S	Submission)	Date 04/16/	2003		
	THIS SPACE FO	R FEDERAL OR STATE	OFFICE US	SE .	
Approved By ACCEPT	ED		N MASON EUM ENGINE	ER	Date 04/17/200
Conditions of approval, if any, are attache tertify that the applicant holds legal or equivalent would entitle the applicant to conduction.	uitable title to those rights in the act operations thereon.	subject lease Office Farmin	_		
Fitle 18 U.S.C. Section 1001 and Title 43 States any false, fictitious or fraudulent s	U.S.C. Section 1212, make it a catatements or representations as	crime for any person knowingly as to any matter within its jurisdiction	nd willfully to ma n.	ake to any department or	agency of the United