Form 3160-5 April 2004) DEPAF	INTERIOR				FORM APPROV OM B No. 1004-0 Expires: March 31	137		
	AGEMENT				5. Lease Serial No.			
	ICES AND REP				SF 0790		· · · · · · · · · · · · · · · · · · ·	
Do not use this form abandoned well. Us					6. If Indian	, Allottee or Trib	e Name	
SUBMIT IN TRIPLIC	ATE- Other instr	uctions on I	reverse	side.	1 13	r CA/Agreement,	Name and/or No.	•
1. Type of Well Oil Well Gas V	10.11	7		<u> </u>	me and No.			
2. Name of Operator Devon Energy Produ	uction Company, L.P.	VEZ.	**,		NEBU			
3a. Address	3b. Phone No. (include area code)			47 -	30-039-27808			
PO Box 6459, Navajo Dam, NM 87419 4. Location of Well (Footage, Sec., T., R., M.					l and Pool, or Exploratory Area n Dakota / Pictured Cliffs			
1,545' FNL & 720' FEL, SE NE, Unit	11. Cour				nty or Parish, State			
, ,,					Rio Ar	riba, NM		
12. CHECK APPROP	RIATE BOX(ES) TO	INDICATE N	ATURE (OF NOTICE, R	EPORT, OF	R OTHER DA	TA	
TYPE OF SUBMISSION	TYPE OF SUBMISSION TYPE OF ACTION							
	Acidize	Deepen		Production (Sta	art/Resume)	Water Shu		
	Alter Casing Casing Repair	Fracture Trea	_	Reclamation Recomplete		Well Integ	rity sing and Cement	
Subsequent Report	Change Plans	Plug and Aba		Temporarily Al	bandon			-
Final Abandonment Notice	Convert to Injection	Plug Back		Water Disposal				-
Attach the Bond under which the work following completion of the involved of testing has been completed. Final Aban determined that the site is ready for final Drilled 12 1/4" hole to 305' on 11/CaC1 and 1/4# PSX Floseal. Circle Drilled 8 3/4" hole to 3,440' on 11	perations. If the operation idonment Notices shall be l inspection.) (16/04, set 6 jts of 9 5/8) culated 10 bbls of ceme (19/04, set 77 jts of 7",	results in a multip filed only after all ", H-40, ST&C, nt to surface. T J-55, LT&C, 23	requirement 32.3# casir est casing to	n or recompletion is, including reclaring at 295'. Cemedo 1500 psi.	in a new intervanation, have been ted w/175 s	al, a Form 31604 en completed, and ax (37 bbls) "B' 0 sx (129 bbls)	shall be filed once the operator has cement w/2% 50/50 POZ w/2%	
Gel, 0.2% Versaset, 0.1% Diacel cement to surface. Tested casing Drilled 6 1/4" hole to 7,825' on 11 w/2% Gel, 2/10% Veraset, 1/10%	to 1500 psi. /22/04, set 171 jts 4 1/2 Diacel LWL and tail v	", J-55, LT&C, w/450 sx (118 bl	11.6# casir bls) 50/50 P	ng at 7,821'. Cei OZ, 3% Gel, 1.4	mented lead v	w/250 sx (65 bb	ls) 50/50 POZ	
1/4# Flocele. No cement to surface	e, 10C @ 1,350 . Lan	uea 2 3/8" prod	luction tub	ing at 7,755°.		\$74.J		
							i	
							2	
							-	
14. Thereby certify that the foregoing is true and correct Name (Printed/Typed)						1.1	1	=
Melisa Zimmerman		1	Title Senio	r Operations Te	chnician) [1	
Signature M.S.			Date	1-24	-05	ACCEPTE	FOR RECOR	RD
TH	IS SPACE FOR	FEDERAL (OR STA	TE OFFICE	USE			
A		***************************************				JAN	3 1 2005	-
Approved by Conditions of approval, if any, are attached certify that the applicant holds legal or equi which would entitle the applicant to conduct the conduct to conduct the applicant the applicant to conduct the applicant the applicant to conduct the applicant to conduct the applicant to conduct the applicant the applic	table title to those rights i					FARMUNG I	um FIELU UFFIC	_

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.