<u>District I</u> 1625 N. French Dr., Hobbs, NM 88240 District III

1301 W. Grand Avenue, Artesia, NM 88210

District III 1000 Rio Brazos Road, Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505

## State of New Mexico Energy Minerals and Natural Resources Oil Conservation Drvision

For drilling and production facilities, submit to appropriate NMOCD District Office.
For downstream facilities, submit to Santa Fe office

1220 South St. Francis Dr. Santa Fe, NM 87505

Form C-144 June 1, 2004

Pit or Below-Grade Tank Registration or Closure		
Is pit or below-grade tank covered by a "general plan"? Yes \( \sqrt{No}\) No \( \sqrt{No}\)  Type of action: Registration of a pit or below-grade tank \( \sqrt{L}\) Closure of a pit or below-grade tank \( \sqrt{L}\)		
Decrator: Lance Oil & Gas Company, Inc. Telephone: 505- Address: #31 CR 6500, P. O. Box 70, Kirtland, NM 87417	16920 00 P	jbeckste@westerngas.com
'acility or well name: NV Navajo 36 #2	API#: <u>30-045-31191</u> U/L o	r Qtr/Qtr <u>E</u> Sec <u>36 T <b>29N</b> R <b>14W</b></u>
County: San Juan Latitude Longitude	NAD: 1927 1983 Surface (	Owner Federal 🛛 State 🔲 Private 🔲 Indian 🔲
N4	Below-grade tank	
'it 'ype: Drilling ☑ Production ☐ Disposal ☐	Volume:bbl Type of fluid:	
Workover Emergency	Construction material:	
ined 🖾 Unlined 🗌	Double-walled, with leak detection? Yes  If not, explain why not.	
iner type: Synthetic M Thickness 12 mil Clay	Pound wanted, with reak detection. Tes in not, explain why not.	
it Volume 80 bbl		
a volume	Less than 50 feet	(20 points)
Depth to ground water (vertical distance from bottom of pit to seasonal high	50 feet or more, but less than 100 feet	(10 points)
vater elevation of ground water.)	100 feet or more	( 0 points) <b>0</b>
	V	
Vellhead protection area: (Less than 200 feet from a private domestic	Yes	(20 points)
vater source, or less than 1000 feet from all other water sources.)	No	( 0 points) 0
Distance to surface water: (horizontal distance to all wetlands, playas,	Less than 200 feet	(20 points)
rigation canals, ditches, and perennial and ephemeral watercourses.)	200 feet or more, but less than 1000 feet	(10 points)
and the second s	1000 feet or more	( 0 points) <b>0</b>
	Ranking Score (Total Points)	0
If this is a pit closure: (1) attach a diagram of the facility showing the pit's	relationship to other equipment and tanks. (2) Indic	ate disposal location: (check the onsite box if
your are burying in place) onsite 🛮 offsite 🔲 If offsite, name of facility	. (3) Attach a general	description of remedial action taken including
remediation start date and end date. (4) Groundwater encountered: No 🗵 Yes 🔲 If yes, show depth below ground surface ft. and attach sample results. (5)		
Attach soil sample results and a diagram of sample locations and excavations.		
Additional Comments: Pit was closed according to NMOCD guidelines as they now exist modified by BLM liner cut-off requirements.		
gastante de diej neu entre de de et en requiremente.		
· · · · · · · · · · · · · · · · · · ·		
I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that the above-described pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines , a general permit , or an (attached) alternative OCD-approved plan .  Date: 2/10/2005		
Printed Name/Title Jo Becksted / Compliance Administrator Signature		
Your certification and NMOCD approval of this application/closure does not relieve the operator of liability should the contents of the pitor tank contaminate ground water or otherwise endanger public health or the environment. Nor does it relieve the operator of its responsibility for compliance with any other federal, state, or local laws and/or regulations.		
Approval: Printed Name/Title	CEPUTY OIL & GAS IMSPECTOR, DI	FEB 11 2005

NV Navajo 36 # 2
well pad and section

