Form 3160-5 (November 1994)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or reenter an abandoned well. Use Form 3160-3 (APD) for such proposals.

FORM A	PROVE
OMB No.	1004-013
Expires Ju	ly 31, 199

5. Lease Serial No.

6	If Indian,	Allottee	or Tribe	Name
u.	II IIIUIAII,	MIOUCE	OI TITOC	rvailie

SUBMIT IN TRIPLI	CATE – Other instru	ıctions on reverse side	7. If Unit or CA/Agreement, Name and/or N	
1.			TO RECEIVED	
Oil Well X Gas Well [8. Well Marge and No. 1 MG TO HELL			
2. Name of Operator	Jicarilla Apache B22			
Elm Ridge Resources, Inc.	9. API Well No.			
3a. Address		3b. Phone No. (include area code)	30-039-27728	
		505-632-3476	10. Field and Pool, or Exploratory Area	
4. Location of Well (Footage, Sec., T	T., R., M., or Survey Descripti	ion)	Ballard Pictured Cliffs	
			11. County or Parish, State	
Sec.20-T24N-R5W			Rio Arriba County, NM	
1950 FSL X 1980 FWL			This Arriba County, 14141	
12. CHECK APPROPRIATE BOX	(ES) TO INDICATE NAT	TURE OF NOTICE, REPORT, OR	OTHER DATA	
TYPE OF SUBMISSION	TYPE OF ACTION			
Notice of Intent	Acidize	Deepen Produc	ction (Start/Resume) Water Shut-Off	
	Alter Casing	Fracture Treat Reclar	,	
X Subsequent Report	Casing Repair	☐ New Construction ☐ Recon	pplete X Other Spud	
	Change Plans	Plug and Abandon Tempo	orarily Abandon Surface pipe	
Final Abandonment Notice	Convert to Injection	Plug Back Water	Disposal	
Testing has been completed. Final Aban determined that the site is ready for final inspect	ndonment Notices shall be filed tion.)	only after all requirements, including reclam	d subsequent reports shall be filed within 30 days a new interval, a Form 3160-4 shall be filed once ation, have been completed, and the operator has	
Testing has been completed. Final Aban determined that the site is ready for final inspect Elm Ridge Resources, Inc. ha Ran 8 5/8" 24# J-55 casing to	ndonment Notices shall be filed tion.) as spud the above refor 259'. Pumped 250 s	only after all requirements, including reclam	a new interval, a Form 3160-4 shall be filed once ation, have been completed and the operator has We drilled a 12 1/4" hole to 260'.	
Testing has been completed. Final Aban determined that the site is ready for final inspect Elm Ridge Resources, Inc. has Ran 8 5/8" 24# J-55 casing to cement to surface. Pressure	as spud the above ref co 259'. Pumped 250 s test well to 1500 PSI.	only after all requirements, including reclam	a new interval, a Form 3160-4 shall be filed once ation, have been completed and the operator has. We drilled a 12 1/4" hole to 260'.	
Testing has been completed. Final Aban determined that the site is ready for final inspect. Elm Ridge Resources, Inc. has Ran 8 5/8" 24# J-55 casing to be be coment to surface. Pressure to the surface of the surface	as spud the above ref co 259'. Pumped 250 s test well to 1500 PSI.	erenced well as of 12-17-04. ks of standard cement. We c	a new interval, a Form 3160-4 shall be filed once ation, have been completed and the operator has We drilled a 12 1/4" hole to 260'.	
Testing has been completed. Final Aban determined that the site is ready for final inspect. Elm Ridge Resources, Inc. has Ran 8 5/8" 24# J-55 casing to be be coment to surface. Pressure to the surface of the surface	as spud the above reformed to 259'. Pumped 250 stest well to 1500 PSI.	erenced well as of 12-17-04. ks of standard cement. We c	we drilled a 12 1/4" hole to 260'. JAN 2005	
Testing has been completed. Final Aban determined that the site is ready for final inspect. Elm Ridge Resources, Inc. has Ran 8 5/8" 24# J-55 casing to be be cement to surface. Pressure to the surface of the surface	as spud the above reformed to 259'. Pumped 250 stest well to 1500 PSI.	erenced well as of 12-17-04. ks of standard cement.We c	a new interval, a Form 3160-4 shall be filed once ation, have been completed and the operator has. We drilled a 12 1/4" hole to 260'.	
Testing has been completed. Final Aban determined that the site is ready for final inspect. Elm Ridge Resources, Inc. has Ran 8 5/8" 24# J-55 casing to be be coment to surface. Pressure to the surface of the surface	as spud the above reformed to 259'. Pumped 250 stest well to 1500 PSI.	erenced well as of 12-17-04. ks of standard cement. We c	we drilled a 12 1/4" hole to 260'. JAN 2005	
Testing has been completed. Final Aban determined that the site is ready for final inspect. Elm Ridge Resources, Inc. has Ran 8 5/8" 24# J-55 casing to be coment to surface. Pressure to be coment to surface. Pressure to have (Printed/Typed) Amy Manager 1. Amy	as spud the above refoo 259'. Pumped 250 stest well to 1500 PSI.	erenced well as of 12-17-04. ks of standard cement. We c	we drilled a 12 1/4" hole to 260'. JAN 2005 JAN 2005 duction Assistant	
Testing has been completed. Final Aban determined that the site is ready for final inspect. Elm Ridge Resources, Inc. has Ran 8 5/8" 24# J-55 casing to cement to surface. Pressure to cement to surface. Pressure to Name (Printed/Typied) Signature Amy Management of the site is ready for final Aban determined that the site is ready for final inspect.	as spud the above reformable to 259'. Pumped 250 stest well to 1500 PSI.	erenced well as of 12-17-04. ks of standard cement. We c	we drilled a 12 1/4" hole to 260'. JAN 2005 JAN 2005 duction Assistant anuary 7, 2005	
Testing has been completed. Final Aban determined that the site is ready for final inspect. Elm Ridge Resources, Inc. has Ran 8 5/8" 24# J-55 casing to cement to surface. Pressure to cement to surface. Pressure to Name (Printed/Typed) Amy Manager Signature Approved by	as spud the above reformed as spud the	erenced well as of 12-17-04. ks of standard cement. We c Title Property Date Division of Multi-Res warrant or Office	we drilled a 12 1/4" hole to 260'. JAN 2005 JAN 2005 duction Assistant anuary 7, 2005	

fraudulent statements or representations as to any matter within its jurisdiction.