

UNITED STATES DEPARTMENT OF THE INTERIOR

P. 0. Box 965
Farmington, New Mexico

August 10, 1954

Phillips Petroleum Company P. O. Box 939 Astec, New Maxico

Re: Santa Fe 079225

Gentlemen:

Tour "Subsequent Report of Abandonment" dated June 15, 1954, covering your wall No. 2-16 Fruit San Juan 32-4 Unit, located on subject lease in the SW2 sec. 16, T. 32 N., R. 4 W., N. M. P. M., Rio Arribe County, New Mexico, is hereby approved.

Very truly yours,

P. T. McGrath
District Engineer

PfMcGrathiae

Inspected by: P.T.McGrath August 10, 1954 NOV 28 1962 OIL COM. COM.

FARMINGTON OF THE COPY

Form 9-881 a (Feb. 1951)

(SUBMIT IN TRIPLICATE)

UNITED STATES DEPARTMENT OF THE INTERIOR **GEOLOGICAL SURVEY**

SUNDRY NOTICES AND REPORTS ON W

NOTICE OF INTENTION TO DRILL. SUBSEQUENT REPORT OF WATER SHUT-OFF CALLS NOTICE OF INTENTION TO CHANGE PLANS SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING NOTICE OF INTENTION TO TEST WATER SHUT-OFF SUBSEQUENT REPORT OF ALTERING CASING NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR NOTICE OF INTENTION TO SHOOT OR ACIDIZE SUBSEQUENT REPORT OF ABANDONMENT NOTICE OF INTENTION TO PULL OR ALTER CASING SUPPLEMENTARY WELL HISTORY NOTICE OF INTENTION TO ABANDON WELL

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

June 15, 1954

. 19....

Undt 32-4 Fruit 2-16. Well No.

ft. from

ft.

В.

S line and so ft. from w line of sec.

S4/4 Sec. 16 (Sec. and Sec. No.)

328

(Range)

H MK (Meridian)

Wildest

alo arriba

(County or Substivision)

New Maxico

The elevation of the derrick floor above sea level is 6778

DETAILS OF WORK

(State names of and expected depths to objective sands; show sites, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

5-30-54 TO 6573. J.H. Jak & Co. contractors. Spotted 25 sx. cat. by hall bureon from 6578 to 6444'. Hudded hole 6444' to 6058', placed cement plug by Hallimarton 5053 to 5933'. Shot 7" casing off at 1300' by Dia-Log. Recovered 1300' 7" 30 casing. Walliberton pumped 50 sx. tement 5933' to 1300'. Mudded hole 1300' to 10'. Placed cement plug from 10' to surface. Cement 7' piece of 4" pipe in surface leaving 4' of pipe above surface for marker. Well plugged and abandoned June 2, 1964 at 12:00 Hoom.

Tolisation passing left in hole.

10-3/4"

152' from surface to 171' RAB

4741' from 1317' has to 6058' MB.

I understand that this plan of work must receive approval in wir Phillips Petroleus Comerce Company

Address

F. . . HOX 939

sated, des lexico



literistrict baseristendent from tion epartment