



IN REPLY REFER TO:

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY
Farmington, New Mexico

August 10, 1954

Phillips Petroleum Company
P. O. Box 939
Aztec, New Mexico

Re: Santa Fe 079227

Gentlemen:

Your "Subsequent Report of Abandonment" dated June 15, 1954, covering your well No. 1-29 Mesa San Juan 32-4 Unit, located on subject lease in the SW $\frac{1}{4}$ sec. 29, T. 32 N., R. 4 W., N. M. P. M., Rio Arriba County, New Mexico, is hereby approved.

Very truly yours,

P. T. McGrath
District Engineer

PTMcGrath:ac

Inspected by:
P. T. McGrath
August 10, 1954



Form 9-331a
(Feb. 1951)

4 - USGS
1 - Region
1 - File
1 - Suspense

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Budget Bureau 42-R338.2
Approval expires 12-31-55.

Land Office **Santa Fe**
Lease No. **679227**
Unit **San Juan Unit 32-4**

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	SUBSEQUENT REPORT OF WATER SHUT-OFF.....
NOTICE OF INTENTION TO CHANGE PLANS.....	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....	SUBSEQUENT REPORT OF ALTERING CASING.....
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.....
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....	SUBSEQUENT REPORT OF ABANDONMENT.....
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	SUPPLEMENTARY WELL HISTORY.....
NOTICE OF INTENTION TO ABANDON WELL.....	

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

June 15, 1954

19

Unit **32-4**
Well No. **1-29** is located **1590** ft. from **XXX** line and **1490** ft. from **XXX** line of sec.

SW 1/4 Sec. 29

(1/4 Sec. and Sec. No.)

12N

(Twp.)

4W

(Range)

104N

(Meridian)

Wildcat

(Field)

Rio Arriba

(County or Subdivision)

New Mexico

(State or Territory)

The elevation of the derrick floor above sea level is **7266** ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

5-28-54 TD 6920. J.M. Cox & Co. Contractors. Spotted 40 sz. cement 6920 to 6606 by Halliburton. Mudded hole 6606 to 1683'. Shot 7" casing off at 2900' by Dia-Log, unable to circulate, shot 7" casing off at 1683' by Dia-Log, spotted cement plug 1683 to 1494. Recovered 51 fts. & 1 piece casing, 1685'. Mudded hole to 10', placed cement plug 10' to surface. Placed 4" marker 4' above surface. Well Plugged and abandoned 10:00 A.M. May 31, 1954.

Following casing left in hole:

10-3/4" - 162' from surface to 176' RKB.

7" - 4679' from 1705' RKB to 6384' RKB.

5-1/2" liner 365' from 6336' RKB to 6701' RKB.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company **Phillips Petroleum Company**

Address **P.O. Box 939**

Astec, New Mexico

By

Carl H. ...

Title **District Superintendent**
Production Department