UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

Sundry Notices and Reports on Wells				AMENDED		
				AMENDED		
 Type of Well GAS Name of Operator BURLINGTON 		RECEIVED 1234 STORE OIL CONS. DIV. DIST. 3 6 7 120 EL ZI MOLOONS.	5. 6. 7.	Lease Num SF-078835 If Indian, A Tribe Name Unit Agreed SAN JUAN	ll. or e ment Name	
RESOURCES OIL	& GAS COMPANY LP	STON EN STAN	- 8.	Well Name		
3. Address & Phone No. of Operator				SAN JUAN	28-7 UNIT 254N	
PO Box 4289, Farmington, NM 87499 (505) 326-9700			9.	API Well N	0.	
4. Location of Well, Footage, So	ec TRM	•	-	30-039-3088	84	
Surface: Unit C (NE/NW), 90	52' FNL & 1793' FWL, Secti		ΔŒ	BLANCO N	MV / BASIN DK	
Bottomhole: Unit E (SW/NW	/), 1665' FNL & 850' FWL, 8	section 6, 12/N, R/W, MMP	vi 11.	County and Rio Arriba		
12. CHECK APPROPRIATE BO		E OF NOTICE, REPORT, O	THER	DATA		
Type of Submission Notice of Intent X Subsequent Report Final Abandonment	pe of Action Abandonment Recompletion Plugging Casing Repair Altering Casing	Change of Plans New Construction Non-Routine Fracturing Water Shut off Conversion to Injection	X	Other - Casin	ng Report	
12/31/10 MIRU AWS 673. NU BOPE. PT PU & TIH w/ 8 3/4" bit. Tag & DO cmt to ST @ 2457'. 1st Stage - Pre-flushed w/ 10b 0.4% FL-52, 8% bentonite, & 0.4% SMS. I 0.4% SMS. Tail w/ 91sx(126cf-22bbls) Typ Bumped plug. Plug down @ 02:50hrs 01/0 scavenger w/ 19sx(57cf-10bbls) Premium I 109bbls) Premium Lite w/ 3% CaCl, 0.25 p plug & close ST. Plug down @ 08:50hrs 01/08/11 TIH w/ 6 1/4" bit. Drill out ST @ 01/10/11. Circ. hole & RIH w/ 173jts, (13jt scavenger 9sx(28cf-5bbls) Premium lite H 0.25 pps celloflake 0.3% CD-32, 6.25pps L plug & displaced w/ 116bbls FW. Bumped PT will be conducted by Completion Rig R	csg to 600#/30min @ 12:00hrs on 01/0238'. Drilled ahead to 3868' - Inter TD bls GW, 2bbls FW. Pumped scavenge ead w/ 110sx(234cf-42bbls) Premium to III cmt w/ 1% CaCl, .025 pps celloff/11. Open ST & Circ. 20bbls cmt to stite w/ 3% CaCl, 0.25 pps celloflake, ips celloflake, 5pps LCM-1, 0.4% FL-501/08/11. Circ. 27bbls cmt to surface 2457'. PT 7" esg to 1500#/30min @20 S FM, 0.25pps celloflake, 0.3% CD-3. CM-1 & 1% FL-52 Shut dwn due to plug. Plug down @ 23 44hrs on 01/11. desults & TOC will appear on next rep	reached 01/06/11. Circ hole & RIH var w/ 19sx(57cf-10bbls) Premium Lite Lite w/ 3% CaCl, 0.25 pps celloflake, lake, & 0.2% FL-52. Dropped plug & surface. WOC. 2nd Stage - Pre-flush v5pps LCM-1, 0.4% FL-52, 8% bentonics, & 0.4% SMS. Dropp. RD cmt. WOC. 0:00rs on 01/0811. Test -OK Drilled w#, L-80 csg set @ 7472!. RU to cmt. Pt 2, 6.25pps LCM-1, & 1%FL-52. Tail vpump truck not being able to maintain/11. RD cmt. WOC. ND BOPE NU W	w/ 3% (5pps L0 displace v/ 10 bbl ite, & 0.4 bed plug v/ 6 1/4" re-flushe w/120sxi density	CaCl, 0.25 pps cello CM-1, 0.4% FL-52 d w/ 60bbls FW & s FW, 10bbls GW, 1% SMS. Lead w/ 19 & Displaced w/ 97 bit reached TD @ d w/ 10bbls GW & (238cf-42bbls) Pref Original job called	oflake, 5pps LCM-1, , 8% bentonite, & 91bbls MW. 10bbls FW. Pumped 289sx(616cf- bbls of FW. Bumped 7475' on 22bbls FW. Pumped mium lite HS FM,	
Signed A	Marie E. Ja	aramillo Title Staff Reg	gulator	y Technician	Date <u>02/12/11</u>	
(This space for Federal or State Of APPROVED BY	fice use) Title	AO	CEPT	ED MOR REC	ORD	

MAY 2 3 2011

FARMINGTON FIELD OFFICE

NMOCD A