



Schematic - Current

SAN JUAN 29-6 UNIT #61M

API # 3003930985

District SOUTH	Field Name MV/DK COM	API / UWI 3003930985	County RIO ARRIBA	State/Province NEW MEXICO	
Original Spud Date 3/30/2011	Surface Legal Location 019-029N-006W-K	East/West Distance (ft) 1,790.00	East/West Reference FWL	North/South Distance (ft) 1,975.00	North/South Reference FSL

Well Config: DEVIATED - Original Hole: 6/24/2011 7:43:04 AM

ftKB (MD)

Schematic - Actual

15
16
18
24
68
73
200
201
232
233
238
985
1,028
2,320
2,492
2,845
2,848
3,119
3,321
3,463
3,468
4,093
4,103
4,117
4,324
4,326
4,412
4,413
4,456
4,456
4,474
4,530
4,942
5,096
5,194
5,333
5,388
5,508
5,688
5,996
6,771
7,415
7,425
7,487
7,545
7,597
7,598
7,656
7,657
7,684
7,688
7,689
7,690
7,697
7,698
7,730
7,770
7,806
7,806
7,807
7,808
7,810

- 3-1, Casing Joint, 4 1/2, 4,000, 15
2-1, Casing Joints, 7, 6,366, 15
2-2, PUP JOINT, 7, 6,366, 15, 1.2
1-1, Casing Hanger, 9 5/8, 9,001, 15, 3 1
3-2, Mandrel Pup Joint, 4 1/2, 4,000, 15, 9.3
3-3, Casing Joint, 4 1/2, 4,000, 24, 43 3
3-4, Casing Pup Joint, 4 1/2, 4,000, 68, 5 9
1-2, Casing Joints, 9 5/8, 9,001, 18, 182.0
1-3, Float Collar, 9 5/8, 9,001, 200, 1.5
1-4, Casing Joints, 9 5/8, 9,001, 202, 30.5
1-5, Sawtooth Collar, 9 5/8, 9,001, 232, 0.9
3-5, Casing Joint, 4 1/2, 4,000, 73, 911-6
3-6, Cross Over, 4 1/2, 4,000, 985, 43.1
2-3, Casing Joints, 7, 6,366, 16, 2,829 3
2-4, STAGE TOOL, 7, 6,366, 2,846, 2 5
1-1, Tubing, 2 3/8, 1,995, 15, 7,640.5
3-7, Casing Joints, 4 1/2, 4,000, 1,028, 3,064.5
3-8, Marker Joint, 4 1/2, 4,000, 4,093, 10-1
2-5, Casing Joints, 7, 6,366, 2,848, 1,564.1
2-6, FLOAT COLLAR, 7, 6,366, 4,412, 0.6
PERF - LEWIS, 4,326-4,530, 6/10/2011
2-7, Casing Joints, 7, 6,366, 4,413, 43.1
2-8, FLOAT SHOE, 7, 6,366, 4,456, 0 7
PERF - CH/MEN, 4,942-5,333, 5/27/2011
PERF - POINT LOOKOUT / MENEFFEE LOWER, 5,388-5,688, 5/26/2011
3-9, Casing Joints, 4 1/2, 4,000, 4,103, 3,312 4
3-10, Marker Joint, 4 1/2, 4,000, 7,415, 10 0
PERF - DAKOTA, 7,598-7,684, 5/25/2011
1-2, Tubing Pup Joint, 2 3/8, 1,995, 7,656, 2 0
1-3, Tubing, 2 3/8, 1,995, 7,658, 30.5
1-4, Profile Nipple, 2 3/8, 1,780, 7,688, 0.9
1-5, Mule Shoe Guide, 2 3/8, 1,780, 7,689, 0.8
PERF - DAKOTA, 7,698-7,770, 5/25/2011
3-11, Casing Joints, 4 1/2, 4,000, 7,425, 381.2
3-12, Float Collar, 4 1/2, 4,000, 7,806, 0.8
3-13, Float Shoe, 4 1/2, 4,000, 7,807, 0.8

