Form 3160-5 (August 2007)

## **UNITED STATES** DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

## SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to re-enter an

	FORM APPROVED
	OMB NO 1004-0137
	司 月平平天 Expires July 31, 2010
REUL	5 Lease Serial No.
	NMSF-079232

FALMING ION PIET

٧٧

Iffi Indian, Allottee or Tribe Name abandoned well. Use Form 3160-3 (APD) for such proposals. Bureau of Land Manageried. Agreement, Name and/or No. r armingion SUBMIT IN TRIPLICATE - Other instructions on page 2 Type of Well 8 Well Name and No Oil Well X Gas Well Other BOLACK C #13B 2. Name of Operator XIO ENERGY INC. 9. API Well No 3a Address 3b. Phone No. (include area code) 30-045-31154 AZTEC, NM 87410 505-333-3630 382 CR 3100 10. Field and Pool, or Exploratory Area 4. Location of Well (Footage, Sec., T., R., M., or Survey Description) BLANCO MESAVERDE/ OTERO CHACRA/S BLANCO PC 2,170' FNL & 1,670' FWL SENW SEC 29 (F) -T27N-R08W N.M.P.M. 11 County or Parish, State SAN JUAN CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA 12. TYPE OF SUBMISSION TYPE OF ACTION Water Shut-Off Notice of Intent Acidize Deepen Production (Start/Resume) Alter Casing Fracture Treat Reclamation Well Integrity Subsequent Report Casing Repair New Construction Recomplete Other DHC & PWOP Change Plans Plug and Abandon Temporarily Abandon COMPLETION SUMMARY Final Abandonment Notice Convert to Injection Plug Back Water Disposal Describe Proposed or Completed Operation (clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof If the proposal is to deepen directionally or recomplete horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 shall be filed once testing has been completed Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the final site is ready for final inspection.) XIIO Energy Inc. has recompleted the S. Blanco Pictured Cliffs formation & downhole commingled the MV/CH/PC. (DHC-4388). Well has been put on a pumping unit. Please see the attached summary report. 14. I hereby certify that the foregoing is true and correct Name (Printed/Typed) BARBARA Title REGULATORY COMPLIANCE TECHNICIAN Signature Date 07/18/2011 THIS SPACE FOR FEDERAL OR STATE OFFICE USE Title Approved by

Title 18 U.S.C. Section 1001, and Title 43 U.S.C. Section 1212, makes it a crime for any person by willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction. fictitious or fraudulent statements or representations as to any matter within its jurisdiction

Conditions of approval, if any, are attached Approval of this notice does not warrant or certify that

the applicant holds legal or equitable title to those rights in the subject lease which would

entitle the applicant to conduct operations thereon

Office

## Bolack C 13B

5/31/2011: MIRU.

6/1/2011: TOH tbg. TIH 4-1/2" CIBP set @ 3,000'. PT RBP & csg to 3,000 psig. Tstd OK.

6/2/2011: MIRU WLU. Ran CCL log fr/3,000' - surf. TOC @ 750'. RDMO WLU. RDMO.

**6/8/2011:** MIRU WLU. Ran GR/CCL log fr/3,000' - surf. Correlated depth w/Schlumberger Platform Express log dated 8/24/02. Perf PC w/3-1/8" select-fire csg gun @ 2,808', 2,807', 2,805', 2,801', 2,794', 2,793', 2,789', 2,787', 2,785', 2,784', 2,782', 2,780', 2,779', 2,778', 2,777', 2,776', 2,775', 2,773', 2,772', 2,771', 2,770', 2,768', 2,767', 2,766', 2,765', 2,764', 2,763' & 2,762' w/1 JSPF (10 gm chrgs, 0.34" EHD, 21.42" pene., 28 holes). POH w/csg gun. SWI. RDMO WLU.

**6/11/2011:** MIRU frac equip. Spearhead 1,000 gals 15% NEFE HCl ac. Frac PC perfs fr/2,762' - 2,808' dwn 4-1/2" csg w/58,011 gals foamed linear gelled 2% KCl wtr carrying 115,880# 16/30 PSA sd. RDMO frac equip. RU 3-D flwback mnflld & FL. SWI 4 hrs. SICP 1,300 psig. SICP 1,175 psig. OWU on 24/64" ck @ 3:00 p.m. F. 0 BO, 15 BLW, N2, frac fld, no sd, FCP 1,175 - 500 psig, 24/64" ck, 1 hr. F. 0 BO, 123 BLW, N2, frac fld, no sd, FCP 500 - 25 psig, 32/64" ck, 8 hrs.

6/12/2011: Cont flwback PC frac.

7/12/2011: MIRU. TIH bit & tbg. Tgd @ 2,870' (130' fill). CO fill fr/2,870' - 3,000' (CIBP).

**7/13/2011:** SICP 340 psig. Tgd @ 2,970' (30' fill). CO fill fr/2,970' - 3,000' (CIBP). DO CIBP. Tgd @ 5,452' (PBTD). Tgd @ 5,447' (5' fill).

**7/14/2011:** CO fill fr/5,447' - 5,452' (PBTD). Ld tbg w/donut & seal assy. SN @ 5,381'. TAC @ 5,399'. EOT @ 5,402'. Perfs fr/2,762' - 5,349'. NU WH.

**7/15/2011:** PU EPS & seat pmp. TIH rods. PT tbg to 500 psig. Tstd OK. LS pmp w/rig to 500 psig. GPA. HWO. RDMO.