

**UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT**

**RECEIVED****JUN 29 2011**

Sundry Notices and Reports on Wells

Farmington Field Office  
Bureau of Land Management

1. Type of Well  
GAS

2. Name of Operator  
**BURLINGTON**  
RESOURCES OIL & GAS COMPANY LP

3. Address & Phone No. of Operator  
PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M  
Unit I (NESE), 1650' FSL & 800' FEL, Section 7, T27N, R10W, NMPM

5. Lease Number  
SF-077875  
6. If Indian, All. or  
Tribe Name  
7. Unit Agreement Name

8. Well Name & Number  
Rowley 3

9. API Well No.  
30-045-06647

10. Field and Pool  
Basin FC / Fulcher Kutz PC

11. County and State  
San Juan, NM

**12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA**

Type of Submission	Type of Action		
<input checked="" type="checkbox"/> Notice of Intent	<input checked="" type="checkbox"/> Abandonment	<input checked="" type="checkbox"/> Change of Plans	Other - _____
<input type="checkbox"/> Subsequent Report	<input type="checkbox"/> Recompletion	<input type="checkbox"/> New Construction	
<input type="checkbox"/> Final Abandonment	<input type="checkbox"/> Plugging	<input type="checkbox"/> Non-Routine Fracturing	
	<input type="checkbox"/> Casing Repair	<input type="checkbox"/> Water Shut off	
	<input type="checkbox"/> Altering Casing	<input type="checkbox"/> Conversion to Injection	

**13. Describe Proposed or Completed Operations**

A CBL was run on this well and the cement coverage wasn't as originally thought. Called and visited with the BLM (Steve Mason) and OCD (Brandon Powell) and adjusted the P&A procedure to include the following changes which were approved by both BLM and OCD.

Pump plug 1: (Fruitland Top: 1,483'- 950')

Pump 16 sxs Class B cement & reverse out to 900'. PU hole to 500' & WOC. RIH & tag cement top.

Pump plug 2: (Kirtland, Ojo Alamo Tops: 850'-630')

Set CIBP @ 850'. Pump 10 sxs of Class B cement & reverse out to 500'. PU hole & WOC. Tag cement top.

Pump plug 3: (Surface plug: 176'-surface)

Perf @ 176'. Open annular valves & establish circulation between 2-7/8" X 5-1/2" annulus. Pump 17 sxs of Class B cement, closing annular valves when cement is circulated to surface. Pump 3-4 sxs to fill 2-7/8" csg to surface. Double valve, shut well in, & WOC. Top out as needed.

**14. I hereby certify that the foregoing is true and correct.**

Signed Patsy Clugston Patsy Clugston Title: Sr Regulatory Specialist Date 6/29/11

(This space for Federal or State Office use)

APPROVED BY Original Signed: Stephen MasonTitle \_\_\_\_\_ Date **JUN 30 2011**

CONDITION OF APPROVAL, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

**MMOCD**

A