Jr., Hobbs, NM 88240

. St., Artesia, NM 88210 All Rio Brazos Road, Aztec, NM 87410 strict IV 1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico **Energy Minerals and Natural Resources** Department Oil Conservation Division 1220 South St. Francis Dr.

Form C-144 Revised April 3, 2017

For temporary pits, below-grade tanks, and multi-well fluid management pits, submit to the appropriate NMOCD District Office.

For permanent pits submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

Pit, Below-Grade Tank, or

Santa Fe, NM 87505

Proposed Alternative Method Permit or Closure Plan Application
Type of action: Below grade tank registration Permit of a pit or proposed alternative method Closure of a pit, below-grade tank, or proposed alternative method Modification to an existing permit/or registration Closure plan only submitted for an existing permitted or non-permitted pit, below-grade tank, or proposed alternative method
Instructions: Please submit one application (Form C-144) per individual pit, below-grade tank or alternative request
Please be advised that approval of this request does not relieve the operator of liability should operations result in pollution of surface water, ground water or the environment. Nor does approval relieve the operator of its responsibility to comply with any other applicable governmental authority's rules, regulations or ordinances.
Operator: Huntington Energy, L.LC. OGRID #: 208706 COUNTY OF THE PROPERTY OF T
Address:908 N.W. 71st Street, Oklahoma City, OK 73116
Facility or well name:Ute Mountain Ute #80
API Number:30-045-34513 OCD Permit Number:
U/L or Qtr/Qtr _B Section _20 Township _ 32N Range _14W County: _ San Juan
Center of Proposed Design: Latitude 36.977113°N Longitude -108.328743°W NAD83
Surface Owner: Federal State Private Tribal Trust or Indian Allotment
DENIED - W
DENIED
Temporary: Drilling Workover BY: Cory Smith
DATE: DIVICE LINE PRINCE LINE
Lined Unlined Liner type: Thicknessmil LLDPE HDPE PVC Other
☐ String-Reinforced
Liner Seams: Welded Factory Other Volume: bbl Dimensions: L x W x D
3. Subsection I of 19.15.17.11 NMAC
Volume: _120
Tank Construction material:Metal
Secondary containment with leak detection Visible sidewalls, liner, 6-inch lift and automatic overflow shut-off
☐ Visible sidewalls and liner ☐ Visible sidewalls only ☐ Other
Liner type: Thickness mil HDPE PVC Other
Alternative Method:
Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.
5.
Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pits, temporary pits, and below-grade tanks)
Chain link, six feet in height, two strands of barbed wire at top (Required if located within 1000 feet of a permanent residence, school, hospital, institution or church)
Four foot height, four strands of barbed wire evenly spaced between one and four feet
Alternate Please specify

Netting: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks)	
Screen Netting Other	
☐ Monthly inspections (If netting or screening is not physically feasible)	
7.	
Signs: Subsection C of 19.15.17.11 NMAC	
12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers	
☐ Signed in compliance with 19.15.16.8 NMAC	
8.	
Variances and Exceptions:	
Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance. Please check a box if one or more of the following is requested, if not leave blank:	
Variance(s): Requests must be submitted to the appropriate division district for consideration of approval.	
Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.	
9. Siting Criteria (regarding permitting): 19.15.17.10 NMAC	
Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of acceptance are provided below. Siting criteria does not apply to drying pads or above-grade tanks.	ptable source
material are provided below. Sitting criteria does not apply to drying pads of above-grade tanks.	
General siting	
Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tank.	Yes No
- NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	NA NA
Ground water is less than 50 feet below the bottom of a Temporary pit, permanent pit, or Multi-Well Fluid Management pit. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance	☐ Yes ☐ No
adopted pursuant to NMSA 1978, Section 3-27-3, as amended. (Does not apply to below grade tanks)	
 Written confirmation or verification from the municipality; Written approval obtained from the municipality 	
Within the area overlying a subsurface mine. (Does not apply to below grade tanks) - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No
Within an unstable area. (Does not apply to below grade tanks)	☐ Yes ☐ No
 Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 	
Within a 100-year floodplain. (Does not apply to below grade tanks)	☐ Yes ☐ No
- FEMA map	
Below Grade Tanks	
Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured	☐ Yes ☐ No
from the ordinary high-water mark).	l les No
- Topographic map; Visual inspection (certification) of the proposed site	
 Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption;. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site 	Yes No
Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)	
Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole,	—
or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.) - Topographic map; Visual inspection (certification) of the proposed site	Yes No
Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial	☐ Yes ☐ No
 application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 	
Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No

Within 100 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No			
Temporary Pit Non-low chloride drilling fluid				
Within 300 feet of a continuously flowing watercourse, or any other significant watercourse, or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No			
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No			
Within 500 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 1000 feet of any other fresh water well or spring, in the existence at the time of the initial application; NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site				
Within 300 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No			
Permanent Pit or Multi-Well Fluid Management Pit				
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark).				
- Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No			
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	Yes No			
Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of initial application.	E			
- NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No			
Within 500 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No			
10. Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 N				
Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the do attached.	cuments are			
Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC				
and 19.15.17.13 NMAC	13.17.9 NIVIAC			
Previously Approved Design (attach copy of design) API Number: or Permit Number:	k3			
11. Multi-Well Fluid Management Pit Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the doc	cuments are			
attached. Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC A List of wells with approved application for permit to drill associated with the pit. Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19 and 19.15.17.13 NMAC Hydrogeologic Data - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC				
Previously Approved Design (attach copy of design) API Number: or Permit Number:				

Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC	
Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the	documents are
Hydrogeologic Report - based upon the requirements of Paragraph (1) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Climatological Factors Assessment Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC Dike Protection and Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC Quality Control/Quality Assurance Construction and Installation Plan Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Nuisance or Hazardous Odors, including H ₂ S, Prevention Plan Emergency Response Plan Oil Field Waste Stream Characterization Monitoring and Inspection Plan Erosion Control Plan Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC Proposed Closure: 19.15.17.13 NMAC	
Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan.	1.1334
Type: Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank Multi-well F Alternative Proposed Closure Method: Waste Excavation and Removal Waste Removal (Closed-loop systems only) On-site Closure Method (Only for temporary pits and closed-loop systems) In-place Burial On-site Trench Burial Alternative Closure Method	luid Management Pit
14. Waste Excavation and Removal Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be	attached to the
closure plan. Please indicate, by a check mark in the box, that the documents are attached. Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings) Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	
15. Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable sour provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. I 19.15.17.10 NMAC for guidance.	
Ground water is less than 25 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Ground water is between 25-50 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Ground water is more than 100 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	Yes No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Written confirmation or verification from the municipality; Written approval obtained from the municipality	Yes No
Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	_ =
Within incorporated municipal houndaries or within a defined municipal fresh water well field covered under a municipal ordinance	Yes No

adopted pursuant to NMSA 1978, Section 3-27-3, as amended. - Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No				
Within the area overlying a subsurface mine Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division					
Within an unstable area. - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map	ПуссПо				
Within a 100-year floodplain FEMA map	☐ Yes ☐ No ☐ Yes ☐ No				
On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan. Please indicate, by a check mark in the box, that the documents are attached. Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection E of 19.15.17.13 NMAC Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of Subsection K of 19.15.17.11 NMAC Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon the appropriate requirements of 19.15.17.13 NMAC Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of 19.15.17.13 NMAC Waste Material Sampling Plan - based upon the appropriate requirements of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards cannot be achieved) Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC					
Operator Application Certification: I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and believe to the best of my knowledge					
18. OCD Approval: Permit Application (including closure plan) Closure Plan (only) Conditions (see attachment)					
OCD Representative SignaturesApproval Date:					
Title: OCD Permit Number:					
19. Closure Report (required within 60 days of closure completion): 19.15.17.13 NMAC Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting the closure report. The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not complete this section of the form until an approved closure plan has been obtained and the closure activities have been completed. Closure Completion Date:					
20. Closure Method: Waste Excavation and Removal On-Site Closure Method Alternative Closure Method Waste Removal (Closed-lo If different from approved plan, please explain.	op systems only)				
Closure Report Attachment Checklist: Instructions: Each of the following items must be attached to the closure report. Please into mark in the box, that the documents are attached. Proof of Closure Notice (surface owner and division) Proof of Deed Notice (required for on-site closure for private land only) Plot Plan (for on-site closures and temporary pits) Confirmation Sampling Analytical Results (if applicable) Waste Material Sampling Analytical Results (required for on-site closure) Disposal Facility Name and Permit Number Soil Backfilling and Cover Installation Re-vegetation Application Rates and Seeding Technique Site Reclamation (Photo Documentation)	dicate, by a check				

Operator Closure Certification:		
	ted with this closure report is true, accurate and complete to the best of my knowledge and table closure requirements and conditions specified in the approved closure plan.	
Name (Print):	Title:	_
Signature:	Date:	_
e-mail address:	Telephone:	_

Page 6 of 6

Huntington Energy, L.L.C. Below Grade Tank Closure Plan San Juan Basin

The closure requirements for below-grade tanks include the general provisions of Paragraphs 19.15.17.13 NMAC and the specific requirements of Paragraph E of 9.15.17.13 NMAC.

Closure Timelines:

1. HE shall close an existing BGT within the time periods provided in 19.15.17.13 NMAC, or by and earlier date that the division requires because of imminent danger to fresh water, public health or the environment. HE will close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC or is not included in Paragraph 5 of Subsection I of 19.15.17.11 NMAC.

HE shall close the permitted BGT within 180 days of cessation of the BGT's operation as required by the provisions of the Bureau of Land Management as set forth on conditions of approval from plugging sundry notice.

2. HE shall submit closure notice prior to the implementation of any closure operations to the Division District Office and the surface owners, which are Bureau of Land Management and the Bureau of Indian Affairs-BIA. HE shall notify surface owners on Federal lands. Closure notice will be sent via email to the Bureau of Land Management and NMOCD: certified mail is not required for Federal lands. HE will notify the Division District office at least 72 hours, but not more than one week prior to any closure operation. All operator information shall include the operator's name and the location to be closed by unit letter, section, township and range. The notice shall include the well's name, number and API number.

Closure Method & Procedures:

- 1. Remove liquids and sludge from a BGT prior to implementing a closure method. These will be disposed in facility IEI, Permit # 01001010B, TNT Environmental, permit # NM 01-0008 or Basin Disposal, Inc., permit # NM-01-005.
- 2. HE will obtain approval from the NMOCD to dispose, recycle, reuse, or reclaim the BGT and provide documentation of the final disposition of the BGT in the Closure Report.
- 3. All on-site related equipment with a BGT shall be removed unless equipments is required for some other purpose.
- 4. If the liner material requires disposal, HE will clean the liner (as per subparagraph (m) of paragraph (1) of Subsection C of 19.15.35.8 NMAC), and can be accepted at a solid waste facility at San Juan County Regional Landfill.
- 5. HE shall test the soils beneath the below-grade tank to determine whether any contamination has occurred. At a minimum, HE will conduct a five point composite sample under the liner or the below-grade tank and that sample shall be analyzed for the contents listed in Table I of 19.15.17.13 NMAC. If any concentration is higher than listed in Table I of 19.15.17.13 NMAC, HE will do any additional work at the site with approval from the NMOCD before proceeding with closure. If all contaminant concentrations are less than or equal to the listed

contents in Table I of 19.15.17.13 NMAC, then HE will backfill the pit, pad, or excavation with non-waste containing, uncontaminated, earthen material.

3. Closure Report: Within 60 days of closure, HE shall submit a closure report on form C-144/Checklist Box 24, with the following attachments: Proof of Closure Notice (surface owner and division); Plot Plan, Confirmation Sampling Analytical Results (if applicable); Waste Material Sampling Analytical Results, Disposal Facility Name and Permit Number; Soil Backfilling and Cover Installation; Re-vegetation Application Rates and Seeding Technique; Site Reclamation (Photo Documentation); and Latitude and Longitude of site. HE will certify that all information in the report and attachments is correct and has complied with all applicable closure requirements and conditions specified in the approved closure plan.

Once the Below grade tank is closed, HE will reclaim the location and all areas associated, including associated access roads to a safe and stable condition that blends with the surrounding undisturbed area. The area will be restored to the condition that existed prior to operations by placement of the soil cover as provided in Paragraph (2) of Subsection H of 19.15.17.13 NMAC, re-contour the location and associated areas to a contour to blend with the surrounding topography and re-vegetate according to Paragraph (5) in Subsection H of 19.15.17.13.

The soil cover for closures after the contouring, where the below grade tank are removed, the soil beneath will need a concentration less than 600 mg/kg as analyzed by EPA Method 300.0, shall consist of the background thickness of topsoil or one foot of suitable material, whichever is greater.

HE will construct the soil cover to the site's existing grade and prevent ponding of water and erosion of the cover material.

All area disturbed by the below grade tank closure will be reclaimed as early as practicable to their original condition and be maintained to control dust and minimize erosion. Topsoils and subsoils will be replaced to their original positions as able and contoured to achieve erosion control. The area will then be reseeded in the first favorable growing season following closure of the below grade tank.

The reclamation of the area no longer in use shall be complete when the ground surface disturbing activities at the site have been completed and vegetative growth has occurred to a ration of plus or minus fifty percent (50%) of pre-disturbance level and a total percent plant cover of at least seventy percent (70%) of pre-disturbance levels have been met.

Cathy Smith

From:

Cathy Smith

Sent:

Thursday, July 18, 2019 11:10 AM

To:

'jjardine@blm.gov'

Subject:

RE: UMU 73 & 80 BGT & Reclamation

Importance:

High

Jenn,

Here are the legal locations for the Ute Mountain Ute #73 & 80. I did not include the legals in my previous email. We will contact the BIA and UMU 48 hours before surface reclamation.

Ute Mountain Ute #73
API#: 30-045-33302
Lot E, Sec 23-32N-14W
San Juan Co., NM
36.97674°N and -108.28427°W

Ute Mountain Ute #80
API#: 30-045-34513
Lot B, Sec 20-32N-14W
San Juan Co., NM
36.977113°N -108.328743°W

Thank you.

Cathy Smith Huntington Energy, L.L.C. 908 N.W. 71st Street Oklahoma City, OK 73116 (405) 840-9876 ext. 129 (405) 840-2011 - Fax

From: Cathy Smith

Sent: Wednesday, July 17, 2019 4:25 PM

To: jjardine@blm.gov

Subject: UMU 73 & 80 BGT & Reclamation

Jenn,

Our field supervisor, Ron Lackey, is working on the locations of the above wells which were plugged. He is out there today and wanted to get in contact with you. I am filing a C-144 BGT "Notice of Closure Plan Only" to the NMOCD. You are being notified too, but we need to know if you would like to be present and if you would like the soil to be checked. Please call me at your earliest convenience.

Cathy Smith Huntington Energy, L.L.C. 908 N.W. 71st Street Oklahoma City, OK 73116 (405) 840-9876 ext. 129 (405) 840-2011 - Fax