Received by OCD: 8/16/2020 5:59:36 PM District I 1625 N. French Dr., Hobbs, NM 88240 District II 811 S. First St., Artesia, NM 88210 District III 1000 Rio Brazos Road, Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505	State of New Mexico Energy Minerals and Natural Resources Department Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505	Page 1 of 6 Form C-144 Revised April 3, 2017 For temporary pits, below-grade tanks, and multi-well fluid management pits, submit to the appropriate NMOCD District Office. For permanent pits submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.
Proposed Alter	<u>Pit, Below-Grade Tank, or</u> native Method Permit or Closure F	Plan Application
Type of action: Below g Permit of Closure Modific Closure or proposed alternative metho	grade tank registration of a pit or proposed alternative method of a pit, below-grade tank, or proposed alternati ation to an existing permit/or registration plan only submitted for an existing permitted or d	DENIED ve method non-permitted pit, below-grade tank,
Instructions: Please submit one	application (Form C-144) per individual pit, below-	grade tank or alternative reauest
Please be advised that approval of this request does not a environment. Nor does approval relieve the operator of 1.	elieve the operator of lightlity should and it	
Operator:Advanced Wireless Communications,	LLCOGRID #:371710	
Address:5500 Rail Rd, Farmington, NM 8740	2	
Facility or well name:Hagood #001		
API Number:30-045-09406	OCD Permit Number:	
U/L or Qtr/Qtr 1050FNL,1040FEL Section 24	Township30NRange14W	County: Son Juan
Center of Proposed Design: Latitude 36.80400	85Longitude108.2555466	
Surface Owner: 💢 Federal 🗌 State 🗌 Private 🗌	Tribal Trust or Indian Allotment	NAD85
2.		
Pit: Subsection F, G or J of 19.15.17.11 NMA Temporary: Drilling Workover Permanent Emergency Cavitation P& Lined Unlined Liner type: Thickness String-Reinforced String-Reinforced String-Reinforced	No closure notice, no sam	w Chloride Drilling Fluid 🗌 yes 🗌 no er
Liner Seams: Welded Factory Other	Volume:bbl	Dimensions: Lx Wx D
Tank Construction material: Secondary containment with leak detection Visible sidewalls and liner Visible sidewalls and liner Liner type: Thickness	d:	rflow shut-off
Alternative Method:		
Submittal of an exception request is required. Exception	tions must be submitted to the Santa Fe Environment	al Bureau office for consideration of approval.
 5. Fencing: Subsection D of 19.15.17.11 NMAC (Apple Chain link, six feet in height, two strands of barbes institution or church) Four foot height, four strands of barbed wire even 	lies to permanent pits, temporary pits, and below-graded wire at top (Required if located within 1000 feet of	de tanks)
Alternate. Please specify		

L

L

.

.

Netting:	Subsection	E of 191	5 17 11 NM	C (Applies to per	rmanent pits and peri	manent open top tanks)

Screen Netting Other

Monthly inspections (If netting or screening is not physically feasible)

Signs: Subsection C of 19.15.17.11 NMAC

12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers

Signed in compliance with 19.15.16.8 NMAC

Variances and Exceptions:

7.

8.

Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance.

Please check a box if one or more of the following is requested, if not leave blank:

□ Variance(s): Requests must be submitted to the appropriate division district for consideration of approval.

Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.

<u>Siting Criteria (regarding permitting)</u>: 19.15.17.10 NMAC Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of acceptable source material are provided below. Siting criteria does not apply to drying pads or above-grade tanks.

General siting	
Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tank □ NM Office of the State Engineer - iWATERS database search; □ USGS; □ Data obtained from nearby wells	□ Yes □ No □ NA
Ground water is less than 50 feet below the bottom of a Temporary pit, permanent pit, or Multi-Well Fluid Management pit. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
 Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended. (Does not apply to below grade tanks) Written confirmation or verification from the municipality; Written approval obtained from the municipality 	🗌 Yes 🗌 No
 Within the area overlying a subsurface mine. (Does not apply to below grade tanks) Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division 	🗌 Yes 🗌 No
 Within an unstable area. (Does not apply to below grade tanks) Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 	🗌 Yes 🗌 No
Within a 100-year floodplain. (Does not apply to below grade tanks) - FEMA map	🗌 Yes 🗌 No
Below Grade Tanks	I.
 Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No
 Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption;. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No
Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)	
 Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.) Topographic map; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No
Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial	🗌 Yes 🗌 No
 Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 	
Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application.	🗌 Yes 🗌 No

NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site

Received by OCD: 8/16/2020 5:59:36 PM	Page 3 of 6
Within 100 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	Yes No
Temporary Pit Non-low chloride drilling fluid	
 Within 300 feet of a continuously flowing watercourse, or any other significant watercourse, or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site 	□ Yes □ No
 Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 	Yes No
 Within 500 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 1000 feet of any other fresh water well or spring, in the existence at the time of the initial application; NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No
 Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No
Permanent Pit or Multi-Well Fluid Management Pit	
 Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site 	Yes No
 Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 	
Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of initial application.	
- NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	🗌 Yes 🗌 No
 Within 500 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No
10. Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 N	MAC

Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached. Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC		
Previously Approved Design (attach copy of design) API Number: or Permit Number:		
Multi-Well Fluid Management Pit Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached. Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC A List of wells with approved application for permit to drill associated with the pit. Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC Hydrogeologic Data - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.10 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC		
Previously Approved Design (attach copy of design) API Number: or Permit Number:		

.

.

12.		
<u>Permanent Pits Permit Application Checklist</u> : Subsection B of 19.15.17.9 NMAC <i>Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the</i>	e documents are	
attached. Hydrogeologic Report - based upon the requirements of Paragraph (1) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Climatological Factors Assessment		
Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC		
 Dike Protection and Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC 		
Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC		
Quality Control/Quality Assurance Construction and Installation Plan Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC		
Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19,15,17,11 NMAC		
 Nuisance or Hazardous Odors, including H₂S, Prevention Plan Emergency Response Plan 		
 Oil Field Waste Stream Characterization Monitoring and Inspection Plan 		
Erosion Control Plan		
Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC		
^{13.} <u>Proposed Closure</u> : 19.15.17.13 NMAC Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan.		
Type: Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank Multi-well F	Fluid Management Pit	
Proposed Closure Method: D Waste Excavation and Removal		
 Waste Removal (Closed-loop systems only) On-site Closure Method (Only for temporary pits and closed-loop systems) 		
In-place Burial On-site Trench Burial		
Alternative Closure Method		
closure plan. Please indicate, by a check mark in the box, that the documents are attached. Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings) Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC		
15. <u>Siting Criteria (regarding on-site closure methods only)</u> : 19.15.17.10 NMAC Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable source material are provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. Please refer to 19.15.17.10 NMAC for guidance.		
 Ground water is less than 25 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells 	☐ Yes ☐ No ☐ NA	
Ground water is between 25-50 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	□ Yes □ No □ NA	
Ground water is more than 100 feet below the bottom of the buried waste NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells		
 Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No	
 Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 	🗌 Yes 🗌 No	
 Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application. NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site 	🗋 Yes 🗌 No	
Written confirmation or verification from the municipality; Written approval obtained from the municipality		
Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site		
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance		

•

Received by OCD: 8/16/2020 5:59:36 PM	Page 5 of 6	
 adopted pursuant to NMSA 1978, Section 3-27-3, as amended. Written confirmation or verification from the municipality; Written approval obtained from the municipality 	□ Yes □ No	
 Within the area overlying a subsurface mine. Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division 		
 Within an unstable area. Engineering measures incorporated into the design: NM Bureau of Geology & Minarel Bureau Model and the design of Geology & Minarel Bureau Model and the design of Geology & Minarel Bureau Model and the design of Geology & Minarel Bureau Model and the design of Geology & Minarel Bureau Model and the design of Geology & Minarel Bureau Model and the design of Geology & Minarel Bureau Model and the design of Geology & Minarel Bureau Model and the design of Geology & Minarel Bureau Model and the design of Geology & Minarel Bureau Model and the design of Geology & Minarel Bureau Model and the design of Geology & Minarel Bureau Model and the design of Geology & Minarel Bureau Model and the design of Geology & Minarel Bureau Model and the design of Geology & Minarel Bureau Minarel Bureau Model and the design of Geology & Minarel Bureau Model and the design of Geology & Minarel Bureau Model and the design of Geology & Minarel Bureau Model and the design of Geology & Minarel Bureau Model and the design of Geology & Minarel Bureau Model and the design of Geology & Minarel Bureau Model and the design of Geology & Minarel Bureau Model and the design of Geology & Minarel Bureau Model and the design of Geology & Minarel Bureau Model and the design of Geology & Minarel Bureau Model and the design of Geology & Minarel Bureau Model and the design of Geology & Minarel Bureau Model and the design of Geology & Minarel Bureau Model and the design of Geology & Minarel Bureau Model and the design of Geology & Minarel Bureau Model and the design of Geology & Minarel Bureau Model and the design of Geology & Minarel Bureau Minarel Bureau Model and the design of Geology & Minarel Bureau Model and the design of Geology & Minarel Bureau Model and the design of Geology & Minarel Bureau Model and the design of Geology & Minarel Bureau Model and the design of Geology & Minarel Bureau Model and the design of Geology & Minarel Bureau Model and the design of Geology & Minarel Bureau Model and the	Yes No	
Society; Topographic map Within a 100-year floodplain.	🗌 Yes 🗌 No	
- FEMA map	🗌 Yes 🗌 No	
 Inf. On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan by a check mark in the box, that the documents are attached. Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection E of 19.15.17.13 NMAC Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of Subsection K of 19.15.17.13 NMAC Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan - based upon the appropriate requirements of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards cannot soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC 	11 NMAC 15.17.11 NMAC	
17. Operator Application Certification:		
I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and belie		
Name (Print).		
Signature		
Date:		
e-mail address: Telephone:		
18. OCD Approval: Permit Application (including closure plan) Closure Plan (only) OCD Conditions (see attachment)		
OCD Representative Signature:		
Title		
OCD Permit Number: OCD Permit Number: Closure Report (required within 60 days of closure completion): 19.15.17.13 NMAC Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting the closure report. The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not complete this section of the form until an approved closure plan has been obtained and the closure activities have been completed.		
Closure Completion Date: 3/18/2020	0	
20. <u>Closure Method:</u> Waste Excavation and Removal □ On-Site Closure Method □ Alternative Closure Method □ Waste Removal (Closed-loop If different from approved plan, please explain. <i>Per approved MeElvan Closur Plan</i>	9 systems only)	
Closure Report Attachment Checklist: Instructions: Each of the following items must be attached to the closure report. Please india mark in the box, that the documents are attached. Proof of Closure Notice (surface owner and division) Proof of Deed Notice (required for on-site closure for private land only) Plot Plan (for on-site closures and temporary pits) Confirmation Sampling Analytical Results (if applicable) Waste Material Sampling Analytical Results (required for on-site closure) Disposal Facility Name and Permit Number		
 Soil Backfilling and Cover Installation Photos Re-vegetation Application Rates and Seeding Technique tout of Season, will reserved as soon as appropriat Site Reclamation (Photo Documentation) On-site Closure Location: Latitude 36.8040085 Longitude -108.2555466 NAD: □1927 	e on otherwise Clinected. (1983	

22. Operator Closure Certification:

I hereby certify that the information and attachments submitted with this closure report is true, accurate and complete to the best of my knowledge and belief. I also certify that the closure complies with all applicable closure requirements and conditions specified in the approved closure plan.

Name (Print):Krysten Moore Ti	tle:Member, VP
Signature: Alla alla	Date:4/6/2020
e-mail address:krysten@advancedwirelessllc.com	Telephone:505-486-0045