## State of New Mexico Energy Minerals and Natural Resources

Form C-144 July 21, 2008

<u>District II</u> 1301 W Grand Ave , Artesia, NM 88210 Department
Oil Conservation Division
1220 South St. Francis Dr.
Santa Fe, NM 87505

For temporary pits, closed-loop sytems, and below-grade tanks, submit to the appropriate NMOCD District Office

<u>District III</u> 1000 Rio Brazos Rd , Aztec, NM 87410

For permanent pits and exceptions submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office

District IV 1220 S St Francis Dr., Santa Fe, NM 87505

Pit, Closed-Loop System, Below-Grade Tank, or
Pit, Closed-Loop System, Below-Grade Tank, or Proposed Alternative Method Permit or Closure Plan Application  Type of action    X  Permit of a pit, closed-loop system, below-grade tank, or proposed alternative method RECEIVED
/
Closure of a pit, closed-loop system, below-grade tank, or proposed alternative method MAR 20 1388
Modification to an existing permit  OIL CONS DIV. DIST.
Closure plan only submitted for an existing permitted or non-permitted pit, closed toop system, below-grade tank, or proposed alternative method
Instructions: Please submit one application (Form C-144) per individual pit, closed-loop system, below-grade tank or alternative refires
Please be advised that approval of this request does not relieve the operator of liability should operations result in pollution of surface water, ground water or the environment. Nor does approval relieve the operator of its responsibility to comply with any other applicable governmental authority's rules, regulations or ordinances
1
Operator: Burlington Resources Oil & Gas Company, LP  OGRID#: 14538
Address PO Box 4289, Farmington, NM 87499
Facility or well name. SAN JUAN 28-6 UNIT 460S  API Number 30-039-31021 OCD Permit Number
U/L or Qtr/Qtr. N(SE/SW) Section: 16 Township: 28N Range. 6W County Rio Arriba
Center of Proposed Design: Latitude: 36.65611 °N Longitude: 107.47562 °W NAD. 1927 X 1983
Surface Owner X Federal State Private Tribal Trust or Indian Allotment
Pit: Subsection F or G of 19 15 17 11 NMAC  Temporary
Below-grade tank: Subsection I of 19 15 17 11 NMAC  Volume
Alternative Method:  Submittal of an exception request is required Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval

Fencing: Subsection D of 19 15 17 11 NMAC (Applies to permanent pit, temporary pits, and below-grade tanks)  Chain link, six feet in height, two strands of barbed wire at top (Required if located within 1000 feet of a permanent residence, school, hospital, institution or church)  Four foot height, four strands of barbed wire evenly spaced between one and four feet  Alternate Please specify				
Netting: Subsection E of 19 15 17 11 NMAC (Applies to permanent pits and permanent open top tanks)  Screen Netting Other  Monthly inspections (If netting or screening is not physically feasible)				
Signs: Subsection C of 19 15 17 11 NMAC  12" X 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers  X Signed in compliance with 19 15 3 103 NMAC				
Administrative Approvals and Exceptions:  Justifications and/or demonstrations of equivalency are required. Please refer to 19 15 17 NMAC for guidance.  Please check a box if one or more of the following is requested, if not leave blank:  Administrative approval(s). Requests must be submitted to the appropriate division district of the Santa Fe Environmental Bureau office for consideration of approval.  Exception(s). Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.	ideration of ap	proval		
Siting Criteria (regarding permitting) 19 15 17 10 NMAC Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of acceptable source material are provided below. Requests regarding changes to certain siting criteria may require administrative approval from the appropriate district office or may be considered an exception which must be submitted to the Santa Fe Environmental Bureau Office for consideration of approval. Applicant must attach justification for request. Please refer to 19.15.17.10 NMAC for guidance. Siting criteria does not apply to drying pads or above grade-tanks associated with a closed-loop system.				
Ground water is less than 50 feet below the bottom of the temporary pit, permanent pit, or below-grade tank.  - NM Office of the State Engineer - iWATERS database search, USGS, Data obtained from nearby wells	Yes	No		
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark).  - Topographic map, Visual inspection (certification) of the proposed site	Yes	□No		
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.	Yes	No		
(Applies to temporary, emergency, or cavitation pits and below-grade tanks)  - Visual inspection (certification) of the proposed site, Aerial photo, Satellite image	NA			
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.  (Applied to permanent pits)  - Visual inspection (certification) of the proposed site, Aerial photo, Satellite image	Yes NA	No		
Within 500 horizonal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application.	Yes	No		
- NM Office of the State Engineer - 1WATERS database search, Visual inspection (certification) of the proposed site				
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended  - Written confirmation or verification from the municipality, Written approval obtained from the municipality	Yes	∐No		
Within 500 feet of a wetland.  - US Fish and Wildlife Wetland Identification map, Topographic map, Visual inspection (certification) of the proposed site	Yes	No		
Within the area overlying a subsurface mine.  - Written confirmation or verification or map from the NM EMNRD - Mining and Mineral Division	Yes	No		
<ul> <li>Within an unstable area.</li> <li>Engineering measures incorporated into the design, NM Bureau of Geology &amp; Mineral Resources, USGS, NM Geological Society, Topographic map</li> </ul>	Yes	No		
Within a 100-year floodplain	Yes	No		

Temporary Pits, Emergency Pits and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19 15 17 9 NMAC
Instructions Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached
Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19 15 17 9 NMAC
Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19 15 17 9
Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19 15 17 10 NMAC
Design Plan - based upon the appropriate requirements of 19 15 17 11 NMAC
Operating and Maintenance Plan - based upon the appropriate requirements of 19 15 17 12 NMAC
Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of
19 15 17 9 NMAC and 19 15 17 13 NMAC
Previously Approved Design (attach copy of design) API or Permit
Closed-loop Systems Permit Application Attachment Checklist: Subsection B of 19 15 17 9 NMAC Instructions Each of the following items must be attached to the application Please indicate, by a check mark in the box, that the documents are attached Geologic and Hydrogeologic Data (only for on-site closure) - based upon the requirements of Paragraph (3) of Subsection B of 19 15 17 9
Siting Criteria Compliance Demonstrations (only for on-site closure) - based upon the appropriate requirements of 19 15 17 10 NMAC
X   Design Plan - based upon the appropriate requirements of 19 15 17 11 NMAC
X Operating and Maintenance Plan - based upon the appropriate requirements of 19 15 17 12 NMAC
X Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19 15 17 9 NMAC and 19 15 17 13 NMAC
Previously Approved Design (attach copy of design)  API
Previously Approved Operating and Maintenance Plan API
13
Permanent Pits Permit Application Checklist: Subsection B of 19 15 17 9 NMAC  Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached.
Hydrogeologic Report - based upon the requirements of Paragraph (I) of Subsection B of 19 15 17 9 NMAC
Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19 15 17 10 NMAC
Climatological Factors Assessment
Certified Engineering Design Plans - based upon the appropriate requirements of 19 15 17 11 NMAC
Dike Protection and Structural Integrity Design based upon the appropriate requirements of 19 15 17 11 NMAC
Leak Detection Design - based upon the appropriate requirements of 19 15 17 11 NMAC
Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19 15 17 11 NMAC
Quality Control/Quality Assurance Construction and Installation Plan
Operating and Maintenance Plan - based upon the appropriate requirements of 19 15 17 12 NMAC
Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19 15 17 11 NMAC
Nuisance or Hazardous Odors, including H2S, Prevention Plan
☐ Emergency Response Plan ☐ Oil Field Waste Stream Characterization
Monttoring and Inspection Plan
Frosion Control Plan
Closure Plan - based upon the appropriate requirements of Subsection C of 19 15 17 9 NMAC and 19 15 17 13 NMAC
Proposed Closure: 19 15 17 13 NMAC Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan.
Type Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank X Closed-loop System
Alternative
Proposed Closure Method Waste Excavation and Removal
X Waste Removal (Closed-loop systems only)
On-site Closure Method (only for temporary pits and closed-loop systems)
In-place Burial On-site Trench
Alternative Closure Method (Exceptions must be submitted to the Santa Fe Environmental Bureau for consideration)
15
Waste Excavation and Removal Closure Plan Checklist: (19 15 17 13 NMAC) Instructions: Each of the following items must be attached to the closure plan.
Please indicate, by a check mark in the box, that the documents are attached.
Protocols and Procedures - based upon the appropriate requirements of 19 15 17 13 NMAC
Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection F of 19 15 17 13 NMAC
Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings)  Seel Beel-Fill and Court Desum Specifications, based upon the consequents of Subsection II of 10 15 17 13 NMAC
Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19 15 17 13 NMAC
Re-vegetation Plan - based upon the appropriate requirements of Subsection 1 of 19 15 17 13 NMAC
Site Reclamation Plan - based upon the appropriate requirements of Subsection G of 19 15 17 13 NMAC

Form C-144 Oil Conservation Division Page 3 of 5

Waste Removal Closure For Closed-loop Systems That Utilize Above Ground Steel Instructions Please identify the facility or facilities for the disposal of liquids, drilling				
facilities are required	•	-		
	•	NM-01-0011 / NM-01-00	10B	
	Disposal Facility Permit #		<del></del> .	
Will any of the proposed closed-loop system operations and associated activities  Yes (If yes, please provide the information No	s occur on or in areas that v	vill not be used for future s	service and	
Required for impacted areas which will not be used for future service and operations  Soil Backfill and Cover Design Specification - based upon the appropria	te requirements of Subsect	on H of 19 15 17 13 NMA	С	
Re-vegetation Plan - based upon the appropriate requirements of Subsect				
Site Reclamation Plan - based upon the appropriate requirements of Sub-	section G of 19 15 17 13 N	MAC		
17 Siting Criteria (Regarding on-site closure methods only: 19 15 17 10 NMAC Instructions Each siting criteria requires a demonstration of compliance in the closure plan Recommendations of acceptable source material are provided below Requests regarding changes to certain string criteria may require administrative approval from the appropriate district office or may be considered an exception which must be submitted to the Santa Fe Environmental Bureau office for consideration of approval Justifications and/or demonstrations of equivalency are required Please refer to 19 15 17 10 NMAC for guidance				
Ground water is less than 50 feet below the bottom of the buried waste			Yes No	
- NM Office of the State Engineer - IWATERS database search, USGS Data obtain	ned from nearby wells		∐N/A	
Ground water is between 50 and 100 feet below the bottom of the buried waste			Yes No	
- NM Office of the State Engineer - IWATERS database search, USGS, Data obtain	ned from nearby wells		∐N/A	
Ground water is more than 100 feet below the bottom of the buried waste			Yes No	
- NM Office of the State Engineer - 1WATERS database search, USGS, Data obtain	ned from nearby wells		□N/A	
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other signification (measured from the ordinary high-water mark)	int watercourse or lakebed, sii	nkhole, or playa lake	Yes No	
- Topographic map, Visual inspection (certification) of the proposed site				
Within 300 feet from a permanent residence, school, hospital, institution, or church in ex  - Visual inspection (certification) of the proposed site, Aerial photo, satellite image	sistence at the time of initial a	pplication	∐Yes ∐No	
Within 500 horizontal feet of a private, domestic fresh water well or spring that less that purposes, or within 1000 horizontal fee of any other fresh water well or spring, in existe - NM Office of the State Engineer - iWATERS database, Visual inspection (certification)	nce at the time of the initial ap		YesNo	
Within incorporated municipal boundaries or within a defined municipal fresh water well pursuant to NMSA 1978, Section 3-27-3, as amended  - Written confirmation or verification from the municipality, Written approval obtain		ipal ordinance adopted	Yes No	
Within 500 feet of a wetland - US Fish and Wildlife Wetland Identification map, Topographic map, Visual inspe		posed site	Yes No	
Within the area overlying a subsurface mine			Yes No	
- Written confirantion or verification or map from the NM EMNRD-Mining and Mi	neral Division			
Within an unstable area	LIGOG NIM	0.1.10.4	∐Yes ∐No	
<ul> <li>Engineering measures incorporated into the design, NM Bureau of Geology &amp; Mir Topographic map</li> </ul>	ieral Resources, USGS, NM	Geological Society,		
Within a 100-year floodplain - FEMA map			Yes No	
18 On-Site Closure Plan Checklist: (19 15 17 13 NMAC) Instructions: Each of the Checklist (19 15 17 13 NMAC) Instructions:	of the following items mu	st bee attached to the closu	are plan. Please indicate.	
by a check mark in the box, that the documents are attached.	- , , , , , , , , , , , , , , , , , , ,		-	
Siting Criteria Compliance Demonstrations - based upon the appropriate	requirements of 19 15 17	10 NMAC		
Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection F of 19 15 17 13 NMAC				
Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of 19 15 17 11 NMAC				
Construction/Design Plan of Temporary Pit (for in place burial of a drying pad) - based upon the appropriate requirements of 19 15 17 11 NMAC				
Protocols and Procedures - based upon the appropriate requirements of 19 15 17 13 NMAC  Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection F of 19 15 17 13 NMAC				
Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection F of 19 15 17 13 NMAC  Waste Material Sampling Plan - based upon the appropriate requirements of Subsection F of 19 15 17 13 NMAC				
Waste Material Sampling Plan - based upon the appropriate requirements of Subsection F of 1913 1713 NMAC   Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards cannot be achieved)				
Soil Cover Design - based upon the appropriate requirements of Subsect	-		amor oc acmeved)	
Re-vegetation Plan - based upon the appropriate requirements of Subsection				
Site Reclamation Plan - based upon the appropriate requirements of Subsection G of 19 15 17 13 NMAC				

19
Operator Application Certification:
I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and belief
Name (Print)  Jamie Goodwin  Title  Regulatory Technician  Signature  Date  Date
100000000000000000000000000000000000000
e-mail address / Jamie L Goodwin@conocophillips com Telephone 505-326-99784
20
OCD Approval: Permit Application (including closure plan) Closure Plan (only) OCD Conditions (see attachment)
OCD Representative Signature:
OCD Representative Signature:  Approval Date: 3/1///
Title: OCD Permit Number:
21  Closure Report (required within 60 days of closure completion): Subsection K of 19 15 17 13 NMAC
Instructions Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting the closure report. The closure
report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not complete this section of the form until an
approved closure plan has been obtained and the closure activities have been completed
Closure Completion Date:
22
Closure Method:
Waste Excavation and Removal On-site Closure Method Alternative Closure Method Waste Removal (Closed-loop systems only)
If different from approved plan, please explain
23
Closure Report Regarding Waste Removal Closure For Closed-loop Systems That Utilize Above Ground Steel Tanks or Haul-off Bins Only:
Instructions: Please identify the facility or facilities for where the liquids, drilling fluids and drill cuttings were disposed. Use attachment if more than two facilities were utilized.
Disposal Facility Name Disposal Facility Permit Number
Disposal Facility Name Disposal Facility Permit Number
Were the closed-loop system operations and associated activities performed on or in areas that will not be used for future service and operations?
Yes (If yes, please demonstrate compliane to the items below)
Required for impacted areas which will not be used for future service and operations
Site Reclamation (Photo Documentation)  Soil Backfilling and Cover Installation
Re-vegetation Application Rates and Seeding Technique
24 <u>Closure Report Attachment Checklist:</u> Instructions. Each of the following items must be attached to the closure report. Please indicate, by a check mark in
the box, that the documents are attached.
Proof of Closure Notice (surface owner and division)
Proof of Deed Notice (required for on-site closure)
Plot Plan (for on-site closures and temporary pits)
Confirmation Sampling Analytical Results (if applicable)
Waste Material Sampling Analytical Results (if applicable)
Disposal Facility Name and Permit Number
Soil Backfilling and Cover Installation
Re-vegetation Application Rates and Seeding Technique Site Reclamation (Photo Documentation)
On-site Closure Location Latitude Longitude NAD 1927 1983
Constitution Latitude Longitude NAD 1927 1963
25
Operator Closure Certification:
I hereby certify that the mformation and attachments submitted with this closure report is ture, accurate and complete to the best of my knowledge and belief. I also certify that
the closure complies with all applicable closure requirements and conditions specified in the approved closure plan
Name (Print) Title
Signature Date
Signature Date
e-mail address - Telephone

# Burlington Resources Oil & Gas Company, LP

## **Closed Loop Design:**

The closed loop design will not incorporate a temporary pit or below grade tank. The plan will utilize an above grade tank suitable for holding the cuttings and fluids generated during drilling operations. The volume of the tank shall be of a sufficient volume to maintain an adequate free board for periodic removal and disposal of cuttings and fluids.

Burlington Resources Oil & Gas Company, LP may incorporate the use of a 20 mil, string reinforced, LLDPE liner with factory welded seams to line the drying pad in order to minimize the volume of fluids to be disposed of. The drying pad will be designed to prevent contamination of fresh water, protect public health and the environment, and have sumps to facilitate the collection of liquids derived from drilling cuttings, as specified per subsection H of 19 15 17 11. The cuttings pad will be constructed above grade and containment will be through the use of earthen berms of sufficient height to contain the cuttings and prevent run-off of surface water or fluids. The drying pad area will replace the area of the drill site previously designated for the reserve pit. It will be signed in compliance with 19.15 3 103 NMAC. Frac tanks will be utilized on site for fresh water storage.

### **Closed Loop Operations and Maintenance:**

The closed loop system will be operated and maintained for solids and liquid containment to prevent ground water contamination as follows

- 1 Any free liquids will be recovered and reused or disposed of at the Basin Disposal Facility (Permit # NM-01-005) or JFJ Landfarm % Industrial Ecosystem Inc. (Permit # NM- 01-0010B) Reuse may include the relocating of liquids to be used in other permitted drilling operations
- 2 Drill solids will be recovered from location and hauled to Envirotech (Permit #NM-01-0011) or JFJ Landfarm % Industrial Ecosystem Inc. (Permit # NM-01-0010B) periodically as required to maintain a safe free board in the cuttings tank. No onsite trench burial of cuttings will occur.
- In the event a drying pad is utilized, the cuttings will be picked up and transported to Basin Disposal Facility (Permit #NM-01-005) or JFJ Landfarm % Industrial Ecosystem Inc. (Permit # NM-01-0010B) The liner will be disposed of at the San Juan County Landfill located on CR 3100 The drying pad will be closed within 6 months from the date that the drilling rig is released Berms constructed from native materials will be bladed on site to the location's contour
- 4 Any drilling materials or trash will be stored and disposed of appropriately
- The NMOCD will be notified within 48 hours of the discovery of compromised integrity of the closed loop containment. Any required repairs will commence immediately

### **Closed Loop Closure Plan:**

Upon completion of the drilling operations, all solids and liquids will be removed and disposed of to Envirotech (Permit #NM-01-0011) and/or Basin Disposal Facility (Permit #NM-01-005) and/or JFJ Landfarm % Industrial Ecosystem Inc. (Permit #NM-01-0010B) Equipment shall also be removed from location. In the event a drying pad is utilized, the solids contained on the pad shall remain on site to allow sufficient drying and will then be transported to Envirotech (Permit #NM-01-0011) or JFJ Landfarm % Industrial Ecosystem Inc. (Permit #NM-01-0010B) within 6 months from the date that the drilling rig is released

After the drying pad is removed the surface below will be visually inspected for any contamination. If contamination is discovered a five point composite sample will be taken of the drying pad area using sampling tools and all samples tested per Subsection B of 19.15.17.13(B)(1)(b). In the event that the criteria are not met, all contents will be handled per Subparagraph (a) of Paragraph (1) of Subsection B of 19.15.17.13 i.e., Dig and haul

Components	Tests Method	Limit (mg/Kg)
Benzene	EPA SW-846 8021B or 8260B	0 2
BTEX	EPA SW-846 8021B or 8260B	50
TPH	EPA SW-846 418.1	2500
GRO/DRO	EPA SW-846 8015M	500
Chlorides	EPA 300 1	500

- Re-contouring of location will match fit, shape, line, form and texture of the surrounding Re-shaping will include drainage control, prevent ponding, and prevent erosion. Natural drainages will be unimpeded and water bars and/or silt traps will be place in areas where needed to prevent erosion on a large scale. Final re-contour shall have a uniform appearance with smooth surface, fitting the natural landscape.
- 4 Notification will be sent to OCD when the reclaimed area is seeded
- BR shall seed the disturbed areas the first growing season after the operator closes the drying pad. Seeding will be accomplished via drilling on the contour whenever practical or by other division-approved methods. BLM or Forest Service stipulated seed mixes will used on federal lands. Vegetative cover will equal 70% of the native perennial vegetative cover (un-impacted) consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintain that cover through two successive growing seasons. Repeat seeding or planting will be continued until successful vegetative growth occurs.

Туре	Variety or Cultivator	PLS/A
Western wheatgrass	Arrıba	3 0
Indian ricegrass	Paloma or Rımrock	3 0
Slender wheatgrass	San Luis	20
Crested wheatgrass	Hy-crest	3 0
Bottlebrush Squirreltail	Unknown	20
Four-wing Saltbrush	Delar	25

Species shall be planted in pounds of pure live seed per acre: Present Pure Live Seed (PLS) = Purity X Germination/100 Two lots of seed can be compared on the basis of PLS as follows:

Source No One (poor quality) Source No two (better quality) 80 percent Purity 50 percent Purity Germination 63 percent Germination 40 percent Percent PLS 20 percent Percent PLS 50 percent 5 lb. bulk seed required to make 2 lb. bulk seed required to make

1 lb. PLS 1 lb. PLS