UNITED STATES DEPARTMENT OF THE INTERIOR



BUREAU OF LAND MANAGEMENT	ç	EP 13 2011
Sundry Notices and Reports on Wells		ington Field Office
1. Type of Well GAS 2. Name of Operator BURLINGTON RESCURCES OIL & GAS COMPANY LP 3. Address & Phone No. of Operator	^З иг <u></u> эаи с	SF-079527 If Indian, All. or Tribe Name
2. Name of Operator BURLINGTON	7.	Unit Agreement Name SAN JUAN 27-4 UNIT
RESCURCES OIL & GAS COMPANY LP	— 8.	Well Name & Number SAN JUAN 27-4 UNIT 150M
PO Box 4289, Farmington, NM 87499 (505) 326-9700	9.	API Well No.
4. Location of Well, Footage, Sec., T, R, M		30-039-30926
Surface: Unit F (SE/NW), 1512' FNL & 1503' FWL, Section 36, T27N, R4W, NMPN	10. M	Field and Pool BLANCO MV / BASIN DK
Bottom: Unit D (NW/NW), 1020' FNL & 710' FWL, Section 36, T27N, R4W, NMPN	M 11.	County and State Rio Arriba, NM
12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT,	OTHER I	DATA
Type of Submission Type of Action Notice of Intent Abandonment Change of Plans Recompletion New Construction	<u>X</u>	Other – Casing Report
X Subsequent Report Plugging Non-Routine Fracturing Casing Repair Water Shut off Altering Casing Conversion to Injection		
13. Describe Proposed or Completed Operations 08/14/11 MIRU AWS 673. NU BOPE. PT csg to 600#/30min @ 15:45hrs on 08/15/11. Test - OK. RIH w/ 8 3 DO cmt @ 236'. Drilled to 4447' - TD reached 08/20/11. Circ. hole & RIH w/ 105jts, 7", 23#, J-55, ST&C cas RU to cmt. 1st stage: Pre-flushed w/ 10 bbls GW, 2bbls FW. Pumped scavenger w/ 19sx(57cf-10bbls=3.02yl celloflake, 5pps LCM-1, 0.4% FL-52, 0.4% SMS & 8% bentonite. Lead w/ 8sx(17cf-3bbls=2.13yld) Premium 5pps LCM-1, 0.4% FL-52, 0.4% SMS & 8% bentonite. Tail w/ 60sx(82cf-15bbls=1.38yld) Type III cmt w/ 1shut dwn. Dropped plug & displaced w/ 30bbls FW plus 143bbls MW. Bump plug. Plugged down @ 09:05hr WOC. 2nd stage: Pre-flushed w/ 10bbls FW, 10bbls GW, & 10bbls FW. Pumped scavenger w/ 19sx(57cf-10bc). 25pps celloflake, 5pps LCM-1, 0.4% FL-52, 0.4% SMS & 8% bentonite. Lead w/ 485sx(1033cf-184bbls=2. celloflake, 5pps LCM-1, 0.4% FL-52, 8% bentonite, & 0.4% SMS. Displaced w/ 154bbls FW. Bumped plug & Plug dwn @ 14:44hrs on 08/21/11. RD cmt. WOC. 08/22/11 RIH w/ 6 1/4" bit. Drill out ST @ 3918'. PT 7"csg to 1500#30min @ 06:00hrs on 08/22/11. Test-OK reached on 08/29/11. Circ. hole & RIH w/ 203jts, (BT&C 28jts, LT&C 175jts), 4 1/2", 11.6#, L-80 csg set @ MW, pumped 170bbls MW w/ N2, 10bbls FW w/ N2, 10bbls FW. Pumped scavenger 9 w/ 0.25pps celloflake, 0.3% CD-32, 6.25pps LCM-1, 0.1% FL-52. Tail w/ 296sx(586cf-104bbls=1.98yld) Pred D.3% CD-32, 6.25pps LCM-1, 0.1% FL-52. Tail w/ Dropped plug & displaced w/ 134bbl @ 03:39hrs on 09/02/11. RD cmt. WOC. ND BOPE. NU WH. RD RR @ 19:30hrs on 09/03/11.	sing set @ 44 (d) Premium in Lite w/ 3% % CaCl, 0.25 s 08/21/11. Q bbls=3.02yld .13yld) Prem & close ST to L. Drilled w/ 6 8635'. RU to sx(28cf-5bbl mium Lite w	36' w/ stage tool set @ 3918'. Lite w/ 3% CaCl, 0.25pps CaCl, 0.25 pps celloflake, 5 pps celloflake, & 0.2% FL-52. Circ. 8bbls cmt to surface.) Premium Lite w/ 3% CaCl, ium Lite w/ 3%CaCl, 0.25pps tol. 50bbls cmt to surface. 6 1/4" bit to 8636' TD to cmt. Pre-flushed w/ 25bbls ls=3.10yld) Premium Lite / 0.25pps celloflake,
PT will be conducted by Completion Rig. Results & TOC will appear on next report.		
14. I hereby certify that the fovegoing is true and correct. Signed Marie E. Jaramillo Title: Staff F		Technician Date 09/13/1
(This space for Federal or State Office use) APPROVED BY Title		SEP 1 4 2011
CONDITION OF APROVAL, if any: Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make any department or agency from the United States any false figures or fraudulent statements or representations as to any matter within its jurisdiction.		INGTON/FIELD OFFICE