

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
OMB NO. 1004-0137
Expires July 31, 2010

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to re-enter an
abandoned well. Use Form 3160-3 (APD) for such proposals.

RECEIVED

SUBMIT IN TRIPLICATE - Other instructions on page 2

1 Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2 Name of Operator

XTO ENERGY INC.

3a Address

382 CR 3100 AZTEC, NM 87410

3b. Phone No (include area code)

505-333-3100

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1945' FSL & 1945' FEL NWSE SEC. 14 (J) - T26N-R6W N.M.P.M.

5 Lease Serial No.

NMM-03554

6. If Indian, Allottee or Tribe Name

N/A

7 If Unit or CA/Agreement, Name and/or No

N/A

8 Well Name and No

BREECHER NOV 29 '11

9 API Well No

30-039-30661

10. Field and Pool, or Exploratory Area

BASIN DK/BASIN MY/BASIN MC

11 County or Parish, State

RIO ARRIBA NM

12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☒ Notice of Intent

☐ Subsequent Report

☐ Final Abandonment Notice

BP

TYPE OF ACTION

☐ Acidize

☐ Alter Casing

☐ Casing Repair

☐ Change Plans

☐ Convert to Injection

☐ Deepen

☐ Fracture Treat

☐ New Construction

☐ Plug and Abandon

☐ Plug Back

☐ Production (Start/Resume)

☐ Reclamation

☐ Recomplete

☐ Temporarily Abandon

☐ Water Disposal

☐ Water Shut-Off

☐ Well Integrity

☒ Other REVISED

SURFACE CASING

13 Describe Proposed or Completed Operation (clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recompleat horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompleat in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the final site is ready for final inspection.)

XTO Energy Inc. deepened the surface casing to 500' for the above mentioned well.

Please see attached revised surface casing/cement program.

BLM'S APPROVAL OR ACCEPTANCE OF THIS
ACTION DOES NOT RELIEVE THE LESSEE AND
OPERATOR FROM OBTAINING ANY OTHER
AUTHORIZATION REQUIRED FOR OPERATIONS
ON FEDERAL AND INDIAN LANDS

14 I hereby certify that the foregoing is true and correct
Name (Printed/Typed)

LORRI D. BINGHAM

Title REGULATORY ANALYST

Signature

Date 11/18/11

THIS SPACE FOR FEDERAL OR STATE OFFICE USE

Approved by

Troy L. Salyers

Title

PE

Date

11/23/2011

Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Office

FFO

Title 18 U.S.C. Section 1001, and Title 43 U.S.C. Section 1212, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

NOV 21 2011

Breech C #323F
API #30-039-30661
Sec. 14 (J), T26N, R6W
Rio Arriba County New Mexico

2. CASING PROGRAM:

Interval	Length	Wt	Gr	Cplg	Coll Rating (psi)	Burst Rating (psi)	Jt Str (M-lbs)	ID (in)	Drift (in)	SF Coll	SF Burst	SF Ter
0'-500'	500'	24.0#	J-55	ST&C	1370	2950	244	8.097	7.972	7.950	17.13	28.2

Lead: 370 sx of Class G cement w/1% CaCl₂ + 0.125 pps Poly-ElFalke + 4/10 HR 339 Fluid
 Loss Additive.
 (mixed @ 15.8 ppg, yield – 1.17 ft³/sk, mix wtr. – 5.00 gal/sk)