

Submit 1 Copy To Appropriate District Office
District I - (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II - (575) 748-1283
811 S. First St., Artesia, NM 88210
District III - (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV - (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

Form C-103
Revised August 1, 2011

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS)		WELL API NO. 30-039-25302
1. Type of Well: Oil Well <input checked="" type="checkbox"/> Gas Well <input type="checkbox"/> Other <input type="checkbox"/>		5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
2. Name of Operator Nadel & Gussman Rockies LLC		6. State Oil & Gas Lease No.
3. Address of Operator 621 17 TH Street, Suite 1301, Denver, CO 80293		7. Lease Name or Unit Agreement Name Trix
4. Well Location Unit Letter <u>M</u> : <u>790'</u> feet from the <u>South</u> line and <u>990'</u> feet from the <u>West</u> line Section <u>5</u> Township <u>26N</u> Range <u>2W</u> NMPM Rio Arriba County		8. Well Number #2
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 7107' GR		9. OGRID Number 239353
		10. Pool name or Wildcat Gavilan Mancos

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input checked="" type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	P AND A <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	MULTIPLE COMPL <input type="checkbox"/>	CASING/CEMENT JOB <input type="checkbox"/>	
DOWNHOLE COMMINGLE <input type="checkbox"/>			
OTHER: <input type="checkbox"/>		OTHER: <input type="checkbox"/>	

RCVD DEC 27 '11
OIL CONS. DIV.

DIST. 3

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

Nadel & Gussman Rockies LLC is proposing to plug and abandon the subject well. Attached are wellbore diagrams of the current well condition and the post abandonment condition.

A total of 5 plugs are proposed to be set as follows:

Plug #1 6950-6758 40 sx Class B
Plug #2 6000-5900 23 sx Class B
Plug #3 5490-5390 23 sx Class B
Plug #4 3659-3262 108 sx Class B
Plug #5 1777-1677. Perforate at 1777' Set cement retainer at 1727 59 sx total, 22 inside and 37 outside Class B

* run CBL and submit it for review prior to cementing and approval

Spud Date:

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

Hugo Cartaya

TITLE

Operations Manager

DATE 12/20/11

Type or print name

Hugo Cartaya

E-mail address:

hcartaya@naguss.com

PHONE:

303-296-2771

For State Use Only

APPROVED BY:

Deputy Oil & Gas Inspector

TITLE

Deputy Oil & Gas Inspector,
District #3

DATE

1-23-12

Conditions of Approval (if any):

AV

Trix #2

Proposed Plugback for water well

Gavilan Mancos

790' FSL, 990' FWL, Section 5, T-26-N, R-2-W, Rio Arriba County, NM

Lat: _____ / Lat: _____ API #30-39-25302

Today's Date: 11/3/11

Spud: 8/3/93

Completion: 6/18/95

Elevation: 7105' GR

14.25" hole

10.75", 40.5#, K-55 Casing set @ 325'
Cement with 413 cf, circulate to surface

Nacimiento @ 1727' *est

Cmt Retainer @ 1727'

Perforate @ 1777'
TOC @ 2426' (Calc, 75%)

Plug #5: 1777' – 1677'
Class B cement, 59 sxs:
22 inside and 37 outside

Ojo Alamo @ 3282'

Plug #4: 3659' – 3232'
Class B cement, 108 sxs

Kirtland @ 3412'

Fruitland @ 3450'

Pictured Cliffs @ 3609'

Plug #3: 5490' – 5390'
Class B cement, 23 sxs

Mesaverde @ 5440'

Mesaverde Perforations:
5827' – 5854, squeezed 8/23/06

Mancos @ 5950'

TOC @ DV Tool per sundry

DV Tool @ 6005'
Cmt w/898 cf

Plug #2: 6000' – 5900'
Class B cement, 23 sxs

9-7/8" Hole

5" TOL @ 6808'

Set CR @ 6950'

Plug #1: 6950' – 6758'
Class B cement, 40 sxs

Gallup @ 6950'

7-5/8" 26#/29.7#, K-55 /N-80 Casing
set @ 6950'
Cement with 289 cf
Gallup Perforations: 7000' – 7244'

6.75" Hole

5", 23# Flush Joint Liner @ 7344'
Cemented with 73 cf

TD 7345'
COTD @ 7218'

Trix #2

Current

Gavilan Mancos

790' FSL, 990' FWL, Section 5, T-26-N, R-2-W, Rio Arriba County, NM

Lat: _____ / Lat: _____ API #30-39-25302

Today's Date: 11/3/11

Spud: 8/3/93

Completion: 6/18/95

Elevation: 7105' GR

14.25" hole

10.75", 40.5#, K-55 Casing set @ 325'
Cement with 413 cf, circulate to surface

Nacimiento @ 1727' *est

TOC @ 2806' (Calc, 75%)

Ojo Alamo @ 3282'

2-3/8" tubing at 7184'
(4.7#, J-55, SN 7159', tubing anchor @
6602' with rods and pump)

Kirtland @ 3412'

Fruitland @ 3450'

Pictured Cliffs @ 3609'

Mesaverde @ 5440'

Mesaverde Perforations:
5827' - 5854, squeezed 8/23/06

Mancos @ 5950'

TOC @ DV Tool per sundry

DV Tool @ 6005'
Cmt w/898 cf

5" TOL @ 6808'

TOC @ liner top per sundry

Gallup @ 6950'

9-7/8" Hole

7-5/8" 26#/29.7#, K-55 /N-80 Casing
set @ 6950'
Cement with 289 cf

Gallup Perforations: 7000' - 7244'

6.75" Hole

5", 23# Flush Joint Liner @ 7344'
Cemented with 73 cf

TD 7345'
COTD @ 7218'